



# CONTEXT

## commands

# FN



# **ConTEXt**

## **commands**

**August 10, 1998**  
**english**



`\about{...}[ref]`

... *text*

`\adaptlayout[...][...=...]`

... *number*  
height *dimension* max  
lines *number*

`\adding[...]`

... small medium big

`\appendix[ref,...]{...}`

... *text*

`\arg{...}`

... *text*

`\at{.1.}{.2.}[ref]`

.1. *text*

`\background`

`\blackrule[...=...]`

... see `\setupblackrules`

`\blackrules[...=...]`

... see `\setupblackrules`

`\blank[...]`

... *n\*small n\*medium n\*big nowhite backward white disable force reset line halflines formula fixed flexible*

`\bookmark[.1.]{.2.}`

.1. *name*

`\but[ref]`

`\button[...==...]{...}[ref,...]`

`... see \setupbuttons`  
`... text`

`\Cap{...}`

`... text`

`\CAP{...}`

`... text`

`\Caps{...}`

`... text`

`\chapter[ref,...]{...}`

`... text`

`\character{...}`

`... number`

`\Character{...}`

`... number`

`\Characters{...}`

`... number`

`\characters{...}`

`... number`

`\chem{.1.}{.2.}{.3.}`

`.1. text`  
`.2. text`  
`.3. text`

`\clonefield[.1.][...2.][.3.][...4.]`

`.1. name`  
`.2. name`  
`.3. name`  
`.4. name`

`\color[...]`

... *text*

`\column`

`\comment[.1.][...,...=,...]{.2.}`

.1. *name*  
... see `\setupcomment`

`\comparecolorgroup[...]`

... *name*

`\comparepalet[...]`

... *name*

`\completecombinedlist[...][...,...=,...]`

... *name*  
... see `\setupcombinedlist`

`\completelistofblocks`

`\completelistofsorts`

`\completelistofsynonyms`

`\completeregister[...,...=,...]`

... see `\setupregister`

`\convertnumber{.1.},{.2.}`

.1. *name*  
.2. *number*

`\copyfield[.1.][...,2,...]`

.1. *name*  
.2. *name*

`\correctwhitespace{...}`

`\coupledocument[.1.][.2.][.3.]`

- .1. *name*
- .2. *file*
- .3. *name*
- .4. *text*

`\coupledregister[.1.]{.2.}`

- .1. *text*
- .2. *text*

`\couplemarking[.1.][.2.]`

- .1. *name*
- .2. *name*

`\couplepage[...][...=...]`

- ... *name*
- option *doublesided*
- before *command*
- after *command*

`\couplepaper[...]`

- ... *name*

`\coupleregister[...]`

- ... *name*

`\crlf`

`\currentdate[...]`

- ... day month MONTH weekday WEEKDAY year dd mm jj yy d m j y referral

`\decouplemarking[...]`

- ... *name*

`\define[.1.]\command{.2.}`

- .1. *number*

`\defineblock[...]`

- ... *name*

`\definebodyfont[...1,...][.2.][...,...=,...]`

.1. 5pt ... 12pt  
.2. rm ss tt mm hw cg  
tf *file*  
bf *file*  
sl *file*  
it *file*  
bs *file*  
bi *file*  
sc *file*  
ex *file*  
mi *file*  
sy *file*  
ma *file*  
mb *file*  
mc *file*

`\definebodyfontenvironment[...=,...]`

text *dimension*  
script *dimension*  
scriptscript *dimension*  
x *dimension*  
xx *dimension*  
small *dimension*  
big *dimension*

`\definecolor[...][...,...=,...]`

... *name*  
r *text*  
g *text*  
b *text*  
c *text*  
m *text*  
y *text*  
k *text*  
s *text*

`\definecolorgroup[.1.][.2.][...,3,...]`

.1. *name*  
.2. rgb cmyk k  
.3. [x:y:z=,...]

`\definecombinedlist[.1.][...,2,...][...,...=,...]`

.1. *name*  
.2. *list*  
..=.. see `\setupcombinedlist`

`\defineconversion[.1.][.2.]`

.1. *name*  
.2. *command text*

`\definedescription[...][...,...=,...]`

... *name*  
..=.. see `\setupdescriptions`

`\defineenumeration[...].1,...][.2.][...,...=...,...]`

- .1. *name*
- .2. *name*
- ... see `\setupenumerations`

`\definefield[.1.][.2.][.3.][...,.4.,...][.5.]`

- .1. *name*
- .2. *name*
- .3. *name*
- .4. *name*
- .5. *name*

`\definefieldstack[.1.][...,.2.,...][...,...=...,...]`

- .1. *name*
- .2. *name*
- ... see `\setupfields`

`\definefiguresymbol[.1.][.2.][...,...=...,...]`

- .1. *name*
- .2. *text*
- ... see `\externalfigure`

`\definefloat[.1.][.2.]`

- .1. *singular name*
- .2. *plural name*

`\definefont[.1.][.2.]`

- .1. *name*
- .2. *file*

`\defineframedtext[...][...,...=...,...]`

- ... *name*
- ... see `\setupframedtexts`

`\definehbox[.1.][.2.]`

- .1. *name*
- .2. *number*

`\definehead[.1.][.2.]`

- .1. *name*
- .2. *section*

`\defineindenting[...][...,...=...,...]`

- ... *name*
- ... see `\setupindentations`

`\defineinteractionmenu[.1.][.2.][...]=...`

.1. left right top bottom *name*  
.2. left right top bottom *name*  
... see `\setupinteractionmenu`

`\definelabel[...][...]=...`

... *name*  
text *text*  
location *inmargin intext*  
way *bytext bysection bychapter*  
blockway *yes no*  
headstyle normal bold slanted boldslanted type cap small... *command*  
headcolor *name*  
before *command*  
after *command*

`\definelist[.1.][.2.][...]=...`

.1. *name*  
.2. *name*  
... see `\setuplist`

`\definelogo[.1.][.2.][.3.][...]=...`

.1. *name*  
.2. top header footer bottom  
.3. none leftedge leftmargin left middle right rightmargin rightedge  
command *command text*  
state start stop

`\definemakeup[...][...]=...`

... *name*  
... see `\setupmakeup`

`\definemarking[.1.][.2.]`

.1. *name*  
.2. *name*

`\defineoutput[.1.][...].2.,...`

.1. *name*  
.2. *name*

`\defineoverlay[...].1.,...][.2.]`

.1. *name*  
.2. *command*

`\definepalette[...][...]=...`

... *name*  
*name name*

`\definepapersize[...][...]=...]`

...        *name*  
width     *number*  
height    *number*  
scale     *dimension*

`\defineparagraphs[...][...]=...]`

...        *name*  
n          *number*  
line       *on off*  
height     *fit dimension*  
before     *command*  
after      *command*  
inner      *command*  
distance   *dimension*  
tolerance   *verystrict strict tolerant verytolerant*  
align      *left right middle*

`\defineprofile[...1,...][...2,...]`

.1.        *name*  
.2.        *name*

`\defineprogram[.1.][.2.][.3.]`

.1.        *name*  
.2.        *text*  
.3.        *text*

`\definereference[...][ref,..]`

...        *name*  
...        *text*

`\definereferencelist[...][...]=...]`

...        *name*  
..=...     *see \setupreferencelist*

`\defineregister[.1.][.2.]`

.1.        *singular name*  
.2.        *plural name*

`\definesection[...]`

...        *name*

`\definesectionblock[...][...]=...]`

...        *name*  
..=...     *see \setupsectionblock*

`\definesorting[.1.][.2.][.3.]`

- .1. *singular name*
- .2. *plural name*
- .3. *command*

`\definestartstop[...][...,...=,...]`

- before *command*
- after *command*
- style normal bold slanted boldslanted type cap small... *command*
- commands *command*

`\definesubfield[.1.][.2.][...,3,...]`

- .1. *name*
- .2. *name*
- .3. *name*

`\definesymbol[.1.][.2.]`

- .1. *name*
- .2. *text*

`\definesynonyms[.1.][.2.][.3.][.4.]`

- .1. *singular name*
- .2. *plural name*
- .3. *command*
- .4. *command*

`\definetext[.1.][.2.][.3.][.4.][.5.]`

- .1. *name*
- .2. header footer
- .3. *text*
- .4. *text*
- .5. *text*

`\definetyping[...][...,...=,...]`

- ... *file typing name*
- ... see `\setuptyping`

`\defineversion[.1.][...,2,...]`

- .1. *name*
- .2. *number*

`\description{.1.}.2.\par`

- .1. *text*
- .2. *text*

`\disableinteractionmenu[...][ref,..]`

- ... left right top bottom *name*

`\domicile{...}`

... *text*

`\dotttest`

`\enumeration...\par`

... *text*

`\externalfigure[...][...==...]`

... *file*

..=.. see `\useexternalfigure`

`\field[...]`

... *name*

`\fieldstack[.1.][...2...][...==...]`

.1. *name*

.2. *name*

...=.. see `\setupfields`

`\fillinfield[.1.]{.2.}`

.1. *text*

.2. *text*

`\fillinline[...==...]\par`

..=.. see `\setupfillinlines`

`\fillinrules[...==...]{.1.}{.2.}`

..=.. see `\setupfillinrules`

`\fillintext[...==...]{.1.}{.2.}\par`

..=.. see `\setupfillinrules`

`\fitfield[...]`

... *name*

`\fixedspaces`

`\followprofile{.1.}[.2.]`

.1. *text*

.2. *name*

`\followprofileversion{.1.}[.2.][.3.]`

- .1. *text*
- .2. *name*
- .3. *name*

`\followversion{.1.}[.2.]`

- .1. *text*
- .2. *name*

`\footnote[ref]{...}`

... *text*

`\fraction{.1.}{.2.}`

- .1. *text*
- .2. *text*

`\framed[...]=...]{...}`

... see `\setupframed`  
... *text*

`\framedtext[...]=...]`

... see `\setupframedtexts`

`\from{...}[ref]`

... *text*

`\getbuffer[...]`

... *name*

`\getmarking[.1.][.2.]`

- .1. *name*
- .2. *first last previous*

`\godown[...]`

... *dimension*

`\goto{.1.}{.2.}[ref,..]`

- .1. *text*

`\gotobox{...}[ref,..]`

... *text*

`\gray[...]`

... *text*

`\grid[...]=...]`

*nx*        *number*  
*ny*        *number*  
*dx*        *number*  
*dy*        *number*  
*xstep*    *number*  
*ystep*    *number*  
*offset*    yes *no*  
*factor*    *number*  
*scale*     *number*  
*unit*      cm *pt em mm ex sp in*

`\hairline`

`\head[ref,..]`

`\headnumber[...]`

... *section*

`\headtext{...}`

... *text*

`\hideblocks[...1,...][...2,...]`

.1.        *name*  
.2.        *name*

`\high{...}`

... *text*

`\h1[...]`

... *number*

`\in{.1.}{.2.}[ref]`

.1.        *text*

`\indentation...\par`

... *text*

`\indenting[...]`

...        not never *no yes always*

`\inframed[...]=...]{...}`

..  
... see `\setupframed`  
... text

`\inleft[.1.][ref]{.2.}`

.1. + - low  
.2. text

`\inline[ref]`

`\inmargin[.1.][ref]{.2.}`

.1. + - low  
.2. text

`\inothmargin[.1.][ref]{.2.}`

.1. + - low  
.2. text

`\inright[.1.][ref]{.2.}`

.1. + - low  
.2. text

`\installlanguage[...][...]=...]`

...	<i>name</i>
spacing	<u>packed</u> broad
lefthyphenmin	<i>dimension</i>
righthyphenmin	<i>dimension</i>
state	start <u>stop</u>
leftsentence	<i>command</i>
rightsentence	<i>command</i>
leftsubsentence	<i>command</i>
rightsubsentence	<i>command</i>
leftquote	<i>command</i>
rightquote	<i>command</i>
leftquotation	<i>command</i>
rightquotation	<i>command</i>
default	<i>name</i>

`\interactionbar[...]=...]`

..  
... see `\setupinteractionbar`

`\interactionbuttons[...]=...][...]`

..  
... see `\setupinteractionbar`  
... *name*

`\item[ref,..]`

`\items[...=...]{...}`

... see `\setupitems`

`\its[ref,...]`

`\kap{...}`

... *text*

`\keepblocks[...1,...][...2,...]`

- .1. *name*
- .2. *all name*

`\label[.1.]{.2.}{.3.}{.4.}{.5.}{.6.}{.7.}`

- .1. *tall wide*
- .2. *text*
- .3. *text*
- .4. *text*
- .5. *text*
- .6. *text*
- .7. *text*

`\labeling`

`\labels[...]`

... *name*

`\labeltext{...}`

... *text*

`\language[...]`

... n fr en de sp it da

`\leftaligned{...}`

... *text*

`\letters[...]`

... *name*

`\loadsorts`

`\loadsynonyms`

`\logfields`

`\lohi{.1.}{.2.}`

.1. *text*  
.2. *text*

`\low{...}`

... *text*

`\mainlanguage[...]`

... nl fr en de sp it da

`\mar[ref,...]`

`\marginrule[.1.]{.2.}`

.1. *number*

`\margintext[.1.][ref]{.2.}`

.1. + - low  
.2. *text*

`\marking[.1.]{.2.}`

.1. *name*  
.2. *text*

`\marking(.1.,.2.)(.3.,.4.)[.5.]`

.1. *number*  
.2. *number*  
.3. *number*  
.4. *number*  
.5. *text*

`\markversion`

`\mathematics{...}`

... *formula*

`\mediaeval{...}`

... *number*

`\menubutton[.1.][...=...]{.2.}[ref,...]`

`..=..` see `\setupframed`  
`.1.` *text*

`\midaligned{...}`

`...` *text*

`\mirror{...}`

`\MONTH{...}`

`...` *number*

`\month{...}`

`...` *number*

`\moveongrid[...]`

`...` top both bottom

`\name{...}`

`...` *name*

`\nextsection`

`\nocap{...}`

`...` *text*

`\noheaderandfooterlines`

`\noindenting`

`\nomarking{...}`

`...` *text*

`\nomoreblocks`

`\nomorefiles`

`\nop`

`\nospace`

`\note[ref]`

`\notopandbottomlines`

`\nowhitespace`

`\numbers{...}`

... *number*

`\overbar{...}`

... *text*

`\overbars{.. ... ..}`

... *text*

`\overstrike{...}`

... *text*

`\overstrikes{.. ... ..}`

... *text*

`\packed`

`\page[...,...,..]`

... yes markup no preference bigpreference left right disable last quadruple even odd blank reset

`\pagereference[ref]`

`\pagetype[...]`

... *name*

`\paragraphs`

`\part{...}`

... *text*

`\periods[...]`

...      *number*

`\placeblock[.1.][ref,..]{.2.}{.3.}`

.1.      left right here top bottom inleft inright inmargin margin page opposite always force tall  
.2.      *text*  
.3.      *text*

`\placebookmarks[...1,...][...2,...]`

.1.      *name*

`\placecombinedlist[...][...=,...]`

...      *name*  
..=...    see `\setupcombinedlist`

`\placefootnotes[...=,...]`

..=...    see `\setupfootnotes`

`\placeformula[ref,..].1.$$2.$$`

.1.      *text*  
.2.      *formula*

`\placelist[...][...=,...]`

...      *name*  
..=...    see `\setuplist`

`\placelistofblocks`

`\placelistofsorts`

`\placelistofsynonyms`

`\placelocalfootnotes[...=,...]`

..=...    see `\setupfootnotes`

`\placelogos[...][...]`

...      *name*

`\placeongrid[.1.]{.2.}`

.1.      see `\moveongrid`

`\placeontopofeachother{.1.}{.2.}`

- .1. *text*
- .2. *text*

`\placereferencelist[.....]`

... *name*

`\placeregister[...=...]`

..=.. see `\setupregister`

`\placesidebyside{.1.}{.2.}`

- .1. *text*
- .2. *text*

`\placesubformula[ref,..].1.$$2.$$`

- .1. *text*
- .2. *formula*

`\position(.1.,.2.){.3.}`

- .1. *number*
- .2. *number*
- .3. *text*

`\processpage[...1,...][.2.]`

- .1. *name*
- .2. yes no

`\program[...]`

... *name*

`\publication[ref]`

`\quotation{...}`

... *text*

`\quote{...}`

... *text*

`\redo[...]`

... *n\*text*

`\ref[...][ref]`

...     *tp r s e*  
...     *text*

`\reference[ref]{...}`

...     *text*

`\referral[...==...]`

*bet*     *text*  
*ken*     *text*  
*dat*     *text*  
*from*    *text*  
*to*      *text*  
*ref*     *text*

`\referraldate`

`\referring(.1.,.2.)(.3.,.4.)[.5.]`

.1.     *number*  
.2.     *number*  
.3.     *number*  
.4.     *number*  
.5.     *text*

`\register[.1.]{...+2.+...}`

.1.     *text*  
.2.     *text*

`\remark(.1.,.2.)(.3.,.4.)[...==...]{.5.}`

.1.     *number*  
.2.     *number*  
.3.     *number*  
.4.     *number*  
..==... see `\setupframed`  
.5.     *text*

`\reserveblock[...==...][.1.][ref,...]{.2.}`

*height*    *dimension*  
*width*     *dimension*  
*frame*     on off  
.1.     left right here top bottom inleft inright inmargin margin page opposite always force  
.2.     *text*

`\reset[...,...]`

...     *name*

`\resetmarking[...]`

...     *name*

`\rightaligned{...}`

... *text*

`\romannumerals{...}`

... *number*

`\Romannumerals{...}`

... *number*

`\rotate[...]=...]{...}`

... see `\setuprotate`

`\scale[...]=...]{...}`

*sx* *number*

*sy* *number*

`\screen`

`\section[ref,...]{...}`

... *text*

`\seeregister[.1.]{.2.}{.+3.+}`

.1. *text*

.2. *text*

.3. *text*

`\selectblocks[...1...][...2...][...=...]`

.1. *name*

.2. *name*

criterium all *section*

`\selectpaper[...=...]`

family 1 2

`\selectversion`

`\setupalign[...]`

... width left right middle inner outer broad height bottom line reset

## `\setuparranging[...,...,...]`

...      2\*8 2\*4 2\*2 2UP 2DOWN mirrored rotated doublesided negative 90 180 270

## `\setupbackground[...,...=...,...]`

leftoffset      *dimension*  
rightoffset     *dimension*  
topoffset      *dimension*  
bottomoffset   *dimension*  
state           start stop  
...             see \setupframed

## `\setupbackgrounds[.1.][...,.2.,...][...,...=...,...]`

.1.      top header text footer bottom page leftpage rightpage  
.2.      leftedge leftmargin text rightmargin rechterrind  
...      see \setupframed

## `\setupblackrules[...,...=...,...]`

width           *dimension* max  
height          *dimension* max  
depth           *dimension* max  
alternative     a b  
distance        *dimension*  
n                *number*

## `\setupblank[...]`

...      normal standard line *dimension* big medium small fixed flexible

## `\setupblock[...,...,...][...,...=...,...]`

...      *name*  
before     *command*  
after      *command*  
inner      *command*  
style      normal bold slanted boldslanted type cap small... *command*  
file       *file*

## `\setupbodyfont[...,...,...]`

...      *name* roman sansserif teletype handwritten calligraphic 5pt ... 12pt

## `\setupbottom[...][...,...=...,...]`

...      see \setupheader  
...      see \setupheader

## `\setupbottomtexts[.1.][.2.][.3.]`

.1.      text margin edge  
.2.      *text* *section* date *mark* pagenumber  
.3.      *text* *section* date *mark* pagenumber

## `\setupbuffer[...]=...`

before *command*  
after *command*

## `\setupbuttons[...]=...`

... see `\setupframed`

## `\setupcaption[...][...]=...`

... see `\setupcaptions`

## `\setupcaptions[...]=...`

location top bottom none high low middle  
width fit max *dimension*  
headstyle normal bold slanted boldslanted type cap small... *command*  
style normal bold slanted boldslanted type cap small... *command*  
number yes no  
inbetween *command*  
align left middle right no  
conversion numbers characters Characters romannumerals Romannumerals  
way bytext bysection

## `\setupcolor[...]`

... *name*

## `\setupcolors[...]=...`

state start stop global local  
conversion yes no always  
rgb yes no  
cmyk yes no

## `\setupcolumns[...]=...`

n *number*  
line on off  
height *dimension*  
tolerance verystRICT strict tolerant verytolerant  
distance *dimension*  
balance yes no  
align yes no text  
blank fixed halfline line flexible big medium small fixed,line  
option background  
... see `\setupframed`

## `\setupcombinations[...]=...`

before *commando*  
inbetween *commando*  
after *commando*  
distance *dimension*  
height *dimension* fit  
width *dimension* fit

## `\setupcombinedlist[...][...=...]`

... *name*  
level 1 2 3 4 *section*  
... see `\setuplist`

## `\setupcomment[...=...]`

width *dimension*  
height *dimension*  
color *name*

## `\setupcorrespondence[...=...]`

... formee1 informee1 rekening ls high middle low

## `\setupdescriptions[...=...]`

... *name*  
headstyle normal bold slanted boldslanted type cap small... *command*  
style normal bold slanted boldslanted type cap small... *command*  
color *name*  
width fit broad *dimension*  
distance *dimension*  
sample *text*  
text *text*  
align left middle right  
margin standard no *dimension*  
location left right top serried inmargin inleft inright hanging  
hang fit broad *number*  
before *command*  
inbetween *command*  
after *command*  
indentnext yes no

## `\setupenumerations[...=...]`

... *name*  
headstyle normal bold slanted boldslanted type cap small... *command*  
headcolor *name*  
style normal bold slanted boldslanted type cap small... *command*  
color *name*  
width fit broad *dimension*  
distance *dimension*  
coupling *name*  
sample *text*  
text *text*  
align left middle right  
margin standard no *dimension*  
location left right top serried inmargin inleft inright hanging  
hang fit broad *number*  
before *command*  
inbetween *command*  
after *command*  
levels *number*  
conversion numbers characters Characters romannumerals Romannumerals  
way bytext bysection  
blockway yes no  
sectionnumber yes no  
separator *text*  
stopper *text*  
number no *name*  
coupling *name*  
indentnext yes no

## `\setupexternalfigures[...]`

option	frame empty test
object	<u>yes</u> no
frames	on <u>off</u>
ymax	<i>number</i>
xmax	<i>number</i>
directory	<i>text</i>
location	local global

## `\setupfield[.1][...,.2,...][...=...][...=...][...=...]`

.1.	<i>name</i>
.2.	label horizontal vertical frame
... ..	see <code>\framed</code>
... ..	see <code>\setupfields</code>

## `\setupfields[...][...=...][...=...][...=...]`

...	label horizontal vertical frame
... ..	see <code>\framed</code>
n	<i>number</i>
distance	<i>dimension</i>
before	<i>command</i>
after	<i>command</i>
inbetween	<i>command</i>
color	<i>name</i>
style	<u>normal</u> bold slanted boldslanted type
align	left middle right
option	readonly required protected sorted unavailable hidden printable
clickin	<i>reference</i>
clickout	<i>reference</i>
regionin	<i>reference</i>
regionout	<i>reference</i>
afterkey	<i>reference</i>
format	<i>reference</i>
validate	<i>reference</i>
calculate	<i>reference</i>
fieldoffset	<i>dimension</i>
fieldframecolor	<i>name</i>
fieldbackgroundcolor	<i>name</i>

## `\setupfillinlines[...=...]`

width	<i>dimension</i>
margin	<i>dimension</i>
distance	<i>dimension</i>
before	<i>command</i>
after	<i>command</i>

## `\setupfillinrules[...=...]`

width	<i>fit dimension</i>
distance	<i>dimension</i>
before	<i>command</i>
after	<i>command</i>
style	normal bold slanted boldslanted type cap small... <i>command</i>
n	<i>number</i>
separator	<i>text</i>

## `\setupfloat[...][...=...]`

...            *name*  
height        *dimension*  
width         *dimension*  
pageboundaries *list*  
...            see `\setupframed`

## `\setupfloats[...=...]`

location      *left right middle*  
width         *fit dimension*  
before        *command*  
after         *command*  
margin        *dimension*  
voorwit      *n\*small n\*medium n\*big none*  
nawit         *n\*small n\*medium n\*big none*  
zijvoorwit   *n\*small n\*medium n\*big none*  
zijnawit     *n\*small n\*medium n\*big none*  
ntop          *number*  
nbottom      *number*  
nlines        *number*  
...            see `\setupframed`

## `\setupfloatsplitting[...=...]`

conversion    *numbers characters Characters romannumerals Romannumerals character*  
lines          *number*

## `\setupfooter[...][...=...]`

...            see `\setupheader`  
...            see `\setupheader`

## `\setupfootertexts[.1.][.2.][.3.]`

.1.            *text margin edge*  
.2.            *text section date mark pagenumber*  
.3.            *text section date mark pagenumber*

## `\setupfootnotedefinition[...=...]`

...            see `\definedescription`

## `\setupfootnotes[...=...]`

conversion    *numbers characters Characters romannumerals Romannumerals*  
way            *bytext bysection*  
location      *page text*  
line          *on off*  
before        *command*  
after         *command*  
width         *dimension*  
height        *dimension*  
bodyfont     *5pt ... 12pt small big*  
style          *normal bold slanted boldslanted type cap small... command*  
distance      *dimension*  
columndistance *dimension*  
margindistance *dimension*  
numbercommand *\command#1*  
...            see `\framed`

### `\setupformulae[...]=...]`

location	left <u>right</u>
left	text
right	text

### `\setupframed[...]=...]`

height	fit broad <i>dimension</i>
width	fit broad <i>dimension</i>
offset	none overlay <i>dimension</i>
location	low depth
option	<u>none</u> empty
strut	<u>yes</u> no
align	<u>no</u> left right middle normal
bottom	<i>command</i>
top	<i>command</i>
frame	on <u>off</u>
topframe	on <u>off</u>
bottomframe	on <u>off</u>
leftframe	on <u>off</u>
rightframe	on <u>off</u>
frameoffset	<i>dimension</i>
framedepth	<i>dimension</i>
framecorner	round <u>right</u>
frameradius	<i>dimension</i>
framecolor	<i>name</i>
background	screen color <u>none</u>
backgroundscreen	<i>number</i>
backgroundcolor	<i>name</i>
backgroundoffset	<i>dimension</i>
backgrounddepth	<i>dimension</i>
backgroundcorner	round <u>right</u>
backgroundradius	<i>dimension</i>
depth	<i>dimension</i>
corner	round <u>right</u>
radius	<i>dimension</i>
...	<i>text</i>

### `\setupframedtexts[...]=...]`

bodyfont	5pt ... 12pt small big
style	normal bold slanted boldslanted type small... <i>command</i>
left	<i>command</i>
right	<i>command</i>
before	<i>command</i>
after	<i>command</i>
inner	<i>command</i>
..=..	see <code>\setupframed</code>

## `\setuphead[...][...=...]`

... *section*  
style normal bold slanted boldslanted type cap small... *command*  
textstyle normal bold slanted boldslanted type cap small... *command*  
numberstyle normal bold slanted boldslanted type cap small... *command*  
number yes no  
ownnumber yes no  
page left right yes  
continue yes no  
header none empty high nomarking  
before *command*  
inbetween *command*  
after *command*  
alternative normal inmargin middle text  
command `\command#1#2`  
numbercommand `\command#1`  
textcommand `\command#1`  
prefix + - *text*  
placehead yes no  
incrementnumber yes no *file*  
indentnext yes no  
file *name*

## `\setupheader[...][...=...]`

... text margin edge  
state normal stop start empty high none nomarking *name*  
strut yes no  
style normal bold slanted boldslanted type cap small... *command*  
leftstyle normal bold slanted boldslanted type cap small... *command*  
rightstyle normal bold slanted boldslanted type cap small... *command*  
leftwidth *dimension*  
rightwidth *dimension*  
before *command*  
after *command*

## `\setupheadertexts[.1.][.2.][.3.]`

.1. text margin edge  
.2. *text section date mark pagenumber*  
.3. *text section date mark pagenumber*

## `\setupheadnumber[.1.][.2.]`

.1. *section*  
.2. *number +number -number*

## `\setupheads[...=...]`

sectionnumber yes no  
alternative normal inmargin middle text  
separator *text*  
command `\command#1#2`

## `\setupheadtext[...][..=..]`

... n fr en de sp it da  
*name text*

`\setuphyphenmark[...=...]`

sign    -- --- - ) (= /

`\setupindentations[...][...=...]`

...            *name*  
style          normal bold slanted boldslanted type cap small... *command*  
headstyle     normal bold slanted boldslanted type cap small... *command*  
width         fit *dimension*  
text          *text*  
sample        *text*  
before        *command*  
after         *command*  
separator     *text*

`\setupindenting[...]`

...          none small medium big next first *dimension*

`\setupinmargin[...][...=...]`

...            left right *number*  
location      left right both  
style         normal bold slanted boldslanted type cap small... *command*  
before        *command*  
after         *command*  
align         inner outer  
...            see \setupframed

`\setupinteraction[...=...]`

state            start stop  
menu            on off  
page            yes no  
strut            yes no  
width            *dimension*  
height          *dimension*  
depth          *dimension*  
style            normal bold slanted boldslanted type cap small... *command*  
color            *name*  
contrastcolor   *name*  
symbolset       *name*  
title            *text*  
subtitle        *text*  
author          *text*  
date            *text*

`\setupinteractionbar[...=...]`

state            start stop  
alternative     a b c d e f g  
symbol          yes no  
width            *dimension* hoogte fit  
height          *dimension* hoogte fit  
depth          *dimension*  
color            *name*  
step            *number* small medium big  
...            see \setupframed

`\setupinteractionmenu[...][...=...][...{...[ref,...]}...]`

... left right top bottom *name*  
before *command*  
after *command*  
inbetween *command*  
left *command*  
right *command*  
middle *command*  
state start stop none  
style normal bold slanted boldslanted type cap small... *command*  
color *name*  
distance overlay *dimension*  
samepage yes empty no none  
unknownreference yes empty no none  
leftoffset *dimension*  
rightoffset *dimension*  
topoffset *dimension*  
bottomoffset *dimension*  
... see `\setupframed`

`\setupinteractionscreen[...=...]`

width *dimension* fit  
height *dimension* fit  
backspace *dimension*  
topspace *dimension*  
backoffset *dimension*  
topoffset *dimension*

`\setupinterlinespace[...][...=...]`

... reset small medium big on off  
height *number*  
depth *number*  
line *dimension*  
top *number*  
bottom *number*

`\setupitemize[.1.][...2...][...=...]`

.1. *number* each  
.2. standard *n*\*broad *n*\*serried packed stopper joinedup atmargin inmargin autointro  
margin no standard *dimension*  
width *dimension*  
distance *dimension*  
factor *number*  
items *number*  
before *command*  
inbetween *command*  
after *command*  
beforehead *command*  
afterhead *command*  
headstyle normal bold slanted boldslanted type cap small... *command*  
marstyle normal bold slanted boldslanted type cap small... *command*  
symstyle normal bold slanted boldslanted type cap small... *command*  
stopper *text*  
n *number*  
symbol *number*  
align left right normal  
indentnext yes no

### `\setupitems[...]=...]`

location	<u>left</u> right inmargin top bottom
symbol	1 2 ... n a ... text none
width	<i>dimension</i>
n	<i>number</i> unknown
before	<i>command</i>
inbetween	<i>command</i>
align	left right <u>middle</u> margin
after	<i>command</i>

### `\setuplabeltext[...][..=..]`

...	<u>n</u> l fr en de sp it da
name	text

### `\setuplanguage[...][...]=...]`

... see `\installlanguage`

### `\setuplayout[...]=...]`

width	<i>dimension</i> fit middle
height	<i>dimension</i> fit middle
backspace	<i>dimension</i>
topspace	<i>dimension</i>
margin	<i>dimension</i>
leftmargin	<i>dimension</i>
rightmargin	<i>dimension</i>
header	<i>dimension</i>
footer	<i>dimension</i>
top	<i>dimension</i>
bottom	<i>dimension</i>
leftedge	<i>dimension</i>
rightedge	<i>dimension</i>
headerdistance	<i>dimension</i>
footerdistance	<i>dimension</i>
topdistance	<i>dimension</i>
bottomdistance	<i>dimension</i>
leftmargindistance	<i>dimension</i>
rightmargindistance	<i>dimension</i>
leftedgedistance	<i>dimension</i>
rightedgedistance	<i>dimension</i>
backoffset	<i>dimension</i>
topoffset	<i>dimension</i>
style	normal bold slanted boldslanted type cap small... <i>command</i>
marking	on <u>off</u> color
location	left middle right bottom top <u>singlesided</u> doublesided
scale	<i>dimension</i>
nx	<i>number</i>
ny	<i>number</i>
lines	<i>number</i>
grid	yes <u>no</u>

### `\setuplinenumbering[...]=...]`

conversion	<u>numbers</u> characters Characters romannumerals Romannumerals text
start	<i>number</i>
step	<i>number</i>
width	<i>dimension</i>
location	intext <u>inmargin</u>
style	normal bold slanted boldslanted type cap small... <i>command</i>
prefix	text
referencing	<u>on</u> off

`\setuplines[...]=...`

before *command*  
after *command*  
indenting yes no even odd

`\setuplinewidth[...]`

... *dimension*

`\setuplist[...]=...`

... *name*  
state start stop  
alternative a b c d none  
coupling on off  
criterium *section* local previous all  
pageboundaries *list*  
style normal bold slanted boldslanted type cap small... *command*  
numberstyle normal bold slanted boldslanted type cap small... *command*  
textstyle normal bold slanted boldslanted type cap small... *command*  
pagestyle normal bold slanted boldslanted type cap small... *command*  
color *name*  
command `\command#1#2#3`  
numbercommand `\command#1`  
textcommand `\command#1`  
pagecommand `\command#1`  
interaction sectionnumber text pagenumber all  
before *command*  
after *command*  
left *text*  
right *text*  
label yes no  
prefix yes no  
pagenumber yes no  
sectionnumber yes no  
aligntitle yes no  
margin *dimension*  
width *dimension*  
height *dimension* fit broad  
depth *dimension* fit broad  
offset *dimension*  
distance *dimension*  
separator *text*  
symbol none 1 2 3 ...  
expansion yes no *command*

`\setupmakeup[...]=...`

... *name*  
width *dimension*  
height *dimension*  
voffset *dimension*  
hoffset *dimension*  
page left yes right  
commands *command*  
doublesided yes no empty  
headerstate normal stop start empty none nomarking  
footerstate normal stop start empty none nomarking  
textstate normal stop start empty none nomarking  
topstate stop start  
bottomstate stop start

### `\setupmarginblocks[...]=...`

location    inmargin left middle right  
style       normal bold slanted boldslanted type cap small... *command*  
width       *dimension*  
align       left middle right no  
top         *command*  
inbetween   *command*  
bottom      *command*  
left        *command*  
right       *command*  
before      *command*  
after       *command*

### `\setupmarginrules[...]=..`

level        *number*  
thickness    *dimension*

### `\setupmarking[...][...]=..`

...          *name*  
state        start stop  
expansion    yes no

### `\setupnarrower[...]=...`

left        *dimension*  
right       *dimension*  
middle      *dimension*

### `\setupnumbering[...]=...`

way        bytext bysection bychapter  
state      start stop

### `\setupoppositeplacing[...]=..`

state      start stop

### `\setupoutput[...]=...`

...        *name*

### `\setuppagenumber[...]=...`

number     *number*  
state      start stop keep

## \setuppagenumbering[...]=...]

alternative        singlesided doublesided  
location         header footer left right middle margin marginedge inleft inright  
conversion       numbers characters Characters romannumerals Romannumerals  
style             normal bold slanted boldslanted type cap small... *command*  
left              *text*  
right             *text*  
way               bytext bysection bypart  
text              *text*  
numberseparator *text*  
textseparator    *text*  
sectionnumber    yes no  
separator        *text*  
state             start stop  
command         \command#1

## \setuppagetransitions[...]=...]

...        reset *number*

## \setuppalet[...]

...        *name*

## \setuppapersize[...].1,...][...].2,...]

- .1.        A3 A4 A5 A6 CD *name* landscape mirrored rotated 90 180 270
- .2.        A3 A4 A5 A6 *name* landscape mirrored rotated negative 90 180 270

## \setupparagraphs[.1.][.2.][...]=...]

.1.        *name*  
.2.        *number* each  
style       normal bold slanted boldslanted type cap small... *command*  
width      *dimension*  
height     *dimension*  
align      left right middle breedte  
tolerance  verystrict strict tolerant verytolerant  
distance   *dimension*  
before     *command*  
after      *command*  
inner      *command*  
command   *command*  
line       on off

## \setuppositioning[...]=...]

unit        cm pt em mm ex sp in  
factor      *number*  
scale       *number*  
offset      yes no  
xstep       absolute relative  
ystep       absolute relative

## \setupprofiles[...]=...]

option      test

`\setupprograms[...]=...]`

directory *text*

`\setuppublications[...]=...]`

alternative apa normal  
... see `\setupenumerations`

`\setupquote[...]=...]`

alternative 1 2  
before  
after  
style normal bold slanted boldslanted type cap small... *command*

`\setuppreferencelist[...][...]=...]`

... *name*  
state start stop  
criterium *section* local previous all  
command *command*  
before *command*  
after *command*

`\setuppreferencing[...]=...]`

state start stop  
sectionnumber yes no  
prefix + - *text*  
interaction label text all symbol  
urlalternative none both before after  
urlspace yes no  
width *dimension*  
left *command*  
right *command*

`\setupregister[...][...]=...]`

... *singular name*  
n *number*  
balance yes no  
align yes no  
style normal bold slanted boldslanted type cap small... *command*  
indicator yes no  
coupling yes no  
sectionnumber yes no  
criterium *section* local all part  
distance *dimension*  
symbol 1 2 ... n a ...  
interaction pagenumber text  
expansion yes no  
referencing on off  
command `\command#1`

`\setuprotate[...]=...]`

rotation *number*  
... see `\setupframed`

### `\setupscreens[...]=...]`

method dot line external  
resolution *number*  
factor *number*  
screen *number*

### `\setupsection[...][...]=...]`

... *name*  
conversion numbers characters Characters romannumerals Romannumerals  
previousnumber yes no

### `\setupsectionblock[...][...]=...]`

... *name*  
number yes no  
page yes right  
before *command*  
after *command*

### `\setupsheets[...]=...]`

alternative *number*  
text *text*  
size small medium big  
style normal bold slanted boldslanted type cap small... *command*  
number *number* joinedup

### `\setupsorting[...][...]=...]`

... *name*  
before *command*  
after *command*  
command `\command#1`  
state start stop  
criterium all used  
style normal bold slanted boldslanted type cap small... *command*  
expansion yes no

### `\setupspacing[...]`

... broad packed

### `\setupstickers[...]=...]`

alternative a  
n *number* all  
location margin left right middle

### `\setupsubpagenumber[...]=...]`

way bytext bysection bypart  
state start stop none

### `\setupsymbolset[...]`

... *name*

`\setupsynchronization[...]=...]`

state    start stop

`\setupsynchronizationbar[...]=...]`

alternative    page local  
width            *dimension* hoogte fit  
height          *dimension*  
style            normal bold slanted boldslanted type cap small... *command*  
color            *name*  
...              see \setupframed

`\setupsynonym[...][...]=...]`

...              *name*  
textstyle        normal bold slanted boldslanted type cap small... *command*  
synonymstyle    normal bold slanted boldslanted type cap small... *command*  
location         left right top serried inmargin inleft inright  
width            *dimension*  
state            start stop  
criterium        all used  
conversion        yes no  
expansion        yes no

`\setupsystem[...]=...]`

resolution    *number*

`\setuptab[...]=...]`

sample         *text*  
width            *dimension*  
headstyle        normal bold slanted boldslanted type cap small... *command*  
location         left right

`\setuptables[...]=...]`

distance         small medium big  
bodyfont         5pt ... 12pt small big  
HL                *number* small medium big none  
VL                *number* small medium big none  
commands         *command*  
background        screen color none  
backgroundscreen *number*  
backgroundcolor    *name*

`\setuptext[...][...]=...]`

...              see \setupheader  
...              see \setupheader

### `\setuptextrules[...]=...]`

location     left inmargin  
before       *command*  
after        *command*  
inbetween   *command*  
width        *dimension*  
distance     *dimension*  
bodyfont     5pt ... 12pt small big  
color        *name*  
style        normal bold slanted boldslanted type cap small... *command*  
linecolor    *name*

### `\setuptexttexts[.1.][.2.][.3.]`

.1.        text margin edge  
.2.        *text section* date *mark* pagenumber  
.3.        *text section* date *mark* pagenumber

### `\setupthinrules[.]=..]`

distance     small medium big  
n            *number*  
before       *command*  
after        *command*  
height       *dimension*  
depth        *dimension*

### `\setuptolerance[...]=...]`

...        horizontal vertical verystRICT strict tolerant verytolerant

### `\setuptop[...][...]=...]`

...        see `\setupheader`  
..=..     see `\setupheader`

### `\setuptoptexts[.1.][.2.][.3.]`

.1.        text margin edge  
.2.        *text section* date *mark* pagenumber  
.3.        *text section* date *mark* pagenumber

### `\setuptype[.]=..]`

space       on off  
option       slanted normal none

## `\setuptyping[...][...=...]`

... file typing *name*  
space on off  
page yes no  
option slanted normal commands color none  
before *command*  
after *command*  
margin *dimension* standard  
evenmargin *dimension*  
oddmargin *dimension*  
blank *dimension* small medium big standard halfline line  
escape ^  
indentnext yes no

## `\setupunderbar[...=...]`

alternative a b c  
linethickness *dimension*

## `\setupversions[...=...]`

number *number*  
style normal bold slanted boldslanted type cap small... *command*

## `\setupwhitespace[...]`

... none small medium big line fixed fix *dimension*

## `\sheet[...]`

... *text*

## `\showbodyfont[...=...]`

... see `\setupbodyfont`

## `\showbodyfontenvironment[...=...]`

... see `\setupbodyfont`

## `\showbuildup`

## `\showcolor[...]`

... *name*

## `\showcolorgroup[.1.][...2,...]`

.1. *name*  
.2. horizontal vertical name value number

## `\showexternalfigures`

`\showfields[...,...,...]`

...     *name*

`\showframe[...]`

...     text margin edge

`\showgrid`

`\showlayout`

`\showmakeup`

`\showpalet[.1.][...,.2.,...]`

.1.     *name*  
.2.     horizontal vertical name value

`\showprint[...,.1.,...][...,.2.,...][...,.=.,...]`

... ..    see `\setuppapersize`  
... ..    see `\setuppapersize`  
... ..    see `\setuplayout`

`\showsetups`

`\showstruts`

`\showsymbolset[...]`

...     *name*

`\somedline[ref]`

`\sort[.1.]{.2.}`

.1.     *text*  
.2.     *text*

`\space`

`\splitfloat[...,.=.,...]{.1.}{.2.}`

... ..    see `\setupfloatsplitting`

`\startalignment ... \stopalignment[...]`

... see `\setupalign`

`\startbackground ... \stopbackground`

`\startblocktext[.1.][ref]{.2.}{.3.} ... \stopblock`

.1. left right high middle low offset tall  
.2. text  
.3. text  
.4. text

`\startbuffer[...] ... \stopbuffer`

... *name*

`\startcolor[...] ... \stopcolor`

... *name*  
... *text*

`\startcolumns[,,,=,,,] ... \stopcolumns`

... see `\setupcolumns`

`\startcombination[...] ... \stopcombination`

... *n\*m*

`\startcomment[...][,,,=,,,] ... \stopcomment`

... *name*  
... see `\setupcomment`

`\startcomponent ... .. \stopcomponent`

... *file*

`\startdescription{...} ... \stopdescription`

... *text*

`\startdocument[...] ... \stopdocument`

... *name*

`\startenumeration ... \stopenumeration`

`\startenvironment ... \stopenvironment`

... *file*

`\startfact\geg.1.\.2.\.3.\.\geg ... \stopfact`

.1. *text*

.2. *text*

.3. *text*

`\startfigure[.1.][.2.][...,...=...,...] ... \stopfigure`

.1. *name*

.2. *file*

factor *number*

frame on *off*

`\startformula ... \stopformula`

... *formula*

`\startframedtext[...][...,...=...,...] ... \stopframedtext`

... left right middle

..=.. see `\setupframedtexts`

`\starthiding ... \stophiding`

`\startinteractionmenu[...] ... \stopinteractionmenu`

... *name*

`\startitemize[.....][...,...=...,...] ... \stopitemize`

... a A KA n N m r R KR *number* continue standard *n*\*broad *n*\*serried packed stopper joinedup atmargin inmargin  
intro columns

..=.. see `\setupitemize`

`\startlegend[.1.]\leg.2.\.3.\.4.\.\leg ... \stoplegend`

.1. *two*

.2. *text*

.3. *text*

.4. *text*

`\startline[ref] ... \stopline`

`\startlinecorrection ... \stoplinecorrection`

`\startlinenumbering[...] ... \stoplinenumbering`

... continue

`\startlines ... \stoptlines`

`\startlocal ... \stoplocal`

`\startlocalenvironment ... \stoplocalenvironment`

`\startlocalfootnotes ... \stoplocalfootnotes`

`..=..` see `\setupfootnotes`

`\startmakeup[...][...,...=...,...] ... \stopmakeup`

`...` *name*

`..=..` see `\setupmakeup`

`\startmarginblock ... \stopmarginblock`

`\startmarginrule[...]` ... `\stopmarginrule`

`...` *number*

`\startnamemakeup ... \stopname`

`\startnarrower[.,.,.,.,.] ... \stopnarrower`

`...` *n\*left n\*middle n\*right*

`\startopposite ... \stopopposite`

`\startoverlay[...]` ... `\stopoverlay`

`...` {...}

`\startoverview[.,.,.,.,.] ... \stopoverview`

`...` *name*

`\startpacked[.,.,.,.,.] ... \stoppacked`

`...` *blank*

`\startparagraphs ... \stopparagraphs`

`\startpositioning ... \stoppositioning`

```
\startpostponing ... \stoppostponing
```

```
\startproduct ... \stopproduct  
... file
```

```
\startprofile[.....] ... \stopprofile  
... name
```

```
\startproject ... \stopproject  
... file
```

```
\startquotation[.....] ... \stopquotation  
... n*left n*middle n*right
```

```
\startsymbolset[...] ... \stopsymbolset  
... name
```

```
\startsynchynchronization ... \stopsynchynchronization
```

```
\starttable[...] ... \stoptable  
... text name
```

```
\starttextrule[.1.]{.2.} ... \stoptextrule  
.1. top bottom  
.2. text
```

```
\starttyping ... \stoptyping
```

```
\startunpacked ... \stopunpacked
```

```
\startversion[.....] ... \stopversion  
... number
```

```
\sub[ref,..]
```

```
\subject[ref,..]{...}  
... text
```

`\subsection[ref,...]{...}`

... *text*

`\subsubject[ref,...]{...}`

... *text*

`\subsubsection[ref,...]{...}`

... *text*

`\subsubsubject[ref,...]{...}`

... *text*

`\switchtobodyfont[...,...,...]`

... 5pt ... 12pt small big global

`\sym{...}`

`\symbol[.1.][.2.]`

.1. *name*

.2. *name*

`\synchronizationbar[...][...=...]`

... *name*

alternative page local

... see `\setupsynchronizationbar`

`\synchronize`

`\synonym[.1.]{.2.}{.3.}`

.1. *text*

.2. *text*

.3. *text*

`\tab{.1.}.2.\par`

.1. *text*

.2. *text*

`\tex{...}`

... *text*

`\textreference[ref]{...}`

... *text*

`\textrule[.1.]{.2.}`

.1. top bottom  
.2. *text*

`\thinrule`

`\thinrules[..=..]`

..=.. see `\setupthinrules`

`\title[ref,..]{...}`

... *text*

`\tooltip[.1.]{.2.}`

.1. left right middle  
.2. *text*

`\translate[...]=...]`

*name* *text*

`\typ{...}`

... *text*

`\type{...}`

... *text*

`\typebuffer[...]`

... *name*

`\typefile{...}`

... *file*

`\underbar{...}`

... *text*

`\underbars{.. ... ..}`

... *text*

`\useblocks[...1,...][...2,...]`

- .1. *name*
- .2. *name*

`\usecommands{...}`

`\useexternaldocument[.1.][.2.][.3.]`

- .1. *name*
- .2. *file*
- .3. *text*

`\useexternalfigure[.1.][.2.][...=...]`

- .1. *name*
- .2. *file*
- scale *number*
- factor *max fit broad*
- wfactor *number max broad fit*
- hfactor *number max broad fit*
- width *dimension*
- height *dimension*
- frame *on off*
- preset *yes no*
- preview *yes no*

`\useexternalfile[.1.][.2.][.3.][...=...]`

- .1. *name*
- .2. *name*
- .3. *file*
- bodyfont *5pt ... 12pt small big*

`\useexternalfiles[...][...=...]`

- ... *name*
- bodyfont *5pt ... 12pt small big*
- file *file*

`\usemodule[...]`

- ... *name*

`\userferences{...}`

- ... *file*

`\usespecials[...]`

- ... *reset name*

`\usesymbols[...]`

- ... *name*

`\useURL[.1.][.2.][.3.][.4.]`

- .1. *name*
- .2. *text*
- .3. *file*
- .4. *text*

`\version[...]`

... final concept temporary

`\v1[...]`

... *number*

`\WEEKDAY{...}`

... *number*

`\weekday{...}`

... *number*

`\whitespace`

`\WORD{...}`

... *text*

`\Word{...}`

... *text*

`\wordright{...}`

... *text*

`\WORDS{.. ... ..}`

... *text*

`\Words{.. ... ..}`

... *text*

`\writebetweenlist[.1.]{.2.}`

.1. *section name*

`\writetolist[.1.]{.2.}{.3.}`

.1. *section name*

`\writetoreferencelist[.1.]{.2.}{.3.}`

.1.      *name*

`\writetoregister[.1.][.2.]{...3.+..}`

.1.      *singular name*

.2.      *text*

.3.      *text*







**PRAGMA ADE**  
**Ridderstraat 27, 8061GH Hasselt NL**