

# XFree86 Font De-uglification HOWTO

**Hal Burgiss**

hal@foobox.net

**Original Author: Doug Holland**

meldroc@frii.com

v1.8, 25 June 2001

How to improve ugly and unreadable X Window fonts. Various tips for improving font handling for XFree86, including sections on font servers, TrueType fonts, Netscape, and related topics.

---

# Table of Contents

<b><u>1. Introduction</u></b> .....	<b>1</b>
<u>1.1. Conventions Used in this Document</u> .....	1
<u>1.2. Change Log and What's New</u> .....	2
<u>1.3. New Versions</u> .....	2
<u>1.4. Copyright</u> .....	2
<u>1.5. Credits</u> .....	3
<u>1.6. Translations</u> .....	3
<b><u>2. X Server Configuration</u></b> .....	<b>4</b>
<u>2.1. Setting The FontPath</u> .....	4
<u>2.2. X Server Command Line Options</u> .....	5
<b><u>3. TrueType Fonts (One of the few things Windows is good for)</u></b> .....	<b>6</b>
<u>3.1. Making TrueType Fonts Available</u> .....	6
<u>3.2. Font Servers</u> .....	7
<u>3.2.1. xfstt</u> .....	8
<u>3.2.2. Redhat's xfs</u> .....	9
<u>3.3. xfstt</u> .....	12
<u>3.4. The fonts.alias File</u> .....	13
<b><u>4. XFree86 4.x</u></b> .....	<b>15</b>
<u>4.1. Anti-aliasing</u> .....	16
<u>4.1.1. Requirements</u> .....	16
<u>4.1.2. Installation</u> .....	17
<u>4.1.3. Xft Configuration</u> .....	17
<u>4.1.4. Afterword</u> .....	25
<u>4.2. Redhat 7.x Differences</u> .....	26
<b><u>5. Adjusting Fonts in Specific Applications</u></b> .....	<b>27</b>
<u>5.1. KDE</u> .....	27
<u>5.1.1. Applying KDE Fonts and Colors to non-KDE Applications</u> .....	27
<u>5.2. Netscape</u> .....	27
<b><u>6. Odds and Ends</u></b> .....	<b>29</b>
<u>6.1. Notes</u> .....	29
<u>6.2. Links</u> .....	29

# 1. Introduction

One of the most annoying problems many of us are faced with is the poor default fonts and font settings of X as implemented by many distributions. I'm talking specifically about [XFree86](#), other versions of X may be better. Many programs use fixed width default fonts when a variable width font would be more appropriate. Other programs use fonts that are so small as to be practically unreadable. The fonts that are bundled with XFree86 are not of the same quality as found on some other platforms. XFree86 does come with a halfway decent courier font, but its Times and Helvetica fonts are simple bitmap fonts that pixelize when they are scaled. This is changing for the better recently, but a default Linux desktop still often needs some tweaking to get the best fonts possible.

This HOWTO attempts to show how to adjust various font settings, install new fonts, and do other things that should greatly improve the appearance and readability of fonts on the X Window Desktop. This is done by adjusting the `FontPath` in the `XF86Config` file, by adding switches to X server command line in `startx` or `xdm` (and variants), by adding new fonts, and by installing a TrueType font server and fonts. TrueType does indeed make a huge difference.

Comments, corrections, additions and critiques are always welcome. You can reach the author at [<hal@foobox.net>](mailto:hal@foobox.net). Contributions are also welcomed. Especially anyone who really stays current with KDE and/or Gnome issues!

---

## 1.1. Conventions Used in this Document

- Where examples of commands are used, a "#" character is used to denote where typically the command would be run as the root user. A "\$" is used where typically a non-root user would be executing the command.
- The examples use `/usr/local/share/fonts/ttfonts` as our TrueType font directory. There is no magic to this location, and could conceivably just as well be in any number of other locations. Some distros may have a default location for TrueType fonts, and you may want to use that instead.
- References to "xfs" are to the xfs as packaged by Redhat for versions 6.x and later. This differs significantly in some respects from the stock XFree86 xfs.
- References to "Netscape" are to the entire suite of programs from Netscape: Communicator, Navigator, Messenger, etc. And for all intents and purposes, font configuration in Mozilla is very similar.
- 'XF86Config' is the X configuration file. For Redhat based distros, as of Redhat 7.0, this is now 'XF86Config-4' for XFree86 4.x. For the most part, we'll just use 'XF86Config' here.

Also, while some aspects of XFree86 4.x configuration are the same as 3.3.x, there are some significant differences. We'll only highlight the differences. So unless noted otherwise, any comments or examples will apply to both 3.3.x and 4.x versions.

- File system layout varies somewhat from distribution to distribution. It is impossible to stay on top of every conceivable variation of who keeps which files where. So take the examples here with a grain of salt if the PATHs don't seem to match your system.
-

## 1.2. Change Log and What's New

- 1.8: June 25, 2001: Included a new section on Anti-aliasing and Xft from Danny Tholen <[obiwan@mailmij.org](mailto:obiwan@mailmij.org)>. Many thanks on this not so well documented subject. Sebastiano Vigna's neat little package for downloading and installing MS webfonts, being the most noteworthy: <http://freshmeat.net/webFonts4Linux>. A few other odds and ends.
  - 1.70: April 18, 2001: Added links for converting Mac TrueType Fonts (thanks to Karl A. Krueger), links to Unicode TrueType fonts (thanks to Tzafir Cohen for suggestions and URLs), and added a section on anti-aliasing with X 4.0.2 (or greater). Also, included a reference to [cabextract](#), a utility that is now available for extracting Win32 Fonts (among other things) from a Window's "cab" archive.
  - 1.60: March 21, 2001: A few very minor changes. Most notable news is anti-aliasing support now in XFree 4.02 (referenced in the Notes section only). Chinese translation URL added.
  - 1.55: Oct 11, 2000: Additional info on XFree86 4.x, especially Redhat's changes for RH7.0. A few other minor updates and additions. Also adding a neglected credit to Kristin Aanestad for his insight into much of what this document is all about.
  - 1.5: July 25, 2000: New sections added on fonts.alias, XFree86 4.x, and xfsft. Miscellaneous other changes and additions. Also, includes new Links and Notes sections, as well as a rewrite of the xfs sections. Various other changes and additions.
  - 0.1: Feb. 21, 1999: First release.
- 

## 1.3. New Versions

The pre-release versions of this document can be found at <http://feenix.burgiss.net/ldp/fdu/index.html>.

---

## 1.4. Copyright

Copyright © 1999 by Doug Holland.

Unless otherwise stated, Linux HOWTO documents are copyrighted by their respective authors. Linux HOWTO documents may be reproduced and distributed in whole or in part, in any medium physical or electronic, as long as this copyright notice is retained on all copies. Commercial redistribution is allowed and encouraged; however, the author would like to be notified of any such distributions.

All translations, derivative works, or aggregate works incorporating any Linux HOWTO documents must be covered under this copyright notice. That is, you may not produce a derivative work from a HOWTO and impose additional restrictions on its distribution. Exceptions to these rules may be granted under certain conditions; please contact the Linux HOWTO coordinator for more information.

In short, we wish to promote dissemination of this information through as many channels as possible. However, we do wish to retain copyright on the HOWTO documents, and would very much like to be notified of any plans to redistribute the HOWTOs, this one in particular! Web page authors are free to link to this HOWTO without restriction, though the author would appreciate an email informing him of this, just so he can boost his ego by knowing who else reads and links to this document.

Many of the terms mentioned in this document are trade names. Unless otherwise stated, all trademarks are property of their respective owners.

## 1.5. Credits

Created by Doug Holland.

Email: [meldroc@frii.com](mailto:meldroc@frii.com)

WWW: <http://www.frii.com/~meldroc/>

Updated and maintained by Hal Burgiss.

Email: [hal@foobox.net](mailto:hal@foobox.net)

WWW: <http://feenix.burgiss.net/ldp/fdu/>

Special thanks go to:

- The developers of the [XFree86 Project](#), for all the hard work and time they have given. Also, Juliusz Chroboczek for his work with xfsft, and XFree86 4.x to help bring TrueType to the hungry masses. And Keith Packard for his anti-aliasing, and other work. This is not to slight the many, many other XFree86 volunteers.
- Font wizard Kristin Aanestad, whose legwork and insight on much of the xfs, TrueType, Netscape, and especially, the fonts.alias sections are much appreciated. More from Kristin at [Some Linux for Beginners](#) on a wide range of topics.
- Danny Tholen <[obiwan@mailmij.org](mailto:obiwan@mailmij.org)> is responsible for the nice Xft section, and examples.
- The folks at [comp.os.linux.x](#) who gave me a hand in figuring all of this out in the first place.
- The Linux community in general who made all of this possible in the first place. Especially those who have offered suggestions and comments that help to make this HOWTO a better resource.
- Microsoft and Apple: for providing the fonts that adorn my desktop.

---

## 1.6. Translations

Chinese: <http://www.linux.org.tw/CLDP/mini/FDU.html> by Yu-Chia Chang.

---

## 2. X Server Configuration

There are a few easy steps that can be taken that will help X do its job better.

---

### 2.1. Setting The FontPath

The first place to look for curing font problems is the `XF86Config` file.

`/usr/X11/lib/X11/XF86Config` or `/etc/X11/XF86Config` are the common locations. (This may be `XF86Config-4` for XFree86 4.x.) If you haven't guessed already, the most important part of this file relating to fonts is the `FontPath`. Before we get into that, this would be a good time to check the other parts of your X configuration. Bad monitor settings can be even more of a headache than bad fonts, so make sure your refresh rate is as high as your monitor can handle (85 Hz is great, 75 Hz is OK, 60 Hz is painful.)

Use your favorite text editor and edit `XF86Config`. Near the top of the file in the "Files" section, you should see something vaguely like this:

```
FontPath    "/usr/X11R6/lib/X11/fonts/misc/"
FontPath    "/usr/X11R6/lib/X11/fonts/Type1/"
FontPath    "/usr/X11R6/lib/X11/fonts/Speedo/"
FontPath    "/usr/X11R6/lib/X11/fonts/75dpi/"
FontPath    "/usr/X11R6/lib/X11/fonts/100dpi/"
```

This much should be the same, or at least similar, for both XFree86 3.x and 4.x. The `FontPath` tells X where to find the fonts it uses to render text on your display. Order is important -- when an X application asks X to render some text, the X server usually has some leeway to choose the font that is used. The X server then goes through the `FontPath` and grabs the first font it sees that matches the X client's criteria, and then displays. (Note that Redhat's xfs for versions 6.x and later has a different way of setting the `FontPath`. See the [Section 3.2.2](#) below for more on xfs.)

If the 100dpi fonts are not listed, they probably did not get installed for whatever reason, so you may want install them now. Default installations may put 75dpi fonts before the 100dpi fonts. If you have a high resolution display (1024x768 or higher), this means very tiny fonts. If this is the case, the first tweak you'll use is to switch the 75dpi and 100dpi `FontPath` lines:

```
FontPath    "/usr/X11R6/lib/X11/fonts/misc/"
FontPath    "/usr/X11R6/lib/X11/fonts/Type1/"
FontPath    "/usr/X11R6/lib/X11/fonts/Speedo/"
FontPath    "/usr/X11R6/lib/X11/fonts/100dpi/"
FontPath    "/usr/X11R6/lib/X11/fonts/75dpi/"
```

Next, specify that you prefer to use unscaled bitmap fonts. If you've ever used Netscape or any other program that displays titles using big fonts, you'll likely notice that those fonts are pixelized. This is ugly and needs to be corrected. So add `:unscaled` to the ends of the `misc`, `100dpi` and `75dpi` fonts. You can even use both unscaled and scaled fonts if you want, just put the unscaled `FontPath` lines first to tell X you prefer

unscaled fonts if possible:

```
FontPath    "/usr/X11R6/lib/X11/fonts/misc:unscaled"  
FontPath    "/usr/X11R6/lib/X11/fonts/100dpi:unscaled"  
FontPath    "/usr/X11R6/lib/X11/fonts/75dpi:unscaled"  
FontPath    "/usr/X11R6/lib/X11/fonts/Type1"  
FontPath    "/usr/X11R6/lib/X11/fonts/Speedo"  
FontPath    "/usr/X11R6/lib/X11/fonts/misc"  
FontPath    "/usr/X11R6/lib/X11/fonts/100dpi"  
FontPath    "/usr/X11R6/lib/X11/fonts/75dpi"
```

After making these changes, restart X. Doesn't the desktop look better already?

---

## 2.2. X Server Command Line Options

The next thing you need to do is adjust the command line options for the X server. You'll want to use the `-dpi` switch which specifies the display resolution in dots per inch. As a lot of systems use high resolution displays these days, chances are they'll be working at 100 dpi.

If you start X from the console command prompt, type:

```
$ startx -dpi 100 -depth 16
```

Or these options can be stored in `~/.xserverrc`. See the **startx** and **xinit** man pages for more on this.

If you use `xdm` (or friends such as `gdm`) for graphical logins, you'll want to edit your `/usr/X11/lib/X11/xdm/Xservers` file (or possibly `/etc/X11/xdm/Xservers`) which will have the command line for the Xserver in it. Mine has the line:

```
:0 local /usr/X11R6/bin/X -dpi 100 -gamma 1.6
```

Note that there is no magic to `"-dpi 100"`. Choose something higher if your hardware will support it — like `"-dpi 120"`.

More information is in the **X**, **Xserver**, **xdm**, **xinit**, and **startx** man pages.

---

## 3. TrueType Fonts (One of the few things Windows is good for)

Because the boys at Redmond are very concerned with the appearance of their software (as opposed to the internal workings ;) they built TrueType font support into Windows. And of course no big surprise, but they got the idea from Apple. In fact, TrueType is a registered trademark of Apple Computer, Inc. Windows 9x and nearly every other incarnation of Windows comes with Arial, Times New Roman, and Courier New, which are roughly equivalent to Helvetica, Times and Courier. TrueType fonts are scalable, so they look good in large sizes, and they are well hinted, so they are readable at small sizes. Many windows applications come with dozens more TrueType fonts. Don't microwave your Windows CD yet, you'll want to get those fonts first!

Unfortunately, XFree86 3.x does not come with built in TrueType support, so you'll have to add it yourself (see below). This will mean installing a font server that does support TrueType and, of course, installing the fonts themselves. XFree86 4.x does have built in support however (see [Section 4](#)). You won't find many decent TrueType fonts included with any distribution. The likely reason is that there are not many quality TrueType fonts available under a suitable license at this time.

---

### 3.1. Making TrueType Fonts Available

Let's start with the fonts first. Any TrueType font included with the various MS Windows incarnations should work. Don't forget word processors and other apps that may include their own fonts. MacOS fonts will only work if converted to a usable format. (See the [links section](#) for converter packages.) There are also some 'free' TrueType fonts available for download if you have already nuked that CD (see [links section](#)).

In order to use TrueType, the fonts will have to be always accessible to the font server. This means they will have to be on a filesystem that is *always* mounted. This can conceivably be a Windows partition on a dual boot system. Alternately, the fonts can be copied to Linux. First **su** to root:

```
# su -  
# mkdir -p /usr/local/share/fonts/ttfonts
```

Now, change to the new font directory:

```
# cd /usr/local/share/fonts/ttfonts
```

Then, add the fonts to this directory, either by copying them from your Windows system:

```
# cp /mnt/<path_to_fonts>/*.ttf .
```

or by downloading those available directly from Microsoft:

<http://www.microsoft.com/typography/fontpack/default.htm>. These fonts are in self-extracting zip archives. The ones labeled for use with Windows 3.1 can indeed be unpacked under Linux with the Linux **zip** utility:

```
# ls *exe | xargs -n 1 unzip -L
```

The '-L' option will convert to lower case font names (this may be necessary for some versions of xfsft and Redhat's xfs). Note that the current Linux zip utility does not work with the 32 bit Win9x cab font archives. (It also looks like Microsoft no longer has the 16 bit Arial, Courier and Times-Roman on this site.) But these can be unarchived under Linux with **cabextract**, which can be found <http://www.kyz.uklinux.net/cabextract.php3>. This would now seem to be the best way to go since there is a better selection of fonts.

A slick solution to this from Sebastiano Vigna is his <http://freshmeat.net/webFonts4Linux>, which automates the downloading, extracting and installation of the Microsoft fonts all in one neat package.

Or you can get an RPM of WebFonts that contains some of the MS 'Web' TrueTypes from <ftp://ftp.rpmfind.net/linux/contrib/noarch/noarch/webfonts-1-3.noarch.rpm>. This has enough basic fonts to keep Netscape and other web browsers happy. Something similar for Debian is <http://packages.debian.org/unstable/graphics/msttcorefonts.html>. This does not include the actual fonts, but facilitates the installation.

You will also have to include the new TrueType directory(s) in the X server's fontpath. So with your text editor of choice add the line(s) as appropriate:

```
FontPath    "/usr/local/share/fonts/ttfonts"
FontPath    "/usr/X11R6/lib/X11/fonts/misc:unscaled"
FontPath    "/usr/X11R6/lib/X11/fonts/100dpi:unscaled"
FontPath    "/usr/X11R6/lib/X11/fonts/75dpi:unscaled"
FontPath    "/usr/X11R6/lib/X11/fonts/Type1"
FontPath    "/usr/X11R6/lib/X11/fonts/Speedo"
FontPath    "/usr/X11R6/lib/X11/fonts/misc"
FontPath    "/usr/X11R6/lib/X11/fonts/100dpi"
FontPath    "/usr/X11R6/lib/X11/fonts/75dpi"
```

---

## 3.2. Font Servers

There are several font servers available that will do the job: xfstt, xfsft, and Redhat's patched version of xfs based on xfsft. While these names are all too similar, these are different packages. One, or more, of these should be included with any recent Linux distribution, and you may have one installed already.

Historically, font servers were used to serve fonts over a network. Font resources could then reside on one host, and clients could access them as needed. But, the developers have enhanced these to include features such as the ability to render TrueType fonts. (XFree86 4.x has this ability included already, and thus an additional font server is not really needed solely for the purpose of having TrueType support.)

---

### 3.2.1. xfstt

One such font server is xfstt. xfstt was designed specifically with TrueType fonts in mind.

---

#### 3.2.1.1. Installation

xfstt is *very* easy to install and configure. If it isn't already installed, you'll want to download the tarball, or check your CD. The most current version can be found at <http://metalab.unc.edu/pub/Linux/X11/fonts/>

Once you have the tarball, unpack it:

```
$ tar -zxvf xfstt-*.tgz
```

Then build and install it. Read the INSTALL file for quick instructions, but it's a no brainer.

From the xfstt directory is all you have to do.

```
# make
# make install
```

Then start xfstt with:

```
# xfstt --sync      # updates xfstt's font database
# xfstt &          # runs xfstt in the background.
```

xfstt should be started before the X server starts. Once you have this working correctly, you can add the above lines to `/etc/rc.d/rc.local`, or other suitable start up file. Then type:

```
$ xset +fp unix/:7101 # tells X about xfstt, and where to look for fonts.
```

or add:

```
FontPath "unix/:7101"
```

to your XF86Config to tell X about the font server. Rerun **xfstt --sync** any time the FontPath, or contents, change.

---

#### 3.2.1.2. Adjusting the Default Font Size

If your TrueType fonts appear to be very tiny, the following commands may help.

Add the `-dpi` switch to your X server command line (see section 3 above to do this.)

Use the `--res` switch to tell `xfstt` to increase the default resolution. Use the following command line.

```
# xfstt --res 120
```

---

### 3.2.2. Redhat's xfs

As of Redhat Linux 6.0, Redhat based distributions (Mandrake, etc) have included a specially patched version of `xfs`, the XFree86 Font Server, and patched X servers as well. Redhat's `xfs` includes the `xfstt` patch set which in turn is built upon the FreeType Font library. Redhat's `xfs` provides similar functionality to `xfstt`. `xfs` is able to serve both TrueType and Type 1 fonts, as well as legacy X fonts.

If you are using a Redhat based distro, you should have `xfs` installed already. If not, it is in the `XFree86-xfs*rpm`. To make sure it runs as one of the default services, either use `ntsysv` or:

```
# chkconfig --add xfs
```

Now `xfs` will start every time you boot.

---

#### 3.2.2.1. Setting the xfs FontPath

The default Redhat installation of `xfs` serves fonts via a Unix Domain Socket. We'll need to tell the X server where to look for `xfs`, and thus fonts. The `FontPath` in `/etc/X11/XF86Config` must include for Redhat 6.x:

```
FontPath "unix:/-1"
```

This is changed for Redhat 7.x to:

```
FontPath "unix:/7100"
```

At least for a default configurations. This is a reference to the socket where `xfs` is listening. You may include additional `FontPaths`, but these will be handled by the X server, and not `xfs`. A clean install of Redhat 6/7 should have this already set up, but if you are upgrading from an older version, you may have to change this yourself!

`xfs` then has its own, separate `FontPath` stored in `/etc/X11/fs/config`. This is where it will look to find fonts. This is over and above the X server's `FontPath` in `XF86Config`. You can either add the new path(s) with a text editor, or use the **`chkfontpath`** command:

```
# chkfontpath --add /new/font/path
```

The `FontPath` must exist before running **`chkfontpath`**. The relevant section of `/etc/X11/fs/config` should now look something like this:

```
catalogue = /usr/X11R6/lib/X11/fonts/misc:unscaled,
            /usr/X11R6/lib/X11/fonts/100dpi:unscaled,
            /usr/X11R6/lib/X11/fonts/75dpi:unscaled,
            /usr/X11R6/lib/X11/fonts/Type1,
            /usr/X11R6/lib/X11/fonts/Speedo,
            /usr/X11R6/lib/X11/fonts/misc,
            /usr/X11R6/lib/X11/fonts/100dpi,
            /usr/X11R6/lib/X11/fonts/75dpi,
            /new/font/path
```

When adding a new FontPath for TrueType fonts, you will want to do this step after installing and preparing the fonts. See the next section.

---

### 3.2.2.2. Getting the Fonts Ready

We still have a bit of work to do before we can actually use any TrueType fonts. xfs requires a few things to be in order. First, all font files must have lower case names for xfs. Secondly, they shouldn't have embedded spaces. And then, we will need to create a couple of files to make things go.

Su to root, and change to the directory where the TrueType fonts are.

```
# su -
# cd /usr/local/share/fonts/ttfonts
```

If there are any upper case font names, you can use the following script to convert all names to lower case:

```
#!/bin/sh
#
## ----- convert upper to lower case -----

ls * | while read f
do
  if [ -f $f ]; then
    if [ "$f" != "`echo \"$f\" | tr A-Z a-z`" ]; then
      #Note that 'This' will overwrite 'this!'
      mv -iv "$f" "`echo \"$f\" | tr A-Z a-z`"
    fi
  fi
done

## eof
```

## XFree86 Font De-uglification HOWTO

Note the punctuation — the backquotes are important! Remove any spaces from font names too. Once the TrueType fonts are properly installed, you must create both `fonts.dir` and `fonts.scale` files. The following commands do this:

```
# ttmkfdir -o fonts.scale
# mkfontdir
```

You should now have `fonts.dir` and `fonts.scale` files in your TrueType font directory. **ttmkfdir** is in the `Freetype` RPM, and must be run before **mkfontdir**. With Debian based distros, there is a similar utility called **mkttfdir**, and is in the `fttools` Deb package. Though this apparently does not generate as many encodings as **ttmkfdir**. These commands may not always report errors, so verify that they were created and are not empty files:

```
$ ls -l fonts.*
-rw-r--r-- 1 root root 11657 Aug 17 10:31 fonts.dir
-rw-r--r-- 1 root root 11657 Aug 17 10:31 fonts.scale
```

If you encounter any problems, try **ttmkfdir** with the `-m` switch. This will discard bad characters from the font file. Specify a number such as 50 or 100 (**ttmkfdir -m 50**). The files themselves are text files. Have a look:

```
$ less fonts.dir
114
webdings.ttf -microsoft-Webdings-medium-r-normal--0-0-0-0-p-0-microsoft-symbol
verdanaz.ttf -microsoft-Verdana-bold-i-normal--0-0-0-0-p-0-ascii-0
verdanaz.ttf -microsoft-Verdana-bold-i-normal--0-0-0-0-p-0-fcd8859-15
verdanaz.ttf -microsoft-Verdana-bold-i-normal--0-0-0-0-p-0-iso8859-15
verdanaz.ttf -microsoft-Verdana-bold-i-normal--0-0-0-0-p-0-iso8859-9
verdanaz.ttf -microsoft-Verdana-bold-i-normal--0-0-0-0-p-0-iso8859-1
[...]
```

Next, update the `FontPath` and `xfs`:

```
# chkfontpath --add /usr/local/share/fonts/ttfonts
# /etc/rc.d/init.d/xfs restart
```

You should now be in business. You can check which fonts are available to X:

```
$ xlsfonts | less
```

or check them out further with **xfontsel**, or **gfontsel**. If they are visible to **xlsfonts**, then they are available to X and vice versa. If they are not there, try restarting X with `Ctrl-Alt-BS`.

---

### 3.3. xfsft

[xfsft](#) is a TrueType solution from Juliusz Chroboczek. xfsft is based on the FreeType font library as developed by Mark Leisher and others. It is essentially a patch for XFree86's xfs and related libraries -- xfs + ft. Redhat's xfs is essentially xfsft with a few minor modifications. Also, XFree86 4.x includes the freetype font module which is also the result of Juliusz's work, and is one of the TrueType solutions available for XFree86 4.x.

Building xfsft requires having at least some of the XFree86 source available, in addition to xfsft itself, so this is not for the faint of heart. Instructions for building and configuring xfsft are in the tarball, so I won't go into details here. They are pretty straight forward. There are links to binaries available at the xfsft home page (see above).

Note that you *must* also create `fonts.scale` and `fonts.dir` files for xfsft. `fonts.scale` can be created manually (ugh!), or with the **ttmkfdir** utility. This is not included with xfsft but you can get it here: <http://www.joerg-pommnitz.de/TrueType/ttmkfdir.tar.gz>, or probably on many Linux archives sites too. Redhat has this as part of the FreeType RPM. And for Debian it is called **mkttfdir** and is in the `fttools` package.

You will also need a configuration file. Here is a sample:

```
-----
clone-self = off
use-syslog = off

client-limit = 20

catalogue = /usr/local/share/font/ttfonts

error-file = /home/jec/fonts/xfs.errors

# in decipoints
default-point-size = 120

# x,y
default-resolutions = 100,100,75,75
-----
```

You can then run start xfsft:

```
# xfs -port 7100 -config /path/to/your/config/file &
```

You can then add xfsft to the X server's FontPath:

```
$ xset +fp tcp/localhost:7100
```

If all goes well, you could then add this `FontPath` to `XF86Config`.

---

### 3.4. The `fonts.alias` File

`fonts.alias` is yet another font configuration file that can be used to tweak how fonts are handled. Like `fonts.scale` and `fonts.dir`, `fonts.alias` must be in the same directory as the fonts you are aliasing. It is not mandatory however, but does solve certain potential problems. Here is an example from the first line of `/usr/X11R6/lib/X11/fonts/misc/fonts.alias` on a Redhat system:

```
fixed -misc-fixed-medium-r-semicondensed--13-120-75-75-c-60-iso8859-1
```

`fixed` is the 'alias' here. Any time this is requested, we actually get the font definition from the second column. Font too small? Just change the definition. (Warning: this is a critical file, at least on Redhat.) The same principle applies to all fonts, including TrueType. In fact, if you don't have TrueType, you could conceivably use this trick to have a comparable Type 1, or other, font aliased as a TrueType.

`fonts.alias` is important for some applications that don't handle the data provided by `fonts.scale` well. Most notably here is Netscape. Without a `fonts.alias` you will find that Netscape will only show point sizes of 0 and 12 available. `fonts.alias` fixes this. You might also find that if you specify another size with the `scalable font` option under Preferences, Netscape will not remember this setting. Annoying! This is also fixed. So we really need this file. Sample excerpt from a `fonts.scale`:

```
arial.ttf -monotype-Arial-medium-r-normal--0-0-0-0-p-0-ascii-0
arial.ttf -monotype-Arial-medium-r-normal--0-0-0-0-p-0-fcd8859-15
arial.ttf -monotype-Arial-medium-r-normal--0-0-0-0-p-0-iso8859-15
arial.ttf -monotype-Arial-medium-r-normal--0-0-0-0-p-0-iso8859-1
```

These are scalable so we don't get any predefined point sizes. We will need to create our `fonts.alias` something like this excerpt for Arial:

```
-monotype-Arial-medium-r-normal--6-60-0-0-p-0-iso8859-1 \
    -monotype-Arial-medium-r-normal--9-90-75-75-p-0-iso8859-1

-monotype-Arial-medium-r-normal--7-70-0-0-p-0-iso8859-1 \
    -monotype-Arial-medium-r-normal--9-90-75-75-p-0-iso8859-1

-monotype-Arial-medium-r-normal--8-80-0-0-p-0-iso8859-1 \
    -monotype-Arial-medium-r-normal--10-100-75-75-p-0-iso8859-1

-monotype-Arial-medium-r-normal--9-90-0-0-p-0-iso8859-1 \
    -monotype-Arial-medium-r-normal--11-110-75-75-p-0-iso8859-1

-monotype-Arial-medium-r-normal--10-100-0-0-p-0-iso8859-1 \
    -monotype-Arial-medium-r-normal--12-120-75-75-p-0-iso8859-1
```

## XFree86 Font De-uglification HOWTO

```
-monotype-Arial-medium-r-normal--11-110-0-0-p-0-iso8859-1 \  
  -monotype-Arial-medium-r-normal--12-120-75-75-p-0-iso8859-1  
  
-monotype-Arial-medium-r-normal--12-120-0-0-p-0-iso8859-1 \  
  -monotype-Arial-medium-r-normal--12-120-75-75-p-0-iso8859-1  
  
-monotype-Arial-medium-r-normal--13-130-0-0-p-0-iso8859-1 \  
  -monotype-Arial-medium-r-normal--13-130-75-75-p-0-iso8859-1  
  
-monotype-Arial-medium-r-normal--14-140-0-0-p-0-iso8859-1 \  
  -monotype-Arial-medium-r-normal--14-140-75-75-p-0-iso8859-1  
  
-monotype-Arial-medium-r-normal--15-150-0-0-p-0-iso8859-1 \  
  -monotype-Arial-medium-r-normal--15-150-75-75-p-0-iso8859-1  
  
-monotype-Arial-medium-r-normal--18-180-0-0-p-0-iso8859-1 \  
  -monotype-Arial-medium-r-normal--18-180-75-75-p-0-iso8859-1  
  
-monotype-Arial-medium-r-normal--24-240-0-0-p-0-iso8859-1 \  
  -monotype-Arial-medium-r-normal--24-240-75-75-p-0-iso8859-1
```

*(Please note that I have split each line for readability. There should be two columns all on one line, without the "\", and separated by at least one space.)* This will keep Netscape happy. Also, if font names should have embedded spaces, then you should enclose the filename in quotes. You might also note the pointsize discrepancy between the first and second columns of the first few rows. The first column of the first entry has a '6', whereas this is aliased to a '9' in the second column, and thus '9' point. This is by design and is an excellent way to overcome the Netscape 'damn tiny fonts' syndrome. Adjust to suit your tastes, resolution, and eyesight.

This file can be created manually with a text editor, or conceivably with some fancy sed or awk scripting. There is an excellent discussion of this file, and other font related topics at Kristin Aanestad's site at <http://home.c2i.net/dark/linux.html>. There is also a link to a python script which can reportedly automatically generate a `fonts.alias` file at this same site. Thanks to Kristin whose work and insight was the inspiration for this section!

Note that with XFree86 4.0.2 and greater, there are new font handling mechanisms available via the Xft extensions. Font aliasing is done in Xft's own configuration file: `XftConfig`. This is the preferred method where anti-aliasing, and the other new rendering features are desired. See the [Anti-aliasing Section](#) for more on this. This is only true where the application itself supports the new extensions! At this time, not many do yet.

---

## 4. XFree86 4.x

[XFree86 4.0](#) introduced native support for TrueType fonts, along with other new features. The enhanced font support is based on xfsft from Juliusz Chroboczek, which in turn is based on the FreeType font library originally from Mark Leisher, so the configuration is similar to xfsft and Redhat's patched xfs. As of 4.0.2, XFree86 begins to support anti-aliasing which is a technique for smoothing font outlines (see section below).

The `FontPath` is still in `XF86Config`, as always. For Redhat 6/7 using a stock XFree86 4.x (i.e. NOT the Redhat 7.x supplied version), this will mean moving the Redhat xfs `FontPath` from `/etc/X11/fs/config` back to `XF86Config`. A separate font server is no longer needed just for TrueType support. You may disable it, unless it is needed to serve fonts to other clients in a network environment. See the section below for Redhat 7.x specific configuration issues.

```
Section "Files"
FontPath "/usr/X11R6/lib/X11/fonts/misc:unscaled"
FontPath "/usr/X11R6/lib/X11/fonts/100dpi:unscaled"
FontPath "/usr/X11R6/lib/X11/fonts/75dpi:unscaled"
FontPath "/usr/X11R6/lib/X11/fonts/misc"
FontPath "/usr/X11R6/lib/X11/fonts/Type1"
FontPath "/usr/X11R6/lib/X11/fonts/Speedo"
FontPath "/usr/share/fonts/default/Type1"
FontPath "/usr/local/share/fonts/ttfonts"
FontPath "/usr/X11R6/lib/X11/fonts/100dpi"
FontPath "/usr/X11R6/lib/X11/fonts/75dpi"
EndSection
```

In order to use TrueType, you must also specify which font module the X server should be using in the "Module" section:

```
Section "Module"
Load "freetype"
Load "speedo"
Load "type1"
<load other modules....>
EndSection
```

Note that there can be only one 'Module' section, so include any other modules here as well.

You also must to create `fonts.scale` and `fonts.dir` file for each TrueType font directory, just like for xfsft and Redhat's xfs. [ttmkfdir](#) will come in handy for `fonts.scale`. See the xfs [Section 3.2.2](#) above for more details and examples.

`xtt` is another available TrueType module that is best known for supporting ideographic (Oriental) type fonts. You can use either, but only one at a time.

X server command line options are still the same as previous versions of X:

```
$ startx -dpi 100
```

---

## 4.1. Anti-aliasing

Anti-aliasing is a technique for producing even smoother, crisper looking fonts by subtly softening the sharp, jagged edges. This has long been a feature of Apple and Microsoft font rendering, and is now making its way into X via the X Rendering Extension specification thanks to Keith Packard. The new extensions provide other benefits as well. This is still a bit experimental at this time (June 2001). Distributions that support anti-aliasing with their stable/official versions are now being released.

That is the good news. The bad news is that not all drivers support anti-aliasing yet. This is a moving target, so you will have to dig around to find whether your chipset is supported or not. The recently released 4.1 should have near universal support. More not-so-good news is that few applications are actually taking advantage of this yet. We will have to wait for the various toolkits (TK, GTK, etc) to catch up.

If you are reading this long after the publication date (June 2001), hopefully most of these shortcomings will have been overcome. All hardware will eventually be supported, mainstream distros will have shipped releases that include the new extensions, and they will be enabled by default. Many apps will look better since they will be "AA" aware, and we won't have to jump through any configuration hoops just to make it work. In the meantime, read on ...

---

### 4.1.1. Requirements

Minimum requirements for Anti-Aliasing:

- XFree86 4.0.2 or later.
- Your graphic card's driver has to support anti-aliasing. If 4.0.2 (or greater) is already installed, you can get this information direct from the driver with `xdpinfo`. Run this and look for "Number of Extensions:". If this lists "RENDER" among them, then you should be good to go. If not, well, it isn't going to work, and you will have to wait for an updated driver.
- The FreeType2 library available from <http://www.freetype.org>, and also now bundled with XFree86. XFree needs to be linked against this, so install and build first if building from scratch. Your distro should have FreeType packages as well. Just make sure it is `freetype-2`.
- TrueType fonts are best for display purposes. Type1 is also good. See above sections.
- For KDE users, KDE supports anti-aliasing as of 2.x. This will require QT-2.3.0 or later, and built with Xft support. A nice font HOWTO from Troll Tech for KDE and QT can be found: <http://trolls.troll.no/~lars/fonts/qt-fonts-HOWTO.html>.

Gnome does not support anti-aliasing at this time (as of 1.4). Awaiting GTK implementation (probably for GTK 2.0). Apparently this will be available later this year, so stay tuned.

- Applications that "know" about anti-aliasing. Not necessarily at the individual application level, but the libraries and toolkits (GTK, TK, etc.) that the application are built against, must be able to use the new features. At this time, there are scant few. KDE/QT is first out of the box. Also, `xterm` supports the new extensions.
- The new rendering extensions configuration file, `XftConfig`, must be configured for the fonts you want to use.

- The new extensions supplant much of what we have been doing with font servers like xfs. `fonts.alias` and similar configuration files, for instance, are not used for fonts that are being controlled by the new extensions.
- 

### 4.1.2. Installation

Keith Packard has brief summary of the steps required for building, installing and configuring from source at <http://www.xfree86.org/~keithp/render/aafont.txt>. No need to reprint it here.

Newer distro releases are likely to have the foundation support for anti-aliasing available now. Redhat, for instance, has it available as of Redhat 7.1. Or look for the pre-release/unstable packages from your distro. This would be a good approach to take at this time if you want to be on the cutting edge, and may be more palatable for some than building each package from source.

To verify the necessary components, first make sure the "freetype" module (and any others) are loaded. Check the X server output:

```
(II) LoadModule: "freetype"  
(II) Loading /usr/X11R6/lib/modules/fonts/libfreetype.a  
(II) Module freetype: vendor="The XFree86 Project"  
    compiled for 4.0.3, module version = 1.1.9  
    Module class: XFree86 Font Renderer  
    ABI class: XFree86 Font Renderer, version 0.2  
(II) Loading font FreeType
```

Then verify if the "RENDER" extension is available, either check with `xdpyinfo`, or check the X server log, typically `/var/log/XFree86.0.log`:

```
(II) Initializing built-in extension MIT-SHM  
(II) Initializing built-in extension XInputExtension  
(II) Initializing built-in extension XTEST  
(II) Initializing built-in extension XKEYBOARD  
(II) Initializing built-in extension LBX  
(II) Initializing built-in extension XC-APPGROUP  
(II) Initializing built-in extension SECURITY  
(II) Initializing built-in extension XINERAMA  
(II) Initializing built-in extension XFree86-Bigfont  
(II) Initializing built-in extension RENDER
```

If "RENDER" is there, anti-aliasing and the other advanced rendering extensions should be enabled.

---

### 4.1.3. Xft Configuration

By Danny Tholen <[obiwan@mailmij.org](mailto:obiwan@mailmij.org)>

Xft is an interface to the freetype rasterizer written by Keith Packard, member of the XFree86 Project, Inc. It allows applications to use fonts from the new X render extension using a unified font naming scheme. In `/etc/X11/XftConfig` (or `/usr/X11R6/lib/X11/XftConfig`) you will find a configuration file which can be adapted to suit your personal taste. In this section I will explain the syntax and demonstrate some things you can do with this file.

The following information is based on 4.0.3. 4.1 is just released, and there may be a few new wrinkles not touched on here.

---

### 4.1.3.1. XftConfig Structure

The basic structure revolves around a 'pattern'. A pattern is a set of name/valuelist pairs, each valuelist contains one or more typed values. A certain application requests a font, for example:

```
family: "Arial"
size: 12
encoding: "iso8859-1"
```

A size 12 arial font in latin-1 encoding. The Xft extension will now try to patch this pattern to all of the fonts available in the system. And selecting the one with the best score. Before the matching is done Xft looks in `XftConfig`. The requested pattern can here be extended before use. An example is:

```
match any family == "Arial" edit antialias = true;
```

This will enable anti-aliasing for all fonts of the family Arial.

Also, the X server is queried to list all of its fonts; the XLFD contains just enough information to match fonts roughly.

Here's a list of attributes used in matching fonts (in priority order, this may not be up to date anymore!):

```
foundry    font foundry (string, like "monotype")
encoding   font encoding (string, like "iso8859-1")
spacing    font spacing (integers or proportional (0), mono (100),
             charcell (110))
bold       is the font bold? (boolean)
italic     is the font italic? (boolean)
antialias  is the font antialiased? (boolean)
family     font family (string)
size       font size (double)
style      font style (string, like "Bold Italic")
slant      font slant (roman, italic, oblique)
weight     font weight ( integers or light, medium (100), demi-bold,
             bold, black)
rasterizer not yet used (probably "TrueType", "Type1", ...)
outline    are outlines available? (boolean)
```

---

#### 4.1.3.2. XftConfig Syntax

- **dir**

Adds a directory to the list of places Xft will look for fonts. There is no particular order implied by the list; Xft treats all fonts about the same.

- **include and includeif**

Cause Xft to load more configuration parameters from the indicated file. "includeif" doesn't elicit a complaint if the file doesn't exist. If the file name begins with a "~" character, it refers to a path relative to the home directory of the user. This is useful for user-specific configurations.

- **match edit**

If a pattern from an application matches the pattern after "match", it is edited with the instructions in `edit`. The pattern match is done as follows:

```
match qual FIELD-NAME COMPARE CONSTANT
```

where `qual` is either `any` (matches one specific font) or `all` (matches all fonts). An example:

```
match all foundry=="monotype"
```

which will match (and edit) all fonts belonging to the foundry "monotype".

```
match any family=="arial"
```

will match (and edit) one specific font with the family name "arial".

`FIELD-NAME` is any one of the properties found in the above section [Structure](#), or additionally:

<code>pixelsize</code>	font size in pixels (integer)
<code>charspace</code>	character space (integer)
<code>minspace</code>	minimal spacing (integer)
<code>rgba</code>	color hinting (string "rgb" or "bgr" and vertical hinting "vrgb" "vbgr")
<code>xlfd</code>	x server font (string, type xlsfonts to see a list of your xlfd strings)
<code>file</code>	the font file (string)
<code>core</code>	use X core fonts? (boolean)
<code>render</code>	use render fonts? (boolean)
<code>index</code>	I have no idea what this does:)

## XFree86 Font De-uglification HOWTO

scalable      is the font scalable (boolean)  
scale         scale the font (integer)  
charwidth    character width (integer)  
charheight   character height (integer)  
matrix        no idea (not really at least)

COMPARE can be <, >, or ==.

CONSTANT is the value of the field-name in the appropriate type (see above section [Structure](#)).

You can use multiple matches before you use the "edit" statement:

```
edit FIELD-NAME ASSIGN EXPR SEMI
```

Where ASSIGN can be one of =, += or =+. With =, the matching value in the pattern will be replaced by the given expression. += or =+ will prepend/append a new value to the list of values for the indicated field.

EXPR sets the FIELD-NAME to a value.

SEMI is a semicolon (;). You can use multiple instructions, separated by a semicolon. See below for examples if this is confusing.

---

### 4.1.3.3. XftConfig Examples

And now I'll try to list a few useful configurations and explain them. Note that it is configured for my system, and I may use different fonts than you, so try to adapt the examples to your own needs.

#### 1. How do I make fonts available to Xft?

List your Type 1 and TrueType font directories with "dir". On my system (Mandrake 7.2) this becomes:

```
dir "/usr/X11R6/lib/X11/fonts/Type1"  
dir "/usr/X11R6/lib/X11/fonts/drakfont"
```

#### 2. How do I use a user specific XftConfig file?

Put an `.xftconfig` file in your user directory and add:

```
includeif "~/xftconfig"
```

to your standard `XftConfig`. This will enable a user specific configuration file, but it will not complain if there is no such file.

#### 3. How do I make aliases for my fonts?

### 4.1.3. Xft Configuration

## XFree86 Font De-uglification HOWTO

I noted that my KDE console asks for "mono" fonts when it is looking for a fixed font. "console" is used when I select "linux" in the font menu of the KDE konsole. Therefore, I used two aliases for fonts which are also named "fixed":

```
match any family == "fixed" edit family += "mono";
match any family == "console" edit family += "mono";
```

### 4. Anti-aliasing my fonts makes me dizzy!

Although there is a big fuzz around AA in X, good fonts actually look better if they are not anti-aliased. The anti-aliasing blurs the fonts by adding gray pixels to the edges, and this may strain your eyes if you looking at them for a long time. (Your eyes will try to get the fonts sharper, which of course is not working because they are blurred;) However, for very small fonts, anti-aliasing may increase the readability of the fonts, because with sharp edges, there are to little pixels available for your mind to figure out what it means. And for bigger fonts, the edges become very jagged when not anti-aliased, so here you also might want to have aliased fonts. Of course you can also turn off the anti-aliasing for specific fonts. In other operating systems, most truetype fonts are not anti-aliased between 8 and 12 pixels, while only large Type1 fonts are anti-aliased.

Use the following in your `XftConfig` to anti-alias only fonts of specific sizes:

```
match
  any size > 8
  any size < 15
edit
  antialias = false;
```

### 5. My fixed fonts do not appear or look \_very\_ wrong in the KDE konsole or similar programs!

I noted that somehow a lot of fixed font do not tell Xft that they are fixed, and thus, mono spaced. Therefore only a part of the font is displayed. We can manually set the spacing for these fonts (this assumes you have fixed aliased with mono as in question 3 above:

```
match
  any family == "mono"
edit
  spacing = mono;
```

### 6. My Symbol, Webdings, etc. fonts do not show up!

For some reason some (symbol) fonts are not correctly recognized, and Xft will show your default font, or a font which has the closest match (which is generally not what you mean at all). For Adobe Symbol and MS-webdings I did the following to get them working:

```
match
  any family == "webdings"
edit
  antialias = false;
```

## XFree86 Font De-uglification HOWTO

```
encoding += "glyphs-fontspecific";
```

```
match
    any family == "symbol"
edit
    antialias = false;
    encoding += "glyphs-fontspecific";
```

A useful way of figuring out these things is to activate debugging with:

```
export XFT_DEBUG=1024
```

This will generate a lot of output, especially if you have many fonts, because it lists the properties and scores of every font available. You can also use other values. For a nice summary of what happens (requested font, XftConfig substitutions, x server additions and the finally matched font), you can use `XFT_DEBUG=2`.

### 7. Why do my KDE programs start now sooooo slooow?

The Xft mechanism in XFree prior to 4.1 had to parse the `xftConfig` file each time a program was started. And the info of all these fonts had to be re-read. As of X 4.1.0, a cache is used and starting applications using Xft is much faster. Especially if you have many fonts this can be very useful. So, upgrading XFree86, and related packages, is a good idea.

### 8. I have a LCD screen, can I use subpixel hinting instead of normal anti-aliasing?

Yes you can. Subpixel hinting uses colors instead of gray pixels to do the AA. I do not have a LCD screen so I do not have any idea of how it looks but you can play with the `rgba` setting. Try:

```
match edit rgba=bgr;
```

or use `rgb` if you have a different type of monitor. For vertical AA you can try `vbgr` and `vbgr`.

### 9. My fonts still look bad!

If you do not have some good truetype fonts, it is worth to go and look for them on the Internet. Other reasons why your fonts still look bad can be because of your build of freetype2. Snapshots versions before 2.0.2 were compiled with an option that had some patent issues. Therefore, the standard 2.0.2 and 2.0.3 compiles without this option. To fix this, download the freetype2 source rpm and change in `include/freetype/config/ftoption.h` line 314:

```
#undef TT_CONFIG_OPTION_BYTECODE_INTERPRETER
```

to:

## XFree86 Font De-uglification HOWTO

```
#define TT_CONFIG_OPTION_BYTECODE_INTERPRETER
```

and rebuild with this modified source. See the freetype2 README file for details. Adobe Courier looks terrible on my system, so I made an alias so that Lucida console is displayed instead. If anyone can get it to display nicely I would appreciate it.

This is my XftConfig:

```
#
# XftConfig
#
# By: Danny Tholen
#
# Use with Type1 and TrueType fonts
#

dir "/usr/X11R6/lib/X11/fonts/Type1"
dir "/usr/X11R6/lib/X11/fonts/drakfont"
dir "/usr/share/fonts/default/Type1"

#
# alias 'fixed' and 'console' for 'mono'
# (some programs ask for 'mono' if they mean 'fixed';)
#
match any family == "fixed"    edit family += "mono";
match any family == "console"  edit family += "mono";

#
#Check users config file
#
includeif  "~/xftconfig"

#
# Use TrueType fonts for defaults
# Danny: disabled
#match any family == "serif"    edit family += "Times New Roman";
#match any family == "sans"    edit family += "Verdana";

#
# Use lucida console as default fixed type font
# and set the spacing of "mono" to 100, this
# fixes broken fonts which are fixed, but do not
# set mono-spacing.
match
    any family == "mono"
edit
    family += "lucida console";
```

### 4.1.3. Xft Configuration

## XFree86 Font De-uglification HOWTO

```
spacing = 100;

#
# Alias between XLFD families and font file family name, prefer local fonts
#
match any family == "Charter"      edit family += "Bitstream Charter";
match any family == "Bitstream Charter" edit family += "Charter";

match any family == "Lucidux Serif"  edit family += "LuciduxSerif";
match any family == "LuciduxSerif"  edit family += "Lucidux Serif";

match any family == "Lucidux Sans"   edit family += "LuciduxSans";
match any family == "LuciduxSans"   edit family += "Lucidux Sans";

match any family == "Lucidux Mono"   edit family += "LuciduxMono";
match any family == "LuciduxMono"   edit family += "Lucidux Mono";

#
# TrueType font aliases
#
match any family == "Comic Sans"     edit family += "Comic Sans MS";
match any family == "Comic Sans MS"  edit family += "Comic Sans";
match any family == "Trebuchet"      edit family += "Trebuchet MS";
match any family == "Trebuchet MS"   edit family += "Trebuchet";
match any family == "Monotype"       edit family += "Monotype.com";
match any family == "Andale Mono"    edit family += "Monotype.com";
match any family == "Monotype.com"   edit family += "Andale Mono";

# Danny:
# set the AA for different fonts
#
# most TT fonts do not need to be aliased between
# 8 and 15 points, although this might be a matter of taste.
match
    any size > 8
    any size < 15
edit
    antialias = false;

# Danny: Courier looks terrible, and I
# cannot get most characters to fit nicely
# in their space. So I use courier 10 pitch
match
    any family == "courier"
edit
    family += "courier 10 pitch";
```

# these are symbols, and for some reason this needs to be added!:

```
match
  any family == "webdings"
edit
  antialias = false;
  encoding += "glyphs-fontspecific";
```

```
match
  any family == "symbol"
edit
  antialias = false;
  encoding += "glyphs-fontspecific";
```

```
match
  any family == "Standard Symbols L"
edit
  antialias = false;
  encoding += "glyphs-fontspecific";
```

```
match
  any family == "dingbats"
edit
  antialias = false;
  encoding += "glyphs-fontspecific";
```

```
match
  any family == "Cursor"
edit
  antialias = false;
  encoding += "glyphs-fontspecific";
```

# maybe arial looks better like this?:

```
match
  any family == "Arial"
  any size > 7
  any size < 15
edit
  antialias = false;
```

# end

---

## 4.1.4. Afterword

You've gone through all the steps, and verified that the "RENDER" extension is available, but you don't

perceive a difference? Well, maybe the applications themselves just aren't there yet, and are not able to utilize these new features. Mozilla and Netscape, for instance, are not able to yet (as of this writing).

So how to know what does and does not make use of anti-aliasing? A quick test is to use something like xmag, or gimp, and enlarge the text considerably. Look for diagonal lines, and if they are clearly stair-stepped with no softened edges. If so, then while anti-aliasing is technically available, it is not being used. With anti-aliasing you should see gradients instead of well defined sharp edges. You can compare this with xterm and "AA":

```
$xterm -fa charter -fs 14
```

---

## 4.2. Redhat 7.x Differences

Redhat 7.0 introduced some changes to X configuration over previous Redhat versions. It is also different from the stock XFree86 configuration as addressed above. Notable differences:

- Both XFree86 3.3.6 and 4.x are included. If upgrading you may wind up with 3.3.6. The X configuration file is XF86Config for 3.3.6 and XF86Config-4 for 4.x. Of course, you'll need to know which is which for editing and configuration purposes.
  - xfs is still handling all font duties. A default Redhat 7.x installation does not use the 'modules' section of XF86Config. Instead it relies on xfs. This is different from a stock installation of XFree86 4.x where the X server does all the font work -- including TrueType.
  - The socket for xfs is "unix:/7100" with RH 7.x, as opposed to "unix:/-1" in previous versions.
-

# 5. Adjusting Fonts in Specific Applications

## 5.1. KDE

KDE is one of the best things that have happened to Linux and X in a long time. It provides a consistent user interface that goes a long way towards making Linux accessible to the average non-geek. More information about KDE can be found at <http://www.kde.org/>. So why am I singing its praises here? This is because KDE 1.1 has a new feature that will make the fonts and colors in your programs, including non-KDE applications consistent with KDE's current style.

---

### 5.1.1. Applying KDE Fonts and Colors to non-KDE Applications

This is very easy. Simply start up the KDE Control Center, go to Desktop, and go to Style inside Desktop. In there, there will be a toggle switch labeled "Apply fonts and colors to non-KDE apps". Turn it on, click OK, and you're done! The next time you start up many X applications, they will use the same colors and fonts that your KDE applications do. Some people may like this feature better than others, but if you don't like it you can always turn it off.

---

## 5.2. Netscape

Let's face it, Netscape is an important application in Linux. We all use it, and we all need it, so let's look at it specifically for a minute. An out of the box Netscape installation is prone to the font problems we've discussed — large fonts that get pixelized, splotchy looking fonts, fonts so small they are unreadable. In short, ugly. Maybe this is why you are here?

Hopefully, at this point you have followed the above suggestions. These steps can help greatly. TrueType font availability is almost a necessity, and you need a TrueType font server for this. Many web pages specify font families — like Arial — that are not typically available to Linux users. This is bad design, but having some of the basic TrueType fonts available will help greatly in overcoming the short-sightedness of some designers. Microsoft — can't live with 'em, can't live without 'em.

Assuming you have TrueType working, from the Netscape menu select `Edit -> Preferences -> Fonts`. Open the `Variable Width Font` droplist on the right side of the window. Your TrueTypes should be there along with other fonts. Choose whichever one suits your fancy as the default. Check the `Allow Scaling` checkbox too. If the available point sizes are 0 and 12, you can go down and, and enter your desired point size in the box to the right and click on the `OK` button. The down-side to this is that Netscape will not remember these settings, and you will have to do this each time you start Netscape. *Unless* — you have `fonts.alias` set up already. Then this will solve these problems. See [Section 3.4](#) for more on `fonts.alias`.

You might consider experimenting with some `~/ .Xdefaults` (or perhaps it's `~/ .Xresources` on your system) settings too:

```
Netscape*DocumentFonts.sizeIncrement: 10
Netscape*documentFonts.xResolution*iso-8859-1: 120
```

## XFree86 Font De-uglification HOWTO

Netscape\*documentFonts.yResolution\*iso-8859-1: 120

The 'sizeIncrement' controls how much of a jump Netscape makes when different 'basefont' sizes are specified ala:

```
<basefont size=7>
```

for instance. The default is '20', which is a pretty good jump. Changing this can help Netscape from scaling to too large and too small of a font. The x and y resolutions are roughly equivalent to 'dpi' settings. Any random number within reason can be used here. Experiment.

Then run:

```
$ xrdb -load ~/.Xdefaults
```

(or `.Xresources` as the case may be) and restart Netscape. There are many settings that can be tweaked or altered this way. Look at the `Netscape.ad` (app defaults) file that should be included with Netscape packages.

If this approach does not get the job done as far as the 'tiny fonts' problem in Netscape, then see the `fonts.alias` section above. You can really fine tune many things with this approach.

Mozilla configuration should be roughly the same. You might find, however, that Mozilla does a better job of handling fonts in X, and pages will look better overall.

---

## 6. Odds and Ends

### 6.1. Notes

- Unfortunately there is no unified font handling system for Linux. You will have to configure each individual program so you can use TrueType, Type 1 or fonts that pique your fancy. And each program may well have its own way of doing this so you will have to RTFM. Desktop Environments like Gnome and KDE may provide much of this functionality.
  - Most GUI apps should be able to use TrueType, and Type 1 fonts too. Wordperfect for Linux, however, cannot use TrueType. (See the links section below for more on Wordperfect.) Text editors, terminal programs and the like need fixed width fonts, and do not play well with TrueType or other scalable fonts.
  - Though not discussed here, Type 1 fonts provide many of the same benefits as TrueType and are historically better supported in the Unix world. You likely have many of these installed already. Unfortunately however, Type 1 are not a web standard like TrueType. But they are suitable for many other purposes. They are where it's at for printing. See [ghostscript](#) for more on this.
  - While it is possible to specify a default point size for the xfs font server, very few applications will actually use this value.
  - Abiword comes with a suite of fonts, called 'Abisuite'. Apparently, some of these fonts have the same names as some of the well known MS TrueType fonts: Arial, etc. And apparently, these are of much less quality. And because of the way X searches for fonts, it may find these first and use these, even if the 'real' ones are installed and may be the preferred choice. The solution is to uninstall 'Abisuite'.
  - The new Xft rendering extensions of XFree86 4.x will mostly supplant similar features as provided by xfs, and older XFree86 extensions. For instance, font aliasing should be done in `XftConfig` if the new extensions are being used. This would only be true where the application is built against a toolkit (like QT or GTK) that supports the new extensions. At this time, there are not many apps that do support this yet.
- 

### 6.2. Links

- The [Video Timings HOWTO](#), the ins and outs of getting the most from your monitor.
- [Font HOWTO](#) Many good tips for installing fonts and for applications such as StarOffice, Applixware, Wordperfect, Ghostscript, TeX/LaTeX.
- A [TrueType HOWTO](#), good tips for printing, and a few application specific tips.
- [xfsft Homepage](#), TrueType font support for X. This is the origin of the "freetype" font module for XFree86 4.x, and Redhat's xfs. Good site, and good links to other information related to fonts and TrueType.
- [Some Linux for Beginners](#). Great font site, and other Linux topics. Covers many of the topics discussed here in more detail. Some font and other tips for Mozilla: [http://home.c2i.net/dark/My\\_Mozilla\\_FAQ.html](http://home.c2i.net/dark/My_Mozilla_FAQ.html).
- [X-TrueType Homepage](#), and yet another TrueType Font server, especially good for Japanese, Chinese and Korean character sets.
- Tips on font size problems from [Netscape](#).
- [Wordperfect for Linux -- Fonts and Printers](#) by Rod Smith, the author of *Using Corel Wordperfect 8 for Linux* from Que. Excellent information on Wordperfect and where TrueType fits in.
- [XFree86 Project](#), the guys and gals who do an incredible amount of work to give us a killer GUI environment. Some info on fonts in [XFree86 4.x](#).

## XFree86 Font De-uglification HOWTO

- [Microsoft Web Fonts](#) direct from the Lion's den --- and they are free! These can be unpacked in Linux (see above).
- [Web Fonts RPM package](#), contains a few of the MS web browser fonts.  
<http://packages.debian.org/unstable/graphics/msttcorefonts.html> is a similar package for Debian.
- Sebastiano Vigna's <http://freshmeat.net/webFonts4Linux> automates the downloading, extracting and installation of the Microsoft fonts all in one neat package.
- [Freeware Connection -- Free Fonts Sites](#) lots of links to lots of sites.
- [Bitstream's Geometric Slabserif](#) TrueType Font.
- Two converters for converting a Mac Font "suitcase" to a \*nix compatible font:  
<http://www.macinsearch.com/infomac2/font/util/tt-converter-15.html> and  
<http://www.netmagic.net/~evan/shareware/#TTFontConvert>
- The Unicode HOWTO: <http://linuxdoc.org/HOWTO/Unicode-HOWTO.html>
- Two sources of 'free' TrueType fonts with large Unicode support are Bitstream Cyberbit, which covers Roman, Cyrillic, Greek, Hebrew, Arabic, combining diacritical marks, Chinese, Korean, Japanese, and more, and is available from  
<ftp://ftp.netscape.com/pub/communicator/extras/fonts/windows/Cyberbit.ZIP>. And Lucida Sans Unicode, which is included in IBM's JDK 1.3.0beta for Linux, and covers Roman, Cyrillic, Greek, Hebrew, combining diacritical marks. This can be downloaded from  
<ftp://ftp.maths.tcd.ie/Linux/opt/IBMJava2-13/jre/lib/fonts/> as LucidaSansRegular.ttf and LucidaSansOblique.ttf. Thanks to Tzafrir Cohen for these references. He also has a nice page on Hebrew fonts and related topics at <http://www.iglu.org.il/faq/?file=133>.