

Firewall Piercing mini-HOWTO

Table of Contents

<u>Firewall Piercing mini-HOWTO</u>	1
François-René Rideau, fare@tunes.org	1
1. Stuff	1
2. Introduction	1
3. Understanding the problem	1
4. Secure solution: piercing using ssh	1
5. Unsecure solution: piercing using telnet	1
6. Routing	1
7. Reverse piercing	2
8. Final notes	2
1. Stuff	2
1.1 DISCLAIMER	2
1.2 Legal Blurp	2
1.3 Looking for a maintainer	2
1.4 Credits	2
2. Introduction	3
2.1 Foreword	3
2.2 Security issues	3
2.3 Other requirements	4
2.4 Downloading software	4
3. Understanding the problem	5
3.1 Giving names to things	5
3.2 The main problem	5
3.3 The secondary problem	5
4. Secure solution: piercing using ssh	6
4.1 Principle	6
4.2 A sample session	6
5. Unsecure solution: piercing using telnet	7
5.1 Principle	7
5.2 fwprc	7
5.3 .fwprerc	8
6. Routing	8
6.1 The catch	8
6.2 Example of routing	9
7. Reverse piercing	10
7.1 Rationale	10
7.2 Getting the trigger message	10
8. Final notes	11
8.1 Other settings	11
8.2 HOWTO maintenance	12
8.3 Related Documents	12
8.4 Final Word	12
8.5 Extra copy of IMPORTANT DISCLAIMER --- BELIEVE IT!!!	12

Firewall Piercing mini-HOWTO

François-René Rideau, fare@tunes.org

v0.92, 15 July 2001

Directions for using ppp over ssh or telnet so as to do network stuff transparently through an Internet firewall. Also applies to VPN construction.

1. [Stuff](#)

- [1.1 DISCLAIMER](#)
- [1.2 Legal Blurp](#)
- [1.3 Looking for a maintainer](#)
- [1.4 Credits](#)

2. [Introduction](#)

- [2.1 Foreword](#)
- [2.2 Security issues](#)
- [2.3 Other requirements](#)
- [2.4 Downloading software](#)

3. [Understanding the problem](#)

- [3.1 Giving names to things](#)
- [3.2 The main problem](#)
- [3.3 The secondary problem](#)

4. [Secure solution: piercing using ssh](#)

- [4.1 Principle](#)
- [4.2 A sample session](#)

5. [Unsecure solution: piercing using telnet](#)

- [5.1 Principle](#)
- [5.2 fwprc](#)
- [5.3 .fwprcrc](#)

6. [Routing](#)

- [6.1 The catch](#)
- [6.2 Example of routing](#)

7. [Reverse piercing](#)

- [7.1 Rationale](#)
- [7.2 Getting the trigger message](#)

8. [Final notes](#)

- [8.1 Other settings](#)
 - [8.2 HOWTO maintenance](#)
 - [8.3 Related Documents](#)
 - [8.4 Final Word](#)
 - [8.5 Extra copy of IMPORTANT DISCLAIMER ---- BELIEVE IT!!!](#)
-

1. [Stuff](#)

1.1 DISCLAIMER

READ THIS IMPORTANT SECTION !!!

I hereby disclaim all responsibility for *your* use of this hack. If it backfires on you in any way whatsoever, that's the breaks. Not my fault. If you don't understand the risks inherent in doing this, don't do it. If you use this hack and it allows vicious vandals to break into your company's computers and costs you your job and your company millions of dollars, well that's just tough nuggies. Don't come crying to me.

1.2 Legal Blurp

Copyright © 1998–2001 by François–René Rideau.

This document is free software published under the [bugroff license](#).

1.3 Looking for a maintainer

I haven't been actively developing this mini-HOWTO recently; in particular, the french version is lagging behind. I'm looking for a maintainer to take over this document, and maybe develop software to make it easier to pierce firewalls. I also have a lot of ideas for active maintainers to expand this HOWTO, if anyone is interested.

1.4 Credits

Even though the only thing left is the disclaimers, this document owes a lot to the [Term–Firewall mini-HOWTO](#) by [Barak Pearlmutter](#). Barak's mini-HOWTO relies on an ancient and no–more–supported program named Term (a great program in its time, and maybe still useful in some unhappy circumstances), as well as on peculiarities of a not–so–standard telnet implementation, that is, many obsolete and non–portable facts. Nevertheless, there was a necessity for a mini-HOWTO about piercing firewalls, and despite the limitations of its hacks, this mini-HOWTO was a model and an encouragement.

I'd also like to congratulate [Lars Brinkhoff](#) and [Magnus Lundström](#) for their fine http, mail and icmp tunnels.

2. [Introduction](#)

2.1 Foreword

This document has a moral. And the moral is: **a firewall cannot protect a network against its own internal users, and should not even try to.**

When an internal user asks you system administrator to open an outbound port to an external machine, or an inbound port to an internal machine, then you should do it for him. Of course you should help the user to make sure that his transactions are secure, and that his software is robust. But a flat out denial of service is plain incompetence. For unless he is so firewalled as to be completely cut from the outside world, with no ssh, no telnet, no web browsing, no email, no dns, no ping, no phone line, no radio, no nothing, then the user can and will use firewall piercing techniques to access the machines he wants nonetheless, and the net result for security will be an unaudited connection with the outside world. So either you trust your users, after proper training and selection, or you shouldn't grant them access to the network at all. You can and you shall protect them from the outside world, but you can't protect them from themselves.

Because there exists such things as system administrators who are either unresponsive, absent, overworked, plain incompetent, or more generally managed by incompetent people, it so happens that a user may find himself behind a firewall that he may cross, but only in awkward ways. This mini-HOWTO explains a generic and portable way to pierce tunnels into firewalls, by turning any thin, tiny trickle of bits into a full-fledged information superhighway, so the user can seamlessly use standard tools to access computers on the other side of the firewall. The very same technique can be used by competent system administrators to build virtual private networks (VPN).

2.2 Security issues

Of course, if your sysadm has setup a firewall s/he might have a good reason, and you may have signed an agreement to not circumvent it. On the other hand, the fact that you can use telnet, the web, e-mail, or whatever other bidirectional information flux with the outside of the firewall (which is a prerequisite for the presented hacks to work) means that you are allowed to access external systems, and the fact that you can log into a particular external system somehow means you're allowed to do it, too.

So this is all a matter of *conveniently* using legal holes in a firewall, and allow generic programs to work from there with generic protocols, as opposed to requiring special or modified (and recompiled) programs going through lots of special-purpose proxies that be misconfigured by an uncaring or incompetent sysadm, or to installing lots of special-purpose converters to access each of your usual services (like e-mail) through ways supported by the firewall (like the web).

Moreover, the use of a user-level IP emulator such as SLiRP should still prevent external attackers from piercing the firewall back in the other way, unless explicitly permitted by you (or they are clever and wicked, and root or otherwise able to spy you on the remote host).

All in all, the presented hack should be *relatively* safe. However, it all depends on the particular circumstances in which you set things up, and I can give no guarantee about this hack. Lots of things are intrinsically unsafe about any Internet connection, be it with this hack or not, so don't you assume anything is

safe unless you have good reasons, and/or use some kind of encryption all the way.

Let's repeat the basics of networking security: *you cannot trust anything about a connection more than you trust the hosts that can handle the unencrypted data*, including hosts on both ends of the connection, and all hosts that can intercept the communication, unless the communication is properly encrypted with secret keys. If you misplace your trust, your passwords may be stolen and used against you, your credit card number may be stolen and used against you, and you may be fired from your work for endangering the whole company. Tough nuggies.

To sum it up, don't use this hack unless you know what you're doing. Re-read the disclaimer above.

2.3 Other requirements

It is assumed that you know what you're doing, that you know about configuring a network connection, that in case of doubt, you will have read all relevant documentation (HOWTOs, manual pages, web pages, mailing-list archives, RFCs, courses, tutorials).

It is assumed that you have shell accounts on both sides of the firewall, that you can somehow transmit packets of information both ways across the firewall (with telnet, ssh, e-mail, and the web being the ways currently known to work), and that you can let a daemon run as a background task on the remote site (or benefit from an existing daemon, sshd, telnetd, or sendmail/procmail).

It is assumed that you know or are willing to learn how to configure an IP emulator (pppd, slirp) or an Internet access daemon and its associated library (SOCKS, Term) on each side, according to your needs in terms of connectivity and to your access rights, with your recompiling some software if needed.

Last but not least, so that you can use the hacks described in this document, it is assumed that you are root on the side of the firewall that needs full transparent IP access to the other side. Indeed, you'll want to run the PPP daemon on this side which allows for use of the normal kernel packet routing facilities. In case you're not root on this side, your case is not desperate though: indeed, Barak Pearlmutter's [Term-Firewall mini-HOWTO](#) describes how to use Term, a purely userland program, to the end of piercing firewalls. Although there's no HOWTO, I suspect SOCKS could also be used as a way to pierce firewalls without having root privilege.

2.4 Downloading software

Most software named in this HOWTO should be available from your standard Linux distribution, possibly among contrib's. At least, the four first below are available in as `.rpm` and `.deb` packages. In case you want to fetch the latest sources (after all, one of the ends of the connection may not be running under Linux), use the addresses below:

- SLiRP can be found at <http://blitzen.canberra.edu.au/slirp> and/or ftp://www.ibc.wustl.edu/pub/slirp_bin/.
- zsh can be found at <http://www.zsh.org/>.
- ppp can be found at <ftp://cs.anu.edu.au/pub/software/ppp/>.
- ssh can be found at <http://www.openssh.com/>.
- fwprc, cotty and getroute.plan be found at <http://fare.tunes.org/files/fwprc/>.
- httptunnel can be found at <http://www.nocrew.org/software/httptunnel/>.
- mailtunnel can be found at <http://www.detached.net/mailtunnel/>.

3. Understanding the problem

Understanding a problem is the first half of the path to solving it.

3.1 Giving names to things

If you want this hack to work for you, you'll have to get an idea of how it works, so that in case anything breaks, you know where to look for.

The first step toward understanding the problem is to give a name to relevant concepts.

As usual, we'll herein call "local" the client machine that decides to initiate the connection, as well as programs and files on that machine; conversely, we'll call "remote" what's on the other side of the connection, where a server runs that waits for connections.

3.2 The main problem

The main problem with firewall piercing is to create a tunnel: a continuous connection from the local machine to a remote machine on the other side of the firewall, that allows for bidirectional exchange of information. Optionally, this connection should be a secure one. The secondary problem is to transform this connection into a full IP access for normal programs to use transparently.

For the main problem, we'll assume that either (1) you can establish normal TCP/IP connections from the local side of the firewall to some port on a remote machine where a `sshd` runs or can be set to run, or (2) you can somehow establish a telnet connection through a telnet proxy. In case you cannot, we give you pointers to other software that allows you to pierce a tunnel across a firewall. Although we only give a secure solution in the first case, you can hack your own secure solution in the other cases, if you understand the principle (if you don't, someone, e.g. I, can do it for you in exchange for money).

3.3 The secondary problem

For the secondary problem, IP emulators (`pppd` or `SLiRP`) are run on each side of the tunnel.

On the side that wants full IP access to the other side, you'll want to run `pppd`. On the other side, you want to run `pppd` if you also want full IP access to the first side, or `SLiRP` if you want to prevent any access. Go to your usual `pppd` or `SLiRP` documentation for more information, if you have specific needs not covered by the examples given below.

Although this is conceptually trivial, it nonetheless requires a few silly tricks, so as to work, since (a) in case you're using some kind of programmed interactive shell session to start the remote IP emulator on either side, you need to correctly synchronize the start of the IP emulator on the other side, so as not to send garbage into the shell session, and (b) IP emulators are designed to be run on a "tty" interface so you have to convert your tunnel's interface into a tty one.

Issue (a) is just your usual synchronization problem, and doesn't even exist if you use `ssh`, that transparently handles remote command launching.

Issue (b) requires the use of a simple external utility. We wrote one, `cotty` just for that purpose.

<FLAME ON>

Among the silly problems caused by `pppd` maintainers' shortmindedness, you can only run it through either a device in `/dev` or the current `tty`. You cannot run it through a pair of pipe (which would be the obvious design). This is fine for the remote `pppd` if any, as it can use the `telnet` or `ssh` session's `tty`; but for the local `pppd`, this conflicts with the possible use of `telnet` as a way to establish a connection.

Indeed, `telnet`, too wants to be on a `tty`; it behaves *almost* correctly with a pair of pipe, except that it will still insist on doing `ioctl`'s to the current `tty`, with which it will interfere; using `telnet` without a `tty` also causes race conditions, so that the whole connection will fail on "slow" computers (`fwprc 0.1` worked perfectly on a P/MMX 233, one time out of 6 on a 6x86-P200+, and never on a 486dx2/66). All in all, when using `telnet`, you need `cotty` to run as a daemon to copy output from one `tty` on which runs `pppd` into another `tty` on which runs `telnet`, and conversely.

If I find the sucker (probably a MULTICS guy, though there must have been UNIX people stupid enough to copy the idea) who invented the principle of "tty" devices by which you read and write from a "same" pseudo-file, instead of having clean pairs of pipes, I strangle him!

</FLAME>

4. [Secure solution: piercing using ssh](#)

4.1 Principle

Let's assume that your site administrator allows transparent TCP connections to some port on some remote machine, (be it the standard SSH port 22, or an alternate destination port, like the HTTP port 80 or whatever), or that you somehow managed to get some port in one side of the firewall to get redirected to a port on the other side (using `httptunnel`, `mailtunnel`, some tunnel over `telnet`, or whatelse).

Then, you can run an `sshd` on the remote port, and connect to it with an `ssh` on the local port. On both sides of the `ssh` connection, you run IP emulators (`pppd`), and there you have your VPN, Virtual Public Network, that circumvents the stupid firewall limitations, with the added bonus of being encrypted for privacy (beware: the firewall administrator still knows the other end of the tunnel, and whatever authentication information you might have sent before to run `ssh`).

The exact same technology can be used to build a VPN, Virtual Private Network, whereby you securely join physical sites into a one logical network without sacrificing security with respect to the transport network between the sites.

4.2 A sample session

Below is a sample session to integrate in a shell script (it assumes `sh/bash` syntax; YMMV).

Be sure to edit this into a script with the right values for your needs. Use option `-p` for `ssh` to try another port than port 22 (but then, be sure to run `sshd` on same port). You can use `slirp` on the remote end, if you are not `root` there, or simply want to screen your local network from outbound connections.

Automatic reconnection is left as an exercise to the reader (the `nodetach` option from `pppd` might help).

```
#!/bin/sh
REMOTE_ACCOUNT=root@remote.fqdn.tld
REMOTE_PPPD="pppd ipcp-accept-local ipcp-accept-remote"
#REMOTE_PPPD="slirp ppp"
LOCAL_PPPD="pppd silent 10.0.2.15:10.0.2.2"
$LOCAL_PPPD pty "ssh -t $REMOTE_ACCOUNT $REMOTE_PPPD"
```

If you use `slirp` instead of `pppd`, just uncomment the relevant line. Note that default options from your `/etc/ppp/options` or `~/.slirprc` may break this script, so remove any unwanted option from there. If your old or non-linux `pppd` hasn't got the `pty` option, use `cotty -d -- $LOCAL_PPPD -- ssh -t $REMOTE_ACCOUNT $REMOTE_PPPD`. For more customization, please read the documentation for the relevant program.

Note that 10.0.2.2 is the default setting for `slirp`, which might or not fit your specific setup. In any case, you should most likely be using some address in one of the ranges reserved by RFC 1918 for private networks: 10.0.0.0/8, 172.16.0.0/12 or 192.168.0.0/16. The firewall-protected LAN might already be using some of them, and avoiding clashes is your responsibility.

5. [Unsecure solution: piercing using telnet](#)

5.1 Principle

If all you can do is telnet (because of a telnet proxy), then this solution might be fit for you.

The firewall-piercing program, `fwprc`, will use a "tty proxy", `cotty`, that opens two pseudo-tty devices, launches some command on each of those devices' slaves, and stubbornly copies every character that one outputs to the tty that serves as input of the other command. One command will be telnet connection to remote site, and the other will be the local `pppd`. `pppd` can then open and control the telnet session with a chat script as usual.

Actually, if your telnet proxy allows connection to an arbitrary port, and if you can reliably run a daemon on the remote host (with a cron job to relaunch it in case of breakage), then you'd better write some program that will just connect a local port to the remote one through the proxy, so you can use the above secure solution, possibly using some variant of `ssh -t -o "ProxyCommand . . ."` (if you submit it to me, I'll gladly integrate such a solution to the `fwprc` distribution).

Note: if you must use the unsecure telnet-based solution, be sure that nothing lies in your target account that you want to keep secret or untampered, since the password will be sent in clear text across the Internet.

5.2 `fwprc`

I wrote a very well self-documented script to pierce firewalls, `fwprc`, available from [my site](#), together with `cotty` (which is required by `fwprc` .2 0 and later). At the time of my writing these lines, latest versions are `fwprc` 0.3e and `cotty` 0.4b.

The name "fwprc" is voluntarily made unreadable and unpronounceable, so that it will confuse the incompetent paranoid sysadm who might be the cause of the firewall that annoys you (of course, there can be

legitimate firewalls, too, and even indispensable ones; security is all a matter of *correct* configuration). If you must read it aloud, choose the worst way you can imagine.

CONTEST! CONTEST! Send me an audio file with a digital audio recording of how you pronounce "fwprc". The worst entry will win a free upgrade and his name on the fwprc 1.0 page!

I tested the program in several settings, by configuring it through resource files. But of course, by Murphy's law, it will break for you. Feel free to contribute enhancements that will make life easier to other people who'll configure it after you.

5.3 .fwprcrc

fwprc can be customized through a file .fwprcrc meant to be the same on both sides of the firewall. Having several alternate configurations to choose from is sure possible (for instance, *I* do it), and is left as an exercise to the reader.

To begin with, copy the appropriate section of fwprc (the previous to last) into a file named .fwprcrc in your home directory. Then replace variable values with stuff that fits your configuration. Finally, copy to the other host, and test.

Default behavior is to use pppd locally, and slirp remotely. To modify that, you can redefine the appropriate function in your .fwprcrc with such a line as:

```
remote_IP_emu () { remote_pppd }
```

Note that SLiRP is safer than pppd, and easier to have access to, since it does not require being root on the remote machine, and needn't additional firewall configuration to prevent connections from the outside world into the firewalled network. The basic functionality in SLiRP works quite well, but I haven't managed to get some advertised pluses to work (like run-time controllability). Of course, since it is free software, feel free to hack the source so as to actually implement or fix whichever feature you need.

6. [Routing](#)

Piercing the firewall is not everything. You must also route the packets from this side of the firewall to the other. This section tackles the basic settings specific about routing accross a tunnel. For more detailed explanations of routing, see the relevant HOWTOs and man pages about networking, routing and masquerading.

6.1 The catch

The main point is that although your network administration would tell you to setup your local router as the default route, you might want to have it but a specific route to the networks within your side or the firewall, whereas the other end of your PPP link should be the router for the networks on the other side. Your default route should point to a router on whichever side gives you access to the Internet. Most importantly, all machines involved in routing packets to the other end of the tunnel should be routed through your usual network (i.e. ethernet), for your kernel will have problems if it tries to route through the tunnel the packets to the remote host that precisely serves as end-point for the tunnel.

Firewall Piercing mini-HOWTO

So you'll have to setup proper routes in your network startup configuration like `/etc/init.d/network` or `/etc/network/`, as well as your PPP startup configuration in `/etc/ppp/ip-up` or `/etc/ppp/ip-up.d/` or wherever your distribution puts them. To identify your distribution-specific file locations, RTFM the docs of your distribution, use `grep` recursively on your `/etc`, and if all else fails, trace the boot behaviour of your computer from `/sbin/init`.

Also, when piercing a tunnel from a roaming laptop on the Internet into a protected network, I used to use from within my `ip-up` the script `getroute.pl` (available from the `fwprc` distribution) that gives me the current route for the host on the other end of the tunnel.

Once you can route packets to the other side of the tunnel, you might want to setup your machine as a router for all your pals on your site of the firewall, achieving a full-fledged shared VPN. This is not specific to Firewall-Piercing, so just you read the relevant HOWTOs about networking, routing and masquerading. Also, for security reasons, be sure to also setup a proper firewall on your machine, especially if you're going to be a router for other people.

Finally, be reminded that if you're using `pppd` on the other end of the tunnel (as opposed to user-mode `slirp`), you will have to configure proper routes and firewall rules on the other side of the tunnel, too.

6.2 Example of routing

Let's consider an example. In your case, of course, you'll have to adapt the IP numbers, and insert the commands in the right place, which depends on your distribution.

For instance, imagine your machine is on the ethernet `eth0` with IP address is `12.34.56.78` on network `12.24.56.0/24`, router `12.34.56.1`. Your network administrator will have told you to use `12.34.56.1` as default router. But you shouldn't, as you should only use it to route on your side of the firewall. Imagine you have networks `12.34.0.0/16` and `12.13.0.0/16` and host `11.22.33.44` accessible through your router on your side of the firewall. Then you'll add these routes to your startup script:

```
route add -net 12.34.0.0 netmask 255.255.0.0 gw 12.34.56.1
route add -net 12.13.0.0 netmask 255.255.0.0 gw 12.34.56.1
route add -host 11.22.33.44 gw 12.34.56.1
```

You must also keep the route to the local network, necessary for linux kernel 2.0 and earlier, but implicitly added by `ifconfig` on 2.2 and later:

```
route add -net 12.34.56.0 netmask 255.255.255.0 dev eth0
```

On the other hand, you must remove any default route from your scripts:

```
route add default gw 12.34.56.1
```

If the default route has already been set, you can remove it as is:

```
route del default gw 12.34.56.1
```

Then you can have `pppd` setup a default route automatically when it starts by using its `defaultroute` option. Or you can add it after the fact with:

```
route add default gw 10.0.2.2
```

If you don't want `pppd` as a default route, because the Internet is on your side of the firewall, and instead want network `98.76.0.0/20` to be routed through the tunnel, except from host `98.76.54.20` that serves as the other end of the tunnel, then have this executed from your `/etc/ppp/ip-up`:

```
route add -host 98.76.54.32 gw 12.34.56.1
route add -net 98.76.0.0 netmask 255.255.240.0 gw 10.0.2.2
```

If you're a laptop and your current LAN moves, and yet you want to keep your current route to `98.76.54.32`, whatever it be, then use `getroute.pl` as follows to automatically find the right gateway in the `route add -host` command:

```
$(getroute.pl 98.76.54.32)
```

Note that if you have them in your `/etc/hosts`, you might use symbolic names instead of numerical IP addresses (and you might even use FQDN's, if you trust the DNS never to fail).

7. [Reverse piercing](#)

7.1 Rationale

Sometimes, only one side of the firewall can launch telnet sessions into the other side; however, some means of communication is possible (typically, through e-mail). Piercing the firewall is still possible, by triggering with whatever messaging capability is available a telnet connection from the "right" side of the firewall to the other.

`fwprc` includes code to trigger such connections from an OpenPGP-authenticated email message; all you need is add `fwprc` as a `procmail` filter to messages using the protocol, (instructions included in `fwprc` itself). Note however, that if you are to launch `pppd` with appropriate privileges, you might need create your own `suid` wrapper to become root. Instructions enclosed in `fwprc`.

Also, authenticated trigger does not remotely mean secure connection. You should really use `ssh` (perhaps over telnet) for secure connections. And then, beware of what happens between the triggering of a telnet connection, and `ssh` taking over that connection. Contribution in that direction welcome.

7.2 Getting the trigger message

If you are firewalled, your mail may as well be in a central server that doesn't do `procmail` filtering or allow telnet sessions. No problem! You can run `fetchmail` in daemon mode (or within a cron job) to poll your server and deliver mail to your linux system which itself will have been configured to use `procmail` at delivery. Note that if you run `fetchmail` as a background daemon, it will lock away any other `fetchmail` that you'd like to run only at other times, like when you open a `fwprc`; of course, if you can also run a `fetchmail` daemon as a fake user. Too frequent a poll won't be nice to either the server or your host. Too infrequent a poll means you'll have to wait before the message gets read and the reverse connection gets established. I use two-minute poll frequency.

Another way to poll for messages, when you don't have a mailbox, but do have outbound FTP access, is to use [FTP tunnel](#).

8. [Final notes](#)

8.1 Other settings

There are other kinds of firewalls than those that allow for direct ssh or telnet connections. As long as a continuous flow of packets may transmit information through a firewall in both directions, it is possible to pierce it; only the price of writing the piercer may be higher or lower.

In a very easy case, we saw that you can just launch ssh over a pty master and do some pppd in the slave tty. You may even want to do it without an adverse firewall, just so as to build a secure ``VPN" (Virtual Private Network). The [VPN mini-HOWTO](#) gives all the details you need about this. We invite you, as an exercise, to modify fwprc so as to use this technique, or perhaps even so as to use it inside a previous non-secure fwprc session.

Now, if the only way through the firewall is a WWW proxy (usually, a minimum for an Internet-connected network), you might want to use [Chris Chiappa's](#) script [ssh-https-tunnel](#).

Another promising program for piercing through HTTP is [Lars Brinkoff's](#) [httptunnel](#), a http daemon and client combination that achieves a TCP/IP tunnel connection through the proxy-friendly HTTP protocol. You should then be able to run fwprc (preferably over ssh) over that connection, although I haven't tried it yet. Could anyone test and report? Note that httptunnel is still under development, so you may help implement the features it currently lacks, like, having multiple connections, and/or serving fake pages so as to mislead suspicious adverse firewall administrators.

Whatever goes through your firewall, be it telnet, HTTP or other TCP/IP connections, or something real weird like DNS queries, ICMP packets, e-mail (see [mailtunnel](#), [icmptunnel](#)), or whatelse, you can always write a tunnel client/daemon combination, and run a ssh and/or PPP connection through it. The performance mightn't be high, depending on the effective information communication rate after paying the overhead for coding around filters and proxies; but such a tunnel is still interesting as long as it's good enough to use fetchmail, suck, and other non-interactive programs.

If you need cross a 7-bit line, you'll want to use SLIP instead of PPP. I never tried, because lines are more or less 8-bit clean these days, but it shouldn't be difficult. If necessary, fall back to using the [Term-Firewall mini-HOWTO](#).

If you have an 8-bit clean connection and you're root on linux both sides of the firewall, you might want to use ethertap for better performance, encapsulating raw ethernet communications on top of your connection. David Madore has written ethertap-over-TCP and ethertap-over-UDP tunneling <ftp://quatramaran.ens.fr/pub/madore/misc/>. There remains to write some ethertap-over-tty to combine with fwprc-like tools.

If you really need more performance than you can get while paying for a user-space sequential communication tunnel through which to run PPP, then you're in the very hard case where you might have to re-hack a weird IP stack, using (for instance) the Fox project's packet-protocol functors. You'll then achieve some direct IP-over-HTTP, IP-over-DNS, IP-over-ICMP, or such, which requires not only an elaborate protocol, but also an interface to an OS kernel, both of which are costly to implement.

8.2 HOWTO maintenance

I felt it was necessary to write it, but I don't have that much time for that, so this mini-HOWTO is very rough. Thus will it stay, until I get enough feedback so as to know what sections to enhance, or better, until someone comes and takes over maintenance for the mini-HOWTO. Feedback welcome. Help welcome. mini-HOWTO maintenance take-over welcome.

In any case, the above sections have shown many problems whose solution is just a matter of someone (you?) spending some time (or money, by hiring someone else) to sit down and write it: nothing conceptually complicated, though the details might be burdensome or tricky.

Do not hesitate to contribute more problems, and hopefully more solutions, to this mini-HOWTO.

8.3 Related Documents

The [LDP](#) publishes many documents related to this mini-HOWTO, most notably the [Linux Security Knowledge Base](#), the [VPN HOWTO](#) and the [VPN mini-HOWTO](#). For more general questions about networking, routing and firewalling, start from the [Networking Overview HOWTO](#).

Then again, when facing a problem with some program, one reflex for any Linux user should be to RTFM: Read The Fcking Manual pages for the considered programs.

8.4 Final Word

If you think that all this mucking around with stupid scripts and silly HOWTOs is overly complicated and that a decent computer system ought to automate it all for you, then welcome with me among [UNIX haters](#) and other people who hate current low-level operating systems, and yearn for declarative computing systems that take care of the silly details and let us focus on things that matter. (Maybe have a peek at my [TUNES project](#)).

8.5 Extra copy of IMPORTANT DISCLAIMER --- BELIEVE IT!!!

I hereby disclaim all responsibility for *your* use of this hack. If it backfires on you in any way whatsoever, that's the breaks. Not my fault. If you don't understand the risks inherent in doing this, don't do it. If you use this hack and it allows vicious vandals to break into your company's computers and costs you your job and your company millions of dollars, well that's just tough nuggies. Don't come crying to me.
