

BERKELEY LOGO 6.0

Berkeley Logo User Manual

Brian Harvey

Short Contents

1	Introduction	1
2	Data Structure Primitives	9
3	Communication	19
4	Arithmetic	29
5	Logical Operations	35
6	Graphics	37
7	Workspace Management	49
8	Control Structures	67
9	Macros	83
10	Error Processing	87
11	Special Variables	89
12	Internationalization	93
	INDEX	97

Table of Contents

1	Introduction	1
1.1	Overview	1
1.2	Getter/Setter Variable Syntax	2
1.3	Entering and Leaving Logo	5
1.4	Tokenization	6
2	Data Structure Primitives	9
2.1	Constructors	9
	word	9
	list	9
	sentence	9
	fput	9
	lput	9
	array	9
	mdarray	10
	listtoarray	10
	arraytolist	10
	combine	10
	reverse	10
	gensym	10
2.2	Data Selectors	10
	first	10
	firsts	11
	last	11
	butfirst	11
	butfirsts	11
	butlast	12
	item	12
	mditem	12
	pick	12
	remove	12
	remdup	12
	quoted	12
2.3	Data Mutators	12
	setitem	12
	mdsetitem	13
	.setfirst	13
	.setbf	13
	.setitem	13
	push	13
	pop	13
	queue	14
	dequeue	14

2.4	Predicates	14
	wordp	14
	listp	14
	arrayp	14
	empty	14
	equalp	14
	notequalp	15
	beforep	15
	.eq	15
	memberp	15
	substringp	16
	numberp	16
	vbarredp	16
2.5	Queries	16
	count	16
	ascii	16
	rawascii	16
	char	17
	member	17
	lowercase	17
	uppercase	17
	standout	17
	parse	18
	runparse	18
3	Communication	19
3.1	Transmitters	19
	print	19
	type	19
	show	20
3.2	Receivers	20
	readlist	20
	readword	20
	readrawline	20
	readchar	21
	readchars	21
	shell	21
3.3	File Access	22
	setprefix	22
	prefix	22
	openread	22
	openwrite	22
	openappend	23
	openupdate	23
	close	23
	allopen	23
	closeall	23
	erasefile	23

dribble	24
nodribble	24
setread	24
setwrite	24
reader	25
writer	25
setreadpos	25
setwritepos	25
readpos	25
writepos	25
eofp	25
filep	26
3.4 Terminal Access	26
keyp	26
cleartext	26
setcursor	26
cursor	26
setmargins	26
settextcolor	27
increasefont	27
settextsize	27
textsize	27
setfont	28
font	28
4 Arithmetic	29
4.1 Numeric Operations	29
sum	29
difference	29
minus	29
product	29
quotient	29
remainder	30
modulo	30
int	30
round	30
sqrt	30
power	30
exp	30
log10	30
ln	30
sin	31
radsin	31
cos	31
radcos	31
arctan	31
radarctan	31
iseq	31

rseq.....	31
4.2 Numeric Predicates	32
lessp.....	32
greaterp	32
lessequalp.....	32
greaterequalp	32
4.3 Random Numbers.....	32
random	32
rerandom	33
4.4 Print Formatting.....	33
form.....	33
4.5 Bitwise Operations.....	33
bitand	33
bitor	33
bitxor.....	33
bitnot.....	34
ashift	34
lshift.....	34
5 Logical Operations	35
and	35
or.....	35
not	35
6 Graphics	37
6.1 Turtle Motion.....	37
forward	37
back.....	37
left	38
right	38
setpos	38
setxy	38
setx.....	38
sety.....	38
setheading	38
home	38
arc.....	39
6.2 Turtle Motion Queries.....	39
pos	39
xcor	39
ycor	39
heading.....	39
towards.....	39
scrunch	39
6.3 Turtle and Window Control	39
showturtle	39
hideturtle.....	40
clean.....	40

clearscreen	40
wrap	40
window	40
fence	40
fill	41
filled	41
label	41
setlabelheight	41
textscreen	41
fullscreen	41
splitscreen	42
setscrunch	42
refresh	42
norefresh	42
6.4 Turtle and Window Queries	42
shownp	43
screenmode	43
turtlemode	43
labelsize	43
6.5 Pen and Background Control	43
pendown	43
penup	43
penpaint	44
penerase	44
penreverse	44
setpencolor	44
setpalette	44
setpensize	44
setpenpattern	45
setpen	45
setbackground	45
6.6 Pen Queries	45
pendownp	45
penmode	45
pencolor	45
palette	46
pensize	46
pen	46
background	46
6.7 Saving and Loading Pictures	46
savepict	46
loadpict	46
epspict	47
6.8 Mouse Queries	47
mousepos	47
clickpos	47
buttonp	47
button	47

7	Workspace Management	49
7.1	Procedure Definition	49
	to	49
	define	50
	text	51
	fulltext	51
	copydef	51
7.2	Variable Definition	51
	make	51
	name	51
	local	52
	localmake	52
	thing	52
	global	52
7.3	Property Lists	53
	pprop	53
	gprop	53
	remprop	53
	plist	53
7.4	Workspace Predicates	53
	procedurep	53
	primitivep	53
	definedp	54
	namep	54
	plistp	54
7.5	Workspace Queries	54
	contents	54
	buried	54
	traced	54
	stepped	54
	procedures	55
	primitives	55
	names	55
	plists	55
	namelist	55
	pplist	55
	arity	55
	nodes	56
7.6	Workspace Inspection	56
	po	56
	poall	56
	pops	56
	pons	56
	popls	57
	pon	57
	popl	57
	pot	57
	pots	57

7.7 Workspace Control.....	57
erase.....	57
erall.....	58
erps.....	58
erns.....	58
erpls.....	58
ern.....	58
erpl.....	58
bury.....	59
buryall.....	59
buryname.....	59
unbury.....	59
unburyall.....	59
unburyname.....	59
buriedp.....	60
trace.....	60
untrace.....	60
tracedp.....	60
step.....	60
unstep.....	60
steppedp.....	61
edit.....	61
editfile.....	61
edall.....	62
edps.....	62
edns.....	62
edpls.....	62
edn.....	62
edpl.....	62
save.....	62
savel.....	63
load.....	63
cslsload.....	63
help.....	63
seteditor.....	64
setlibloc.....	64
setcslsloc.....	64
sethelploc.....	64
settemploc.....	64
gc.....	64
.setsegmentsize.....	65

8	Control Structures	67
8.1	Control	67
	run	67
	runresult	67
	repeat	67
	forever	67
	repcount	68
	if	68
	ifelse	68
	test	68
	iftrue	68
	iffalse	68
	stop	69
	output	69
	catch	69
	throw	69
	error	70
	pause	70
	continue	70
	wait	71
	bye	71
	.maybeoutput	71
	goto	71
	tag	72
	ignore	72
	'	72
	for	72
	do.while	73
	while	73
	do.until	73
	until	73
	case	74
	cond	74
8.2	Template-based Iteration	74
	apply	76
	invoke	76
	foreach	76
	map	77
	map.se	77
	filter	78
	find	78
	reduce	78
	crossmap	79
	cascade	79
	cascade.2	81
	transfer	81

9	Macros	83
	.macro	83
	.defmacro	85
	macrop	85
	macroexpand	85
10	Error Processing	87
10.1	Error Codes	87
11	Special Variables	89
	allowgetset	89
	buttonact	89
	caseignoredp	89
	commandline	89
	erract	89
	fullprintp	90
	keyact	90
	loadnoisily	90
	printdepthlimit	90
	printwidthlimit	90
	redefp	91
	startup	91
	unburyonedit	91
	usealternatenames	91
	logoversion	91
	logoplatform	91
12	Internationalization	93
	INDEX	97

1 Introduction

1.1 Overview

Copyright © 1993 by the Regents of the University of California

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but *WITHOUT ANY WARRANTY*; without even the implied warranty of *MERCHANTABILITY* or *FITNESS FOR A PARTICULAR PURPOSE*. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 675 Mass Ave, Cambridge, MA 02139, USA.

This is a program that is still being written. Many things are missing, including adequate documentation. This manual assumes that you already know how to program in Logo, and merely presents the details of this new implementation.

Read *Computer Science Logo Style, Volume 1: Symbolic Computing* by Brian Harvey (MIT Press, 1997) for a tutorial on Logo programming with emphasis on symbolic computation.

Here are the special features of this dialect of Logo:

Source file compatible among Unix, DOS, Windows, and Mac platforms.

Random-access arrays.

Variable number of inputs to user-defined procedures.

Mutators for list structure (dangerous).

Pause on error, and other improvements to error handling.

Comments and continuation lines; formatting is preserved when procedure definitions are saved or edited.

Terrapin-style tokenization (e.g., `[2+3]` is a list with one member) but LCSI-style syntax (no special forms except `TO`). The best of both worlds.

First-class instruction and expression templates (see `APPLY`).

Macros.

Features **not** found in Berkeley Logo include robotics, music, animation, parallelism, and multimedia. For those, buy a commercial version.

1.2 Getter/Setter Variable Syntax

Logo distinguishes *procedures* from *variables*. A procedure is a set of instructions to carry out some computation; a variable is a named container that holds a data value such as a number, word, list, or array.

In traditional Logo syntax, a non-numeric word typed without punctuation represents a request to invoke the procedure named by that word. A word typed with a preceding quotation mark represents the word itself. For example, in the instruction

```
PRINT FIRST "WORD
```

the procedures named `FIRST` and `PRINT` are invoked, but the procedure named `WORD` is not invoked; the word *W-O-R-D* is the input to `FIRST`.

What about variables? There are two things one can do with a variable: give it a value, and find out its value. To give a variable a value, Logo provides the primitive procedure `MAKE`, which requires two inputs: the name of the variable and the new value to be assigned. The first input, the name of the variable, is just a word, and if (as is almost always the case) the programmer wants to assign a value to a specific variable whose name is known in advance, that input is quoted, just as any known specific word would be:

```
MAKE "MY.VAR FIRST "WORD
```

gives the variable named `MY.VAR` the value `W` (the first letter of `WORD`).

To find the value of a variable, Logo provides the primitive procedure `THING`, which takes a variable name as its input, and outputs the value of the accessible variable with that name. Thus

```
PRINT THING "MY.VAR
```

will print `W` (supposing the `MAKE` above has been done). Since finding the value of a specific, known variable name is such a common operation, Logo also provides an abbreviated notation that combines `THING` with quote:

```
PRINT :MY.VAR
```

The colon (which Logo old-timers pronounce "dots") replaces `THING` and `"` in the earlier version of the instruction.

Newcomers to Logo often complain about the need for all this punctuation. In particular, Logo programmers who learned about dots and quotes without also learning about `THING` wonder why an instruction such as

```
MAKE "NEW.VAR :OLD.VAR
```

uses two different punctuation marks to identify the two variables. (Having read the paragraphs above, you will understand that actually both variable names are quoted, but the procedure `THING` is invoked to find the value of `OLD.VAR`, since it's that value, not `OLD.VAR`'s

name, that `MAKE` needs to know. It wouldn't make sense to ask for `THING` of `NEW.VAR`, since we haven't given `NEW.VAR` a value yet.)

Although Logo's punctuation rules make sense once understood, they do form a barrier to entry for the Logo beginner. Why, then, couldn't Logo be designed so that an unpunctuated word would represent a procedure if there is a procedure by that name, or a variable if there is a variable by that name? Then we could say

```
PRINT MY.VAR
```

and Logo would realize that `MY.VAR` is the name of a variable, not of a procedure. The traditional reason not to use this convention is that Logo allows the same word to name a procedure and a variable at the same time. This is most often important for words that name data types, as in the following procedure:

```
TO PLURAL :WORD
  OUTPUT WORD :WORD "S
END
```

Here the name `WORD` is a natural choice for the input to `PLURAL`, since it describes the kind of input that `PLURAL` expects. Within the procedure, we use `WORD` to represent Logo's primitive procedure that combines two input words to form a new, longer word; we use `:WORD` to represent the variable containing the input, whatever actual word is given when `PLURAL` is invoked.

```
? PRINT PLURAL "COMPUTER
COMPUTERS
```

However, if a Logo instruction includes an unquoted word that is **not** the name of a procedure, Logo could look for a variable of that name instead. This would allow a "punctuationless" Logo, **provided that users who want to work without colons for variables choose variable names that are not also procedure names.**

What about assigning a value to a variable? Could we do without the quotation mark on `MAKE`'s first input? Alas, no. Although the first input to `MAKE` is **usually** a constant, known variable name, sometimes it isn't, as in this example:

```
TO INCREMENT :VAR
  MAKE :VAR (THING :VAR)+1 ; Note: it's not "VAR here!
END

? MAKE "X 5
? INCREMENT "X
? PRINT :X
6
```

The procedure `INCREMENT` takes a variable name as its input and changes the value of that variable. In this example there are two variables; the variable whose name is `VAR`, and whose value is the word `X`; and the variable whose name is `X` and whose value changes from 5 to 6. Suppose we changed the behavior of `MAKE` so that it took the word after `MAKE` as the name of the variable to change; we would be unable to write `INCREMENT`:


```

TO INCREMENT :VAR ; nonworking!
MAKE VAR (THING VAR)+1
END

```

This would assign a new value to VAR, not to X.

What we can do is to allow an **alternative** to MAKE, a "setter" procedure for a particular variable. The notation will be

```

? SETFOO 7
? PRINT FOO
7

```

SETFOO is a "setter procedure" that takes one input (in this case the input 7) and assigns its value to the variable named FOO.

Berkeley Logo allows users to choose either the traditional notation, in which case the same name can be used both for a procedure and for a variable, or the getter/setter notation, in which variable FOO is set with SETFOO and examined with FOO, but the same name can't be used for procedure and variable.

Here is how this choice is allowed: Berkeley Logo uses traditional notation, with procedures distinct from variables. However, if there is a variable named AllowGetSet whose value is TRUE (which there is, by default, when Logo starts up), then if a Logo instruction refers to a **nonexistent** procedure (so that the error message "I don't know how to ..." would result), Logo tries the following two steps:

1. If the name is at least four characters long, and the first three characters are the letters SET (upper or lower case), and if the name is followed in the instruction by another value, and if the name without the SET is the name of a variable that already exists, then Logo will invoke MAKE with its first input being the name without the SET, and its second input being the following value.
2. If step 1's conditions are not met, but the name is the name of an accessible variable, then Logo will invoke THING with that name as input, to find the variable's value.

Step 1 requires that the variable already exist so that misspellings of names of SETxxx primitives (e.g., SETHEADING) will still be caught, instead of silently creating a new variable. The command GLOBAL can be used to create a variable without giving it a value.

One final point: The TO command in Logo has always been a special case; the rest of the line starting with TO is not evaluated as ordinary Logo expressions are. In particular, the colons used to mark the names of inputs to the procedure do not cause THING to be invoked. They are merely mnemonic aids, reminding the Logo user that these words are names of variables. (Arguably, this nonstandard behavior of TO adds to Logo beginners' confusion about colons.) To a programmer using colonless variable references, the colons in the TO line are unnecessary and meaningless. Berkeley Logo therefore makes the colons optional:

```

TO FOO :IN1 :IN2

```

and

```
TO FOO IN1 IN2
```

are both allowed.

1.3 Entering and Leaving Logo

The process to start Logo depends on your operating system:

- Unix: Type the word `logo` to the shell. (The directory in which you've installed Logo must be in your path.)
- DOS: Change directories to the one containing Logo (probably `C:\UCBLOGO`). Then type `UCBLOGO` for the large memory version, or `BL` for the 640K version.
- Mac: Double-click on the `LOGO` icon within the "UCB Logo" folder.
- Windows: Double-click on the `UCBWLOGO` icon in the `UCBLOGO` folder.

To leave Logo, enter the command `bye`.

On startup, Logo looks for a file named `startup.lg` in the system Logo library and, if found, loads it. Then it looks for `startup.lg` in the user's home directory, or the current directory, depending on the operating system, and loads that. These startup files can be used to predefine procedures, e.g., to provide non-English names for primitive procedures.

Under Unix, DOS, or Windows, if you include one or more filenames on the command line when starting Logo, those files will be loaded before the interpreter starts reading commands from your terminal. If you load a file that executes some program that includes a `bye` command, Logo will run that program and exit. You can therefore write standalone programs in Logo and run them with shell/batch scripts. To support this technique, Logo does not print its usual welcoming and parting messages if you give file arguments to the `logo` command.

If a command line argument is just a hyphen, then all command line arguments after the hyphen are not taken as filenames, but are instead collected in a list, one word per argument; the buried variable `COMMAND.LINE` contains that list of arguments, or the empty list if there are none. On my Linux system, if the first line of an executable shell script is `#!/usr/bin/logo -` (note the hyphen) then the script can be given command line arguments and they all end up in `:COMMAND.LINE` along with the script's path. Experiment.

If you type your interrupt character (see table below) Logo will stop what it's doing and return to top-level, as if you did `THROW "TOPLEVEL`. If you type your quit character Logo will pause as if you did `PAUSE`.

	wxWidgets	Unix	DOS/Windows	Mac Classic
toplevel	alt-S	usually ctrl-C	ctrl-Q	command-. (period)
pause	alt-P	usually ctrl-\	ctrl-W	command-, (comma)

If you have an environment variable called `LOGOLIB` whose value is the name of a directory, then Logo will use that directory instead of the default library. If you invoke a procedure

that has not been defined, Logo first looks for a file in the current directory named `proc.lg` where `proc` is the procedure name in lower case letters. If such a file exists, Logo loads that file. If the missing procedure is still undefined, or if there is no such file, Logo then looks in the library directory for a file named `proc` (no `.lg`) and, if it exists, loads it. If neither file contains a definition for the procedure, then Logo signals an error. Several procedures that are primitive in most versions of Logo are included in the default library, so if you use a different library you may want to include some or all of the default library in it.

1.4 Tokenization

Names of procedures, variables, and property lists are case-insensitive. So are the special words `END`, `TRUE`, and `FALSE`. Case of letters is preserved in everything you type, however.

Within square brackets, words are delimited only by spaces and square brackets. `[2+3]` is a list containing one word. Note, however, that the Logo primitives that interpret such a list as a Logo instruction or expression (`RUN`, `IF`, etc.) reparse the list as if it had not been typed inside brackets.

After a quotation mark outside square brackets, a word is delimited by a space, a square bracket, or a parenthesis.

A word not after a quotation mark or inside square brackets is delimited by a space, a bracket, a parenthesis, or an infix operator `+*/=<>`. Note that words following colons are in this category. Note that quote and colon are not delimiters. Each infix operator character is a word in itself, except that the two-character sequences `<=`, `>=`, and `<>` (the latter meaning not-equal) with no intervening space are recognized as a single word.

A word consisting of a question mark followed by a number (e.g., `?37`), when runparsed (i.e., where a procedure name is expected), is treated as if it were the sequence

`(? 37)`

making the number an input to the `?` procedure. (See the discussion of templates, below.) This special treatment does not apply to words read as data, to words with a non-number following the question mark, or if the question mark is backslashed.

A line (an instruction line or one read by `READLIST` or `READWORD`) can be continued onto the following line if its last character is a tilde (`~`). `READWORD` preserves the tilde and the newline; `READLIST` does not.

Lines read with `READRAWLINE` are never continued.

An instruction line or a line read by `READLIST` (but not by `READWORD`) is automatically continued to the next line, as if ended with a tilde, if there are unmatched brackets, parentheses, braces, or vertical bars pending. However, it's an error if the continuation line contains only the word `END`; this is to prevent runaway procedure definitions. Lines explicitly continued with a tilde avoid this restriction.

If a line being typed interactively on the keyboard is continued, either with a tilde or automatically, Logo will display a tilde as a prompt character for the continuation line.

A semicolon begins a comment in an instruction line. Logo ignores characters from the semicolon to the end of the line. A tilde as the last character still indicates a continuation line, but not a continuation of the comment. For example, typing the instruction

```
print "abc;comment ~
def
```

will print the word `abcdef`. Semicolon has no special meaning in data lines read by `READWORD` or `READLIST`, but such a line can later be reparsed using `RUNPARSE` and then comments will be recognized.

The two-character sequence `#!` at the beginning of a line also starts a comment. Unix users can therefore write a file containing Logo commands, starting with the line

```
#!/usr/bin/logo
```

(or wherever your Logo executable lives) and the file will be executable directly from the shell.

To include an otherwise delimiting character (including semicolon or tilde) in a word, precede it with backslash (`\`). If the last character of a line is a backslash, then the newline character following the backslash will be part of the last word on the line, and the line continues onto the following line. To include a backslash in a word, use `\\`. If the combination backslash-newline is entered at the terminal, Logo will issue a backslash as a prompt character for the continuation line. All of this applies to data lines read with `READWORD` or `READLIST` as well as to instruction lines.

A line read with `READRAWLINE` has no special quoting mechanism; both backslash and vertical bar (described below) are just ordinary characters.

An alternative notation to include otherwise delimiting characters in words is to enclose a group of characters in vertical bars. All characters between vertical bars are treated as if they were letters. In data read with `READWORD` the vertical bars are preserved in the resulting word. In data read with `READLIST` (or resulting from a `PARSE` or `RUNPARSE` of a word) the vertical bars do not appear explicitly; all potentially delimiting characters (including spaces, brackets, parentheses, and infix operators) appear unmarked, but tokenized as though they were letters. Within vertical bars, backslash may still be used; the only characters that must be backslashed in this context are backslash and vertical bar themselves.

Characters entered between vertical bars are forever special, even if the word or list containing them is later reparsed with `PARSE` or `RUNPARSE`. Characters typed after a backslash are treated somewhat differently: When a quoted word containing a backslashed character is runparsed, the backslashed character loses its special quality and acts thereafter as if typed normally. This distinction is important only if you are building a Logo expression out of parts, to be `RUN` later, and want to use parentheses. For example,

```
PRINT RUN (SE "\ ( 2 "+ 3 "\))
```

will print 5, but

```
RUN (SE "MAKE ""|( | 2)
```

will create a variable whose name is open-parenthesis. (Each example would fail if vertical bars and backslashes were interchanged.)

A normally delimiting character entered within vertical bars is **EQUALP** to the same character without the vertical bars, but can be distinguished by the **VBARREDP** predicate. (However, **VBARREDP** returns **TRUE** only for characters for which special treatment is necessary: white-space, parentheses, brackets, infix operators, backslash, vertical bar, tilde, quote, question mark, colon, and semicolon.)

2 Data Structure Primitives

2.1 Constructors

word

```
WORD word1 word2
(WORD word1 word2 word3 ...)
```

outputs a word formed by concatenating its inputs.

list

```
LIST thing1 thing2
(LIST thing1 thing2 thing3 ...)
```

outputs a list whose members are its inputs, which can be any Logo datum (word, list, or array).

sentence

```
SENTENCE thing1 thing2
SE thing1 thing2
(SENTENCE thing1 thing2 thing3 ...)
(SE thing1 thing2 thing3 ...)
```

outputs a list whose members are its inputs, if those inputs are not lists, or the members of its inputs, if those inputs are lists.

fput

```
FPUT thing list
```

outputs a list equal to its second input with one extra member, the first input, at the beginning. If the second input is a word, then the first input must be a one-letter word, and FPUT is equivalent to WORD.

lput

```
LPUT thing list
```

outputs a list equal to its second input with one extra member, the first input, at the end. If the second input is a word, then the first input must be a one-letter word, and LPUT is equivalent to WORD with its inputs in the other order.

array

```
ARRAY size
(ARRAY size origin)
```

outputs an array of *size* members (must be a positive integer), each of which initially is an empty list. Array members can be selected with ITEM and changed with SETITEM. The first member of the array is member number 1 unless an *origin* input (must be an integer) is given, in which case the first member of the array has that number as its index. (Typically

0 is used as the origin if anything.) Arrays are printed by `PRINT` and friends, and can be typed in, inside curly braces; indicate an origin with `{a b c}00`.

See `[ITEM]`, page 12 , `[SETITEM]`, page 12 , `[PRINT]`, page 19 .

mdarray

```
MDARRAY sizelist (library procedure)
(MDARRAY sizelist origin)
```

outputs a multi-dimensional array. The first input must be a list of one or more positive integers. The second input, if present, must be a single integer that applies to every dimension of the array.

Ex: `(MDARRAY [3 5] 0)` outputs a two-dimensional array whose members range from `[0 0]` to `[2 4]`.

listtoarray

```
LISTTOARRAY list
(LISTTOARRAY list origin)
```

outputs an array of the same size as the input list, whose members are the members of the input list.

arraytolist

```
ARRAYTOLIST array
```

outputs a list whose members are the members of the input array. The first member of the output is the first member of the array, regardless of the array's origin.

combine

```
COMBINE thing1 thing2 (library procedure)
```

if *thing2* is a word, outputs `WORD thing1 thing2`. If *thing2* is a list, outputs `FPUT thing1 thing2`.

See `[WORD]`, page 9 , `[FPUT]`, page 9

reverse

```
REVERSE list (library procedure)
```

outputs a list whose members are the members of the input list, in reverse order.

gensym

```
GENSYM (library procedure)
```

outputs a unique word each time it's invoked. The words are of the form `G1`, `G2`, etc.

2.2 Data Selectors

first

```
FIRST thing
```

if the input is a word, outputs the first character of the word. If the input is a list, outputs the first member of the list. If the input is an array, outputs the origin of the array (that is, the *index of* the first member of the array).

firsts

FIRSTS list

outputs a list containing the FIRST of each member of the input list. It is an error if any member of the input list is empty. (The input itself may be empty, in which case the output is also empty.) This could be written as

```
to firsts :list
  output map "first :list
end
```

but is provided as a primitive in order to speed up the iteration tools MAP, MAP.SE, and FOREACH.

```
to transpose :matrix
  if empty? first :matrix [op []]
  op fput firsts :matrix transpose bfs :matrix
end
```

See [MAP], page 77 , [MAPdSE], page 77 , [FOREACH], page 76

last

LAST wordorlist

if the input is a word, outputs the last character of the word. If the input is a list, outputs the last member of the list.

butfirst

BUTFIRST wordorlist
BF wordorlist

if the input is a word, outputs a word containing all but the first character of the input. If the input is a list, outputs a list containing all but the first member of the input.

butfirsts

BUTFIRSTS list
BFS list

outputs a list containing the BUTFIRST of each member of the input list. It is an error if any member of the input list is empty or an array. (The input itself may be empty, in which case the output is also empty.) This could be written as

```
to butfirsts :list
  output map "butfirst :list
end
```


but is provided as a primitive in order to speed up the iteration tools MAP, MAP.SE, and FOREACH.

See [MAP], page 77 , [MAPdSE], page 77 , [FOREACH], page 76

butlast

```
BUTLAST wordorlist
BL wordorlist
```

if the input is a word, outputs a word containing all but the last character of the input. If the input is a list, outputs a list containing all but the last member of the input.

item

```
ITEM index thing
```

if the *thing* is a word, outputs the *index*th character of the word. If the *thing* is a list, outputs the *index*th member of the list. If the *thing* is an array, outputs the *index*th member of the array. *Index* starts at 1 for words and lists; the starting index of an array is specified when the array is created.

mditem

```
MDITEM indexlist array (library procedure)
```

outputs the member of the multidimensional *array* selected by the list of numbers *indexlist*.

pick

```
PICK list (library procedure)
```

outputs a randomly chosen member of the input list.

remove

```
REMOVE thing list (library procedure)
```

outputs a copy of *list* with every member equal to *thing* removed.

remdup

```
REMDUP list (library procedure)
```

outputs a copy of *list* with duplicate members removed. If two or more members of the input are equal, the rightmost of those members is the one that remains in the output.

quoted

```
QUOTED thing (library procedure)
```

outputs its input, if a list; outputs its input with a quotation mark prepended, if a word.

2.3 Data Mutators

setitem

```
SETITEM index array value
```

command. Replaces the *indexth* member of *array* with the new *value*. Ensures that the resulting array is not circular, i.e., *value* may not be a list or array that contains *array*.

mdsetitem

MDSETITEM *indexlist array value* (library procedure)

command. Replaces the member of *array* chosen by *indexlist* with the new *value*.

.setfirst

.SETFIRST *list value*

command. Changes the first member of *list* to be *value*.

WARNING: Primitives whose names start with a period are **dangerous**. Their use by non-experts is not recommended. The use of .SETFIRST can lead to circular list structures, which will get some Logo primitives into infinite loops, and to unexpected changes to other data structures that share storage with the list being modified.

.setbf

.SETBF *list value*

command. Changes the butfirst of *list* to be *value*.

WARNING: Primitives whose names start with a period are **dangerous**. Their use by non-experts is not recommended. The use of .SETBF can lead to circular list structures, which will get some Logo primitives into infinite loops; unexpected changes to other data structures that share storage with the list being modified; or to Logo crashes and coredumps if the butfirst of a list is not itself a list.

.setitem

.SETITEM *index array value*

command. Changes the *indexth* member of *array* to be *value*, like SETITEM, but without checking for circularity.

WARNING: Primitives whose names start with a period are **dangerous**. Their use by non-experts is not recommended. The use of .SETITEM can lead to circular arrays, which will get some Logo primitives into infinite loops.

See [SETITEM], page 12.

push

PUSH *stackname thing* (library procedure)

command. Adds the *thing* to the stack that is the value of the variable whose name is *stackname*. This variable must have a list as its value; the initial value should be the empty list. New members are added at the front of the list.

pop

POP *stackname* (library procedure)

outputs the most recently **PUSHed** member of the stack that is the value of the variable whose name is *stackname* and removes that member from the stack.

queue

`QUEUE queueName thing (library procedure)`

command. Adds the *thing* to the queue that is the value of the variable whose name is *queueName*. This variable must have a list as its value; the initial value should be the empty list. New members are added at the back of the list.

dequeue

`DEQUEUE queueName (library procedure)`

outputs the least recently **QUEUED** member of the queue that is the value of the variable whose name is *queueName* and removes that member from the queue.

2.4 Predicates

wordp

`WORDP thing`
`WORD? thing`

outputs **TRUE** if the input is a word, **FALSE** otherwise.

listp

`LISTP thing`
`LIST? thing`

outputs **TRUE** if the input is a list, **FALSE** otherwise.

arrayp

`ARRAYP thing`
`ARRAY? thing`

outputs **TRUE** if the input is an array, **FALSE** otherwise.

emptyp

`EMPTYP thing`
`EMPTY? thing`

outputs **TRUE** if the input is the empty word or the empty list, **FALSE** otherwise.

equalp

`EQUALP thing1 thing2`
`EQUAL? thing1 thing2`
`thing1 = thing2`

outputs **TRUE** if the inputs are equal, **FALSE** otherwise. Two numbers are equal if they have the same numeric value. Two non-numeric words are equal if they contain the same

characters in the same order. If there is a variable named `CASEIGNOREDP` whose value is `TRUE`, then an upper case letter is considered the same as the corresponding lower case letter. (This is the case by default.) Two lists are equal if their members are equal. An array is only equal to itself; two separately created arrays are never equal even if their members are equal. (It is important to be able to know if two expressions have the same array as their value because arrays are mutable; if, for example, two variables have the same array as their values then performing `SETITEM` on one of them will also change the other.)

See `[CASEIGNOREDP]`, page 89 , `[SETITEM]`, page 12

notequalp

```
NOTEQUALP thing1 thing2
NOTEQUAL? thing1 thing2
thing1 <> thing2
```

outputs `FALSE` if the inputs are equal, `TRUE` otherwise. See `EQUALP` for the meaning of equality for different data types.

beforep

```
BEFOREP word1 word2
BEFORE? word1 word2
```

outputs `TRUE` if *word1* comes before *word2* in ASCII collating sequence (for words of letters, in alphabetical order). Case-sensitivity is determined by the value of `CASEIGNOREDP`. Note that if the inputs are numbers, the result may not be the same as with `LESSP`; for example, `BEFOREP 3 12` is false because 3 collates after 1.

See `[CASEIGNOREDP]`, page 89 , `[LESSP]`, page 32

.eq

```
.EQ thing1 thing2
```

outputs `TRUE` if its two inputs are the same datum, so that applying a mutator to one will change the other as well. Outputs `FALSE` otherwise, even if the inputs are equal in value.

WARNING: Primitives whose names start with a period are **dangerous**. Their use by non-experts is not recommended. The use of mutators can lead to circular data structures, infinite loops, or Logo crashes.

memberp

```
MEMBERP thing1 thing2
MEMBER? thing1 thing2
```

if *thing2* is a list or an array, outputs `TRUE` if *thing1* is `EQUALP` to a member of *thing2*, `FALSE` otherwise. If *thing2* is a word, outputs `TRUE` if *thing1* is a one-character word `EQUALP` to a character of *thing2*, `FALSE` otherwise.

See `[EQUALP]`, page 14 .

substringp

```
SUBSTRINGP thing1 thing2
SUBSTRING? thing1 thing2
```

if *thing1* or *thing2* is a list or an array, outputs **FALSE**. If *thing2* is a word, outputs **TRUE** if *thing1* is **EQUALP** to a substring of *thing2*, **FALSE** otherwise.

See [EQUALP], page 14 .

numberp

```
NUMBERP thing
NUMBER? thing
```

outputs **TRUE** if the input is a number, **FALSE** otherwise.

vbarredp

```
VBARREDP char
VBARRED? char
BACKSLASHEDP char (library procedure)
BACKSLASHED? char (library procedure)
```

outputs **TRUE** if the input character was originally entered into Logo within vertical bars (|) to prevent its usual special syntactic meaning, **FALSE** otherwise. (Outputs **TRUE** only if the character is a backslashed space, tab, newline, or one of () [] +-* / =<> " ; \ ~ ? |)

The names **BACKSLASHEDP** and **BACKSLASHED?** are included in the Logo library for backward compatibility with the former names of this primitive, although it does *not* output **TRUE** for characters originally entered with backslashes.

2.5 Queries**count**

```
COUNT thing
```

outputs the number of characters in the input, if the input is a word; outputs the number of members in the input, if it is a list or an array. (For an array, this may or may not be the index of the last member, depending on the array's origin.)

ascii

```
ASCII char
```

outputs the integer (between 0 and 255) that represents the input character in the ASCII code. Interprets control characters as representing vbarred punctuation, and returns the character code for the corresponding punctuation character without vertical bars. (Compare **RAWASCII**.)

rawascii

```
RAWASCII char
```

outputs the integer (between 0 and 255) that represents the input character in the ASCII code. Interprets control characters as representing themselves. To find out the ASCII code of an arbitrary keystroke, use `RAWASCII RC`.

char

`CHAR int`

outputs the character represented in the ASCII code by the input, which must be an integer between 0 and 255.

See [ASCII], page 16 .

member

`MEMBER thing1 thing2`

if *thing2* is a word or list and if `MEMBERP` with these inputs would output `TRUE`, outputs the portion of *thing2* from the first instance of *thing1* to the end. If `MEMBERP` would output `FALSE`, outputs the empty word or list according to the type of *thing2*. It is an error for *thing2* to be an array.

See [MEMBERP], page 15 .

lowercase

`LOWERCASE word`

outputs a copy of the input word, but with all uppercase letters changed to the corresponding lowercase letter.

uppercase

`UPPERCASE word`

outputs a copy of the input word, but with all lowercase letters changed to the corresponding uppercase letter.

standout

`STANDOUT thing`

outputs a word that, when printed, will appear like the input but displayed in standout mode (boldface, reverse video, or whatever your version does for standout). The word contains machine-specific magic characters at the beginning and end; in between is the printed form (as if displayed using `TYPE`) of the input. The output is always a word, even if the input is of some other type, but it may include spaces and other formatting characters. Note: a word output by `STANDOUT` while Logo is running on one machine will probably not have the desired effect if printed on another type of machine.

In the Macintosh classic version, the way that standout works is incompatible with the use of characters whose ASCII code is greater than 127. Therefore, you have a choice to make: The instruction

`CANINVERSE 0`

disables standout, but enables the display of ASCII codes above 127, and the instruction

`CANINVERSE 1`

restores the default situation in which standout is enabled and the extra graphic characters cannot be printed.

parse

`PARSE word`

outputs the list that would result if the input word were entered in response to a `READLIST` operation. That is, `PARSE READWORD` has the same value as `READLIST` for the same characters read.

See `[READLIST]`, page 20 , `[READWORD]`, page 20

runparse

`RUNPARSE wordorlist`

outputs the list that would result if the input word or list were entered as an instruction line; characters such as infix operators and parentheses are separate members of the output. Note that sublists of a runparsed list are not themselves runparsed.

3 Communication

3.1 Transmitters

Note: If there is a variable named `PRINTDEPTHLIMIT` with a nonnegative integer value, then complex list and array structures will be printed only to the allowed depth. That is, members of members of... of members will be allowed only so far. The members omitted because they are just past the depth limit are indicated by an ellipsis for each one, so a too-deep list of two members will print as `[... ...]`.

If there is a variable named `PRINTWIDTHLIMIT` with a nonnegative integer value, then only the first so many members of any array or list will be printed. A single ellipsis replaces all missing data within the structure. The width limit also applies to the number of characters printed in a word, except that a `PRINTWIDTHLIMIT` between 0 and 9 will be treated as if it were 10 when applied to words. This limit applies not only to the top-level printed datum but to any substructures within it.

See `[PRINTDEPTHLIMIT]`, page 90 , `[PRINTWIDTHLIMIT]`, page 90

If there is a variable named `FULLPRINTP` whose value is `TRUE`, then words that were created using backslash or vertical bar (to include characters that would otherwise not be treated as part of a word) are printed with the backslashes or vertical bars shown, so that the printed result could be re-read by Logo to produce the same value. If `FULLPRINTP` is `TRUE` then the empty word (however it was created) prints as `||`. (Otherwise it prints as nothing at all.)

See `[FULLPRINTP]`, page 90 .

print

```
PRINT thing
PR thing
(PRINT thing1 thing2 ...)
(PR thing1 thing2 ...)
```

command. Prints the input or inputs to the current write stream (initially the screen). All the inputs are printed on a single line, separated by spaces, ending with a newline. If an input is a list, square brackets are not printed around it, but brackets are printed around sublists. Braces are always printed around arrays.

type

```
TYPE thing
(TYPE thing1 thing2 ...)
```

command. Prints the input or inputs like `PRINT`, except that no newline character is printed at the end and multiple inputs are not separated by spaces. Note: printing to the screen is ordinarily *line buffered*; that is, the characters you print using `TYPE` will not actually appear on the screen until either a newline character is printed (for example, by `PRINT` or `SHOW`) or Logo tries to read from the keyboard (either at the request of your program or after an instruction prompt). This buffering makes the program much faster than it would be if each character appeared immediately, and in most cases the effect is not disconcerting. To

accommodate programs that do a lot of positioned text display using **TYPE**, Logo will force printing whenever **SETCURSOR** is invoked. This solves most buffering problems. Still, on occasion you may find it necessary to force the buffered characters to be printed explicitly; this can be done using the **WAIT** command. **WAIT 0** will force printing without actually waiting.

See [**SETCURSOR**], page 26 , [**WAIT**], page 71

show

```
SHOW thing
(SHOW thing1 thing2 ...)
```

command. Prints the input or inputs like **PRINT**, except that if an input is a list it is printed inside square brackets.

See [**PRINT**], page 19 .

3.2 Receivers

readlist

```
READLIST
RL
```

reads a line from the read stream (initially the keyboard) and outputs that line as a list. The line is separated into members as though it were typed in square brackets in an instruction. If the read stream is a file, and the end of file is reached, **READLIST** outputs the empty word (not the empty list). **READLIST** processes backslash, vertical bar, and tilde characters in the read stream; the output list will not contain these characters but they will have had their usual effect. **READLIST** does not, however, treat semicolon as a comment character.

readword

```
READWORD
RW
```

reads a line from the read stream and outputs that line as a word. The output is a single word even if the line contains spaces, brackets, etc. If the read stream is a file, and the end of file is reached, **READWORD** outputs the empty list (not the empty word). **READWORD** processes backslash, vertical bar, and tilde characters in the read stream. In the case of a tilde used for line continuation, the output word *does* include the tilde and the newline characters, so that the user program can tell exactly what the user entered. Vertical bars in the line are also preserved in the output. Backslash characters are not preserved in the output.

readrawline

```
READRAWLINE
```

reads a line from the read stream and outputs that line as a word. The output is a single word even if the line contains spaces, brackets, etc. If the read stream is a file, and the end of file is reached, **READRAWLINE** outputs the empty list (not the empty word). **READRAWLINE**

outputs the exact string of characters as they appear in the line, with no special meaning for backslash, vertical bar, tilde, or any other formatting characters.

See [READWORD], page 20 .

readchar

```
READCHAR
RC
```

reads a single character from the read stream and outputs that character as a word. If the read stream is a file, and the end of file is reached, **READCHAR** outputs the empty list (not the empty word). If the read stream is the keyboard, echoing is turned off when **READCHAR** is invoked, and remains off until **READLIST** or **READWORD** is invoked or a Logo prompt is printed. Backslash, vertical bar, and tilde characters have no special meaning in this context.

See [READLIST], page 20 .

readchars

```
READCHARS num
RCS num
```

reads *num* characters from the read stream and outputs those characters as a word. If the read stream is a file, and the end of file is reached, **READCHARS** outputs the empty list (not the empty word). If the read stream is the keyboard, echoing is turned off when **READCHARS** is invoked, and remains off until **READLIST** or **READWORD** is invoked or a Logo prompt is printed. Backslash, vertical bar, and tilde characters have no special meaning in this context.

See [READLIST], page 20 , [READWORD], page 20

shell

```
SHELL command
(SHELL command wordflag)
```

Under Unix, outputs the result of running *command* as a shell command. (The command is sent to `/bin/sh`, not `csh` or other alternatives.) If the command is a literal list in the instruction line, and if you want a backslash character sent to the shell, you must use `\\` to get the backslash through Logo's reader intact. The output is a list containing one member for each line generated by the shell command. Ordinarily each such line is represented by a list in the output, as though the line were read using **READLIST**. If a second input is given, regardless of the value of the input, each line is represented by a word in the output as though it were read with **READWORD**. Example:

```
to dayofweek
  output first first shell [date]
end
```

This is **first first** to extract the first word of the first (and only) line of the shell output.

Under MacOS X, **SHELL** works as under Unix. **SHELL** is not available under Mac Classic.

Under DOS, **SHELL** is a command, not an operation; it sends its input to a DOS command processor but does not collect the result of the command.

Under Windows, the wxWidgets version of Logo behaves as under Unix (except that DOS-style commands are understood; use **dir** rather than **ls**). The non-wxWidgets version behaves like the DOS version.

3.3 File Access

setprefix

SETPREFIX *string*

command. Sets a prefix that will be used as the implicit beginning of filenames in **OPENREAD**, **OPENWRITE**, **OPENAPPEND**, **OPENUPDATE**, **LOAD**, and **SAVE** commands. Logo will put the appropriate separator character (slash for Unix, backslash for DOS/Windows, colon for MacOS Classic) between the prefix and the filename entered by the user. The input to **SETPREFIX** must be a word, unless it is the empty list, to indicate that there should be no prefix.

See [OPENREAD], page 22 , See [OPENWRITE], page 22 , See [OPENAPPEND], page 23 , See [OPENUPDATE], page 23 , See [LOAD], page 63 , See [SAVE], page 62 .

prefix

PREFIX

outputs the current file prefix, or [] if there is no prefix.

See [SETPREFIX], page 22 .

openread

OPENREAD *filename*

command. Opens the named file for reading. The read position is initially at the beginning of the file.

openwrite

OPENWRITE *filename*

command. Opens the named file for writing. If the file already existed, the old version is deleted and a new, empty file created.

OPENWRITE, but not the other **OPEN** variants, will accept as input a two-element list, in which the first element must be a variable name, and the second must be a positive integer. A character buffer of the specified size will be created. When a **SETWRITE** is done with this same list (in the sense of **.EQ**, not a copy, so you must do something like

```
? make "buf [foo 100]
? openwrite :buf
? setwrite :buf
  [...]
? close :buf
```

and not just

```
? openwrite [foo 100]
? setwrite [foo 100]
```

and so on), the printed characters are stored in the buffer; when a `CLOSE` is done with the same list as input, the characters from the buffer (treated as one long word, even if spaces and newlines are included) become the value of the specified variable.

openappend

```
OPENAPPEND filename
```

command. Opens the named file for writing. If the file already exists, the write position is initially set to the end of the old file, so that newly written data will be appended to it.

openupdate

```
OPENUPDATE filename
```

command. Opens the named file for reading and writing. The read and write position is initially set to the end of the old file, if any. Note: each open file has only one position, for both reading and writing. If a file opened for update is both `READER` and `WRITER` at the same time, then `SETREADPOS` will also affect `WRITEPOS` and vice versa. Also, if you alternate reading and writing the same file, you must `SETREADPOS` between a write and a read, and `SETWRITEPOS` between a read and a write.

See `[READER]`, page 25 , `[WRITER]`, page 25 , `[SETREADPOS]`, page 25 , `[SETWRITEPOS]`, page 25

close

```
CLOSE filename
```

command. Closes the named file. If the file was currently the reader or writer, then the reader or writer is changed to the keyboard or screen, as if `SETREAD []` or `SETWRITE []` had been done.

allopen

```
ALLOPEN
```

outputs a list whose members are the names of all files currently open. This list does not include the dribble file, if any.

closeall

```
CLOSEALL (library procedure)
```

command. Closes all open files. Abbreviates `FOREACH ALLOPEN [CLOSE ?]`

See `[FOREACH]`, page 76 , `[CLOSE]`, page 23

erasefile

```
ERASEFILE filename
```

ERF filename

command. Erases (deletes, removes) the named file, which should not currently be open.

dribble

DRIBBLE filename

command. Creates a new file whose name is the input, like **OPENWRITE**, and begins recording in that file everything that is read from the keyboard or written to the terminal. That is, this writing is in addition to the writing to **WRITER**. The intent is to create a transcript of a Logo session, including things like prompt characters and interactions.

See [OPENWRITE], page 22 , [WRITER], page 25

nodribble

NODRIBBLE

command. Stops copying information into the dribble file, and closes the file.

setread

SETREAD filename

command. Makes the named file the read stream, used for **READLIST**, etc. The file must already be open with **OPENREAD** or **OPENUPDATE**. If the input is the empty list, then the read stream becomes the keyboard, as usual. Changing the read stream does not close the file that was previously the read stream, so it is possible to alternate between files.

See [READLIST], page 20 , [OPENREAD], page 22 , [OPENUPDATE], page 23

setwrite

SETWRITE filename

command. Makes the named file the write stream, used for **PRINT**, etc. The file must already be open with **OPENWRITE**, **OPENAPPEND**, or **OPENUPDATE**. If the input is the empty list, then the write stream becomes the screen, as usual. Changing the write stream does not close the file that was previously the write stream, so it is possible to alternate between files.

If the input is a list, then its first element must be a variable name, and its second and last element must be a positive integer; a buffer of that many characters will be allocated, and will become the writestream. If the same list (same in the **.EQ** sense, not a copy) has been used as input to **OPENWRITE**, then the already-allocated buffer will be used, and the writer can be changed to and from this buffer, with all the characters accumulated as in a file. When the same list is used as input to **CLOSE**, the contents of the buffer (as an unparsed word, which may contain newline characters) will become the value of the named variable. For compatibility with earlier versions, if the list has not been opened when the **SETWRITE** is done, it will be opened implicitly, but the first **SETWRITE** after this one will implicitly close it, setting the variable and freeing the allocated buffer.

See [PRINT], page 19 , [OPENWRITE], page 22 ; [OPENAPPEND], page 23 ; [OPENUPDATE], page 23

reader

READER

outputs the name of the current read stream file, or the empty list if the read stream is the terminal.

writer

WRITER

outputs the name of the current write stream file, or the empty list if the write stream is the screen.

setreadposSETREADPOS *charpos*

command. Sets the file pointer of the read stream file so that the next **READLIST**, etc., will begin reading at the *charpos*th character in the file, counting from 0. (That is, **SETREADPOS** 0 will start reading from the beginning of the file.) Meaningless if the read stream is the keyboard.

See [READLIST], page 20 .

setwriteposSETWRITEPOS *charpos*

command. Sets the file pointer of the write stream file so that the next **PRINT**, etc., will begin writing at the *charpos*th character in the file, counting from 0. (That is, **SETWRITEPOS** 0 will start writing from the beginning of the file.) Meaningless if the write stream is the screen.

See [PRINT], page 19 .

readpos

READPOS

outputs the file position of the current read stream file.

writepos

WRITEPOS

outputs the file position of the current write stream file.

eofpEOFP
EOF?

predicate, outputs **TRUE** if there are no more characters to be read in the read stream file, **FALSE** otherwise.

filep

```
FILEP filename
FILE? filename (library procedure)
```

predicate, outputs **TRUE** if a file of the specified name exists and can be read, **FALSE** otherwise.

3.4 Terminal Access**keyp**

```
KEYP
KEY?
```

predicate, outputs **TRUE** if there are characters waiting to be read from the read stream. If the read stream is a file, this is equivalent to **NOT EOF**. If the read stream is the terminal, then echoing is turned off and the terminal is set to **cbreak** (character at a time instead of line at a time) mode. It remains in this mode until some line-mode reading is requested (e.g., **READLIST**). The Unix operating system forgets about any pending characters when it switches modes, so the first **KEYP** invocation will always output **FALSE**.

See [**EOF**], page 25 , [**READLIST**], page 20

cleartext

```
CLEARTEXT
CT
```

command. Clears the text window.

setcursor

```
SETCURSOR vector
```

command. The input is a list of two numbers, the x and y coordinates of a text window position (origin in the upper left corner, positive direction is southeast). The text cursor is moved to the requested position. This command also forces the immediate printing of any buffered characters.

cursor

```
CURSOR
```

outputs a list containing the current x and y coordinates of the text cursor. Logo may get confused about the current cursor position if, e.g., you type in a long line that wraps around or your program prints escape codes that affect the screen strangely.

setmargins

```
SETMARGINS vector
```

command. The input must be a list of two numbers, as for **SETCURSOR**. The effect is to clear the screen and then arrange for all further printing to be shifted down and to the right according to the indicated margins. Specifically, every time a newline character is

printed (explicitly or implicitly) Logo will type *x_margin* spaces, and on every invocation of `SETCURSOR` the margins will be added to the input *x* and *y* coordinates. (`CURSOR` will report the cursor position relative to the margins, so that this shift will be invisible to Logo programs.) The purpose of this command is to accommodate the display of terminal screens in lecture halls with inadequate TV monitors that miss the top and left edges of the screen.

See [SETCURSOR], page 26 .

setttextcolor

```
SETTEXTCOLOR foreground background
SETTC foreground background
```

command (wxWidgets only). The inputs are color numbers, or RGB color lists, as for turtle graphics. The foreground and background colors for the textscreen/splitcreen text window are changed to the given values. The change affects text already printed as well as future text printing; there is only one text color for the entire window.

Command (non-wxWidgets Windows and DOS extended only). The inputs are color numbers, as for turtle graphics. Future printing to the text window will use the specified colors for foreground (the characters printed) and background (the space under those characters). Using `STANDOUT` will revert to the default text window colors. In the DOS extended (`ucblogo.exe`) version, colors in textscreen mode are limited to numbers 0-7, and the coloring applies only to text printed by the program, not to the echoing of text typed by the user. Neither limitation applies to the text portion of splitcreen mode, which is actually drawn as graphics internally.

See [STANDOUT], page 17 .

increasefont

```
INCREASEFONT
DECREASEFONT
```

command (wxWidgets only). Increase or decrease the size of the font used in the text and edit windows to the next larger or smaller available size.

setttextsize

```
SETTEXTSIZE height
```

command (wxWidgets only). Set the "point size" of the font used in the text and edit windows to the given integer input. The desired size may not be available, in which case the nearest available size will be used. Note: There is only a slight correlation between these integers and pixel sizes. Our rough estimate is that the number of pixels of height is about 1.5 times the point size, but it varies for different fonts. See `SETLABELHEIGHT` for a different approach used for the graphics window.

textsize

```
TEXTSIZE
```


(wxWidgets only) outputs the "point size" of the font used in the text and edit windows. See `SETTEXTSIZE` for a discussion of font sizing. See `LABELSIZE` for a different approach used for the graphics window.

setfont

`SETFONT fontname`

command (wxWidgets only). Set the font family used in all windows to the one named by the input. Try `Courier` or `Monospace` as likely possibilities. Not all computers have the same fonts installed. It's a good idea to stick with monospace fonts (ones in which all characters have the same width).

font

`FONT`

(wxWidgets only) outputs the name of the font family used in all windows.

4 Arithmetic

4.1 Numeric Operations

sum

```
SUM num1 num2
(SUM num1 num2 num3 ...)
num1 + num2
```

outputs the sum of its inputs.

difference

```
DIFFERENCE num1 num2
num1 - num2
```

outputs the difference of its inputs. Minus sign means infix difference in ambiguous contexts (when preceded by a complete expression), unless it is preceded by a space and followed by a nonspace. (See also MINUS.)

minus

```
MINUS num
- num
```

outputs the negative of its input. Minus sign means unary minus if the previous token is an infix operator or open parenthesis, or it is preceded by a space and followed by a nonspace. There is a difference in binding strength between the two forms:

```
MINUS 3 + 4      means  -(3+4)
- 3 + 4          means  (-3)+4
```

product

```
PRODUCT num1 num2
(PRODUCT num1 num2 num3 ...)
num1 * num2
```

outputs the product of its inputs.

quotient

```
QUOTIENT num1 num2
(QUOTIENT num)
num1 / num2
```

outputs the quotient of its inputs. The quotient of two integers is an integer if and only if the dividend is a multiple of the divisor. (In other words, QUOTIENT 5 2 is 2.5, not 2, but QUOTIENT 4 2 is 2, not 2.0 — it does the right thing.) With a single input, QUOTIENT outputs the reciprocal of the input.

remainder

REMAINDER *num1 num2*

outputs the remainder on dividing *num1* by *num2*; both must be integers and the result is an integer with the same sign as *num1*.

modulo

MODULO *num1 num2*

outputs the remainder on dividing *num1* by *num2*; both must be integers and the result is an integer with the same sign as *num2*.

int

INT *num*

outputs its input with fractional part removed, i.e., an integer with the same sign as the input, whose absolute value is the largest integer less than or equal to the absolute value of the input.

round

ROUND *num*

outputs the nearest integer to the input.

sqrt

SQRT *num*

outputs the square root of the input, which must be nonnegative.

power

POWER *num1 num2*

outputs *num1* to the *num2* power. If *num1* is negative, then *num2* must be an integer.

exp

EXP *num*

outputs e (2.718281828+) to the input power.

log10

LOG10 *num*

outputs the common logarithm of the input.

ln

LN *num*

outputs the natural logarithm of the input.

sin

SIN degrees

outputs the sine of its input, which is taken in degrees.

radsin

RADSIN radians

outputs the sine of its input, which is taken in radians.

cos

COS degrees

outputs the cosine of its input, which is taken in degrees.

radcos

RADCOS radians

outputs the cosine of its input, which is taken in radians.

arctan

ARCTAN num
(ARCTAN x y)

outputs the arctangent, in degrees, of its input. With two inputs, outputs the arctangent of y/x , if x is nonzero, or 90 or -90 depending on the sign of y , if x is zero.

radarctan

RADARCTAN num
(RADARCTAN x y)

outputs the arctangent, in radians, of its input. With two inputs, outputs the arctangent of y/x , if x is nonzero, or $\pi/2$ or $-\pi/2$ depending on the sign of y , if x is zero.

The expression `2*(RADARCTAN 0 1)` can be used to get the value of π .

iseq

ISEQ from to (library procedure)

outputs a list of the integers from *from* to *to*, inclusive.

```
? show iseq 3 7
[3 4 5 6 7]
? show iseq 7 3
[7 6 5 4 3]
```

rseq

RSEQ from to count (library procedure)

outputs a list of *count* equally spaced rational numbers between *from* and *to*, inclusive.

```
? show rseq 3 5 9
[3 3.25 3.5 3.75 4 4.25 4.5 4.75 5]
? show rseq 3 5 5
[3 3.5 4 4.5 5]
```

4.2 Numeric Predicates

lessp

```
LESSP num1 num2
LESS? num1 num2
num1 < num2
```

outputs TRUE if its first input is strictly less than its second.

greaterp

```
GREATERP num1 num2
GREATER? num1 num2
num1 > num2
```

outputs TRUE if its first input is strictly greater than its second.

lessequalp

```
LESSEQUALP num1 num2
LESSEQUAL? num1 num2
num1 <= num2
```

outputs TRUE if its first input is less than or equal to its second.

greaterqualp

```
GREATEREQUALP num1 num2
GREATEREQUAL? num1 num2
num1 >= num2
```

outputs TRUE if its first input is greater than or equal to its second.

4.3 Random Numbers

random

```
RANDOM num
(RANDOM start end)
```

with one input, outputs a random nonnegative integer less than its input, which must be a positive integer.

With two inputs, `RANDOM` outputs a random integer greater than or equal to the first input, and less than or equal to the second input. Both inputs must be integers, and the first must be less than the second. `(RANDOM 0 9)` is equivalent to `RANDOM 10`; `(RANDOM 3 8)` is equivalent to `(RANDOM 6)+3`.

rerandom

```
RERANDOM
(RERANDOM seed)
```

command. Makes the results of `RANDOM` reproducible. Ordinarily the sequence of random numbers is different each time Logo is used. If you need the same sequence of pseudo-random numbers repeatedly, e.g. to debug a program, say `RERANDOM` before the first invocation of `RANDOM`. If you need more than one repeatable sequence, you can give `RERANDOM` an integer input; each possible input selects a unique sequence of numbers.

4.4 Print Formatting**form**

```
FORM num width precision
```

outputs a word containing a printable representation of *num*, possibly preceded by spaces (and therefore not a number for purposes of performing arithmetic operations), with at least *width* characters, including exactly *precision* digits after the decimal point. (If *precision* is 0 then there will be no decimal point in the output.)

As a debugging feature, (`FORM num -1 format`) will print the floating point *num* according to the C `printf format`, to allow

```
to hex :num
  op form :num -1 "|%08X %08X|
end
```

to allow finding out the exact result of floating point operations. The precise format needed may be machine-dependent.

4.5 Bitwise Operations**bitand**

```
BITAND num1 num2
(BITAND num1 num2 num3 ...)
```

outputs the bitwise *and* of its inputs, which must be integers.

See [AND], page 35 .

bitor

```
BITOR num1 num2
(BITOR num1 num2 num3 ...)
```

outputs the bitwise *or* of its inputs, which must be integers.

See [OR], page 35 .

bitxor

```
BITXOR num1 num2
```

`(BITXOR num1 num2 num3 ...)`

outputs the bitwise *exclusive or* of its inputs, which must be integers.

See [OR], page 35 .

bitnot

`BITNOT num`

outputs the bitwise *not* of its input, which must be an integer.

See [NOT], page 35 .

ashift

`ASHIFT num1 num2`

outputs *num1* arithmetic-shifted to the left by *num2* bits. If *num2* is negative, the shift is to the right with sign extension. The inputs must be integers.

lshift

`LSHIFT num1 num2`

outputs *num1* logical-shifted to the left by *num2* bits. If *num2* is negative, the shift is to the right with zero fill. The inputs must be integers.

5 Logical Operations

and

```
AND tf1 tf2
(AND tf1 tf2 tf3 ...)
```

outputs **TRUE** if all inputs are **TRUE**, otherwise **FALSE**. All inputs must be **TRUE** or **FALSE**. (Comparison is case-insensitive regardless of the value of **CASEIGNOREDP**. That is, **true** or **True** or **TRUE** are all the same.) An input can be a list, in which case it is taken as an expression to run; that expression must produce a **TRUE** or **FALSE** value. List expressions are evaluated from left to right; as soon as a **FALSE** value is found, the remaining inputs are not examined. Example:

```
MAKE "RESULT AND [NOT (:X = 0)] [(1 / :X) > .5]
```

to avoid the division by zero if the first part is false.

See [CASEIGNOREDP], page 89 .

or

```
OR tf1 tf2
(OR tf1 tf2 tf3 ...)
```

outputs **TRUE** if any input is **TRUE**, otherwise **FALSE**. All inputs must be **TRUE** or **FALSE**. (Comparison is case-insensitive regardless of the value of **CASEIGNOREDP**. That is, **true** or **True** or **TRUE** are all the same.) An input can be a list, in which case it is taken as an expression to run; that expression must produce a **TRUE** or **FALSE** value. List expressions are evaluated from left to right; as soon as a **TRUE** value is found, the remaining inputs are not examined. Example:

```
IF OR :X=0 [some.long.computation] [...]
```

to avoid the long computation if the first condition is met.

See [CASEIGNOREDP], page 89 .

not

```
NOT tf
```

outputs **TRUE** if the input is **FALSE**, and vice versa. The input can be a list, in which case it is taken as an expression to run; that expression must produce a **TRUE** or **FALSE** value.

6 Graphics

Berkeley Logo provides traditional Logo turtle graphics with one turtle. Multiple turtles, dynamic turtles, and collision detection are not supported. This is the most hardware-dependent part of Logo; some features may exist on some machines but not others. Nevertheless, the goal has been to make Logo programs as portable as possible, rather than to take fullest advantage of the capabilities of each machine. In particular, Logo attempts to scale the screen so that turtle coordinates $[-100 -100]$ and $[100 100]$ fit on the graphics window, and so that the aspect ratio is 1:1.

The center of the graphics window (which may or may not be the entire screen, depending on the machine used) is turtle location $[0 0]$. Positive X is to the right; positive Y is up. Headings (angles) are measured in degrees clockwise from the positive Y axis. (This differs from the common mathematical convention of measuring angles counterclockwise from the positive X axis.) The turtle is represented as an isocles triangle; the actual turtle position is at the midpoint of the base (the short side). However, the turtle is drawn one step behind its actual position, so that the display of the base of the turtle's triangle does not obscure a line drawn perpendicular to it (as would happen after drawing a square).

Colors are, of course, hardware-dependent. However, Logo provides partial hardware independence by interpreting color numbers 0 through 7 uniformly on all computers:

0 black	1 blue	2 green	3 cyan
4 red	5 magenta	6 yellow	7 white

Where possible, Logo provides additional user-settable colors; how many are available depends on the hardware and operating system environment. If at least 16 colors are available, Logo tries to provide uniform initial settings for the colors 8-15:

8 brown	9 tan	10 forest	11 aqua
12 salmon	13 purple	14 orange	15 grey

Logo begins with a black background and white pen.

6.1 Turtle Motion

forward

```
FORWARD dist
FD dist
```

moves the turtle forward, in the direction that it's facing, by the specified distance (measured in turtle steps).

back

```
BACK dist
BK dist
```

moves the turtle backward, i.e., exactly opposite to the direction that it's facing, by the specified distance. (The heading of the turtle does not change.)

left`LEFT degrees``LT degrees`

turns the turtle counterclockwise by the specified angle, measured in degrees (1/360 of a circle).

right`RIGHT degrees``RT degrees`

turns the turtle clockwise by the specified angle, measured in degrees (1/360 of a circle).

setpos`SETPOS pos`

moves the turtle to an absolute position in the graphics window. The input is a list of two numbers, the X and Y coordinates.

setxy`SETXY xcor ycor`

moves the turtle to an absolute position in the graphics window. The two inputs are numbers, the X and Y coordinates.

setx`SETX xcor`

moves the turtle horizontally from its old position to a new absolute horizontal coordinate. The input is the new X coordinate.

sety`SETY ycor`

moves the turtle vertically from its old position to a new absolute vertical coordinate. The input is the new Y coordinate.

setheading`SETHEADING degrees``SETH degrees`

turns the turtle to a new absolute heading. The input is a number, the heading in degrees clockwise from the positive Y axis.

home`HOME`

moves the turtle to the center of the screen. Equivalent to `SETPOS [0 0] SETHEADING 0`.

See [SETPOS], page 38 , See [SETHEADING], page 38 .

arc

ARC angle radius

draws an arc of a circle, with the turtle at the center, with the specified radius, starting at the turtle's heading and extending clockwise through the specified angle. The turtle does not move.

6.2 Turtle Motion Queries

pos

POS

outputs the turtle's current position, as a list of two numbers, the X and Y coordinates.

xcor

XCOR (library procedure)

outputs a number, the turtle's X coordinate.

ycor

YCOR (library procedure)

outputs a number, the turtle's Y coordinate.

heading

HEADING

outputs a number, the turtle's heading in degrees.

towards

TOWARDS pos

outputs a number, the heading at which the turtle should be facing so that it would point from its current position to the position given as the input.

scrunch

SCRUNCH

outputs a list containing two numbers, the X and Y scrunch factors, as used by **SETSCRUNCH**. (But note that **SETSCRUNCH** takes two numbers as inputs, not one list of numbers.)

See [SETSCRUNCH], page 42 .

6.3 Turtle and Window Control

showturtle

SHOWTURTLE

ST

makes the turtle visible.

hideturtle

HIDETURTLE
HT

makes the turtle invisible. It's a good idea to do this while you're in the middle of a complicated drawing, because hiding the turtle speeds up the drawing substantially.

clean

CLEAN

erases all lines that the turtle has drawn on the graphics window. The turtle's state (position, heading, pen mode, etc.) is not changed.

clearscreen

CLEARSCREEN
CS

erases the graphics window and sends the turtle to its initial position and heading. Like `HOME` and `CLEAN` together.

See [HOME], page 38 .

wrap

WRAP

tells the turtle to enter wrap mode: From now on, if the turtle is asked to move past the boundary of the graphics window, it will "wrap around" and reappear at the opposite edge of the window. The top edge wraps to the bottom edge, while the left edge wraps to the right edge. (So the window is topologically equivalent to a torus.) This is the turtle's initial mode. Compare `WINDOW` and `FENCE`.

See [FENCE], page 40 .

window

WINDOW

tells the turtle to enter window mode: From now on, if the turtle is asked to move past the boundary of the graphics window, it will move offscreen. The visible graphics window is considered as just part of an infinite graphics plane; the turtle can be anywhere on the plane. (If you lose the turtle, `HOME` will bring it back to the center of the window.) Compare `WRAP` and `FENCE`.

See [HOME], page 38 .

fence

FENCE

tells the turtle to enter fence mode: From now on, if the turtle is asked to move past the boundary of the graphics window, it will move as far as it can and then stop at the edge with an "out of bounds" error message. Compare `WRAP` and `WINDOW`.

See [WRAP], page 40 .

fill

FILL

fills in a region of the graphics window containing the turtle and bounded by lines that have been drawn earlier. This is not portable; it doesn't work for all machines, and may not work exactly the same way on different machines.

filled

FILLED color instructions

runs the instructions, remembering all points visited by turtle motion commands, starting *and ending* with the turtle's initial position. Then draws (ignoring penmode) the resulting polygon, in the current pen color, filling the polygon with the given color, which can be a color number or an RGB list. The instruction list cannot include another **FILLED** invocation. (wxWidgets only)

label

LABEL text

takes a word or list as input, and prints the input on the graphics window, starting at the turtle's position.

setlabelheight

SETLABELHEIGHT height

command (wxWidgets only). Takes a positive integer argument and tries to set the font size so that the character height (including descenders) is that many turtle steps. This will be different from the number of screen pixels if **SETSCRUNCH** has been used. Also, note that **SETSCRUNCH** changes the font size to try to preserve this height in turtle steps. Note that the query operation corresponding to this command is **LABELSIZE**, not **LABELHEIGHT**, because it tells you the width as well as the height of characters in the current font.

textscreen

TEXTSCREEN
TS

rearranges the size and position of windows to maximize the space available in the text window (the window used for interaction with Logo). The details differ among machines. Compare **SPLITSCREEN** and **FULLSCREEN**.

See [SPLITSCREEN], page 42 .

fullscreen

FULLSCREEN
FS

rearranges the size and position of windows to maximize the space available in the graphics window. The details differ among machines. Compare **SPLITSCREEN** and **TEXTSCREEN**.

Since there must be a text window to allow printing (including the printing of the Logo prompt), Logo automatically switches from fullscreen to splitscreen whenever anything is printed.

In the DOS version, switching from fullscreen to splitscreen loses the part of the picture that's hidden by the text window. [This design decision follows from the scarcity of memory, so that the extra memory to remember an invisible part of a drawing seems too expensive.]

splitscreen

```
SPLITSCREEN
SS
```

rearranges the size and position of windows to allow some room for text interaction while also keeping most of the graphics window visible. The details differ among machines. Compare **TEXTSCREEN** and **FULLSCREEN**.

See [TEXTSCREEN], page 41 .

setscrunch

```
SETSCRUNCH xscale yscale
```

adjusts the aspect ratio and scaling of the graphics display. After this command is used, all further turtle motion will be adjusted by multiplying the horizontal and vertical extent of the motion by the two numbers given as inputs. For example, after the instruction **SETSCRUNCH 2 1** motion at a heading of 45 degrees will move twice as far horizontally as vertically. If your squares don't come out square, try this. (Alternatively, you can deliberately misadjust the aspect ratio to draw an ellipse.)

For all modern computers, both scale factors are initially 1. For DOS machines, the scale factors are initially set according to what the hardware claims the aspect ratio is, but the hardware sometimes lies. For DOS, the values set by **SETSCRUNCH** are remembered in a file (called **scrunch.dat**) and are automatically put into effect when a Logo session begins.

refresh

```
REFRESH
```

(command) tells Logo to remember the turtle's motions so that they can be used for high-resolution printing (wxWidgets) or to refresh the graphics window if it is moved, resized, or overlaid (non-wxWidgets). This is the default.

norefresh

```
NOREFRESH
```

(command) tells Logo not to remember the turtle's motions, which may be useful to save time and memory if your program is interactive or animated, rather than drawing a static picture you'll want to print later (wxWidgets). In non-wxWidgets versions, using **NOREFRESH** may prevent Logo from restoring the graphics image after the window is moved, resized, or overlaid.

6.4 Turtle and Window Queries

shownp

SHOWNP
SHOWN?

outputs **TRUE** if the turtle is shown (visible), **FALSE** if the turtle is hidden. See **SHOWTURTLE** and **HIDETURTLE**.

See [SHOWTURTLE], page 39 , [HIDETURTLE], page 40 .

screenmode

SCREENMODE

outputs the word **TEXTSCREEN**, **SPLITSCREEN**, or **FULLSCREEN** depending on the current screen mode.

turtlemode

TURTLEMODE

outputs the word **WRAP**, **FENCE**, or **WINDOW** depending on the current turtle mode.

labelsize

LABELSIZE

(wxWidgets only) outputs a list of two positive integers, the width and height of characters displayed by **LABEL** measured in turtle steps (which will be different from screen pixels if **SETSCRUNCH** has been used). There is no **SETLABELSIZE** because the width and height of a font are not separately controllable, so the inverse of this operation is **SETLABELHEIGHT**, which takes just one number for the desired height.

6.5 Pen and Background Control

The turtle carries a pen that can draw pictures. At any time the pen can be **UP** (in which case moving the turtle does not change what's on the graphics screen) or **DOWN** (in which case the turtle leaves a trace). If the pen is down, it can operate in one of three modes: **PAINT** (so that it draws lines when the turtle moves), **ERASE** (so that it erases any lines that might have been drawn on or through that path earlier), or **REVERSE** (so that it inverts the status of each point along the turtle's path).

pendown

PENDOWN
PD

sets the pen's position to **DOWN**, without changing its mode.

penup

PENUP
PU

sets the pen's position to **UP**, without changing its mode.

penpaint

PENPAINT
PPT

sets the pen's position to DOWN and mode to PAINT.

penerase

PENERASE
PE

sets the pen's position to DOWN and mode to ERASE.

See [ERASE], page 57 .

penreverse

PENREVERSE
PX

sets the pen's position to DOWN and mode to REVERSE. (This may interact in system-dependent ways with use of color.)

See [REVERSE], page 10 .

setpencolor

SETPENCOLOR colornumber.or.rgblist
SETPC colornumber.or.rgblist

sets the pen color to the given number, which must be a nonnegative integer. There are initial assignments for the first 16 colors:

```
0 black 1 blue 2 green 3 cyan
4 red 5 magenta 6 yellow 7 white
8 brown 9 tan 10 forest 11 aqua
12 salmon 13 purple 14 orange 15 grey
```

but other colors can be assigned to numbers by the PALETTE command. Alternatively, sets the pen color to the given RGB values (a list of three nonnegative numbers less than 100 specifying the percent saturation of red, green, and blue in the desired color).

setpalette

SETPALETTE colornumber rgblist

sets the actual color corresponding to a given number, if allowed by the hardware and operating system. Colornumber must be an integer greater than or equal to 8. (Logo tries to keep the first 8 colors constant.) The second input is a list of three nonnegative numbers less than 100 specifying the percent saturation of red, green, and blue in the desired color.

setpensize

SETPENSIZ size

sets the thickness of the pen. The input is either a single positive integer or a list of two positive integers (for horizontal and vertical thickness). Some versions pay no attention to the second number, but always have a square pen.

setpenpattern

`SETPENPATTERN pattern`

sets hardware-dependent pen characteristics. This command is not guaranteed compatible between implementations on different machines.

setpen

`SETPEN list (library procedure)`

sets the pen's position, mode, thickness, and hardware-dependent characteristics according to the information in the input list, which should be taken from an earlier invocation of `PEN`.

See `[PEN]`, page 46 .

setbackground

`SETBACKGROUND colornumber.or.rgblist`

`SETBG colornumber.or.rgblist`

set the screen background color by slot number or RGB values. See `SETPENCOLOR` for details.

See `[SETPENCOLOR]`, page 44 .

6.6 Pen Queries

pendownp

`PENDOWNP`

`PENDOWN?`

outputs `TRUE` if the pen is down, `FALSE` if it's up.

penmode

`PENMODE`

outputs one of the words `PAINT`, `ERASE`, or `REVERSE` according to the current pen mode.

See `[ERASE]`, page 57 , `[REVERSE]`, page 10 .

pencolor

`PENCOLOR`

`PC`

outputs a color number, a nonnegative integer that is associated with a particular color, or a list of RGB values if such a list was used as the most recent input to `SETPENCOLOR`. There are initial assignments for the first 16 colors:

0	black	1	blue	2	green	3	cyan
---	-------	---	------	---	-------	---	------

4	red	5	magenta	6	yellow	7	white
8	brown	9	tan	10	forest	11	aqua
12	salmon	13	purple	14	orange	15	grey

but other colors can be assigned to numbers by the **PALETTE** command.

palette

PALETTE colornumber

outputs a list of three nonnegative numbers less than 100 specifying the percent saturation of red, green, and blue in the color associated with the given number.

pensize

PENSIZ

outputs a list of two positive integers, specifying the horizontal and vertical thickness of the turtle pen. (In some implementations, including wxWidgets, the two numbers are always equal.)

PENPATTERN

outputs system-specific pen information.

pen

PEN (library procedure)

outputs a list containing the pen's position, mode, thickness, and hardware-specific characteristics, for use by **SETPEN**.

See [SETPEN], page 45 .

background

BACKGROUND

BG

outputs the graphics background color, either as a slot number or as an RGB list, whichever way it was set. (See **PENCOLOR**.)

6.7 Saving and Loading Pictures

savepict

SAVEPICT filename

command. Writes a file with the specified name containing the state of the graphics window, including any nonstandard color palette settings, in Logo's internal format. This picture can be restored to the screen using **LOADPICT**. The format is not portable between platforms, nor is it readable by other programs. [EPSPICT], page 47 to export Logo graphics for other programs.

loadpict

LOADPICT filename

command. Reads the specified file, which must have been written by a **SAVEPICT** command, and restores the graphics window and color palette settings to the values stored in the file. Any drawing previously on the screen is cleared.

See [SAVEPICT], page 46 .

eps pict

EPSPICT filename

command. Writes a file with the specified name, containing an Encapsulated Postscript (EPS) representation of the state of the graphics window. This file can be imported into other programs that understand EPS format. Restrictions: the drawing cannot use **FILL**, **PENERASE**, or **PENREVERSE**; any such instructions will be ignored in the translation to Postscript form.

See [FILL], page 41 , See [PENERASE], page 44 , See [PENREVERSE], page 44 .

6.8 Mouse Queries

mousepos

MOUSEPOS

outputs the coordinates of the mouse, provided that it's within the graphics window, in turtle coordinates. If the mouse is outside the graphics window, then the last position within the window is returned. Exception: If a mouse button is pressed within the graphics window and held while the mouse is dragged outside the window, the mouse's position is returned as if the window were big enough to include it.

clickpos

CLICKPOS

outputs the coordinates that the mouse was at when a mouse button was most recently pushed, provided that that position was within the graphics window, in turtle coordinates. (wxWidgets only)

buttonp

BUTTONP
BUTTON?

outputs **TRUE** if a mouse button is down and the mouse is over the graphics window. Once the button is down, **BUTTONP** remains true until the button is released, even if the mouse is dragged out of the graphics window.

button

BUTTON

outputs 0 if no mouse button has been pushed inside the Logo window since the last call to **BUTTON**. Otherwise, it outputs an integer between 1 and 3 indicating which button was most recently pressed. Ordinarily 1 means left, 2 means right, and 3 means center, but operating systems may reconfigure these.

7 Workspace Management

7.1 Procedure Definition

to

```
TO procname :input1 :input2 ... (special form)
```

command. Prepares Logo to accept a procedure definition. The procedure will be named *procname* and there must not already be a procedure by that name. The inputs will be called *input1* etc. Any number of inputs are allowed, including none. Names of procedures and inputs are case-insensitive.

Unlike every other Logo procedure, TO takes as its inputs the actual words typed in the instruction line, as if they were all quoted, rather than the results of evaluating expressions to provide the inputs. (That's what *special form* means.)

This version of Logo allows variable numbers of inputs to a procedure. After the procedure name come four kinds of things, *in this order*:

1. 0 or more REQUIRED inputs :FOO :FROBOZZ
2. 0 or more OPTIONAL inputs [:BAZ 87] [:THINGO 5+9]
3. 0 or 1 REST input [:GARPLY]
4. 0 or 1 DEFAULT number 5

Every procedure has a *minimum*, *default*, and *maximum* number of inputs. (The latter can be infinite.)

The *minimum* number of inputs is the number of required inputs, which must come first. A required input is indicated by the

```
:inputname
```

notation.

After all the required inputs can be zero or more optional inputs, each of which is represented by the following notation:

```
[:inputname default.value.expression]
```

When the procedure is invoked, if actual inputs are not supplied for these optional inputs, the *default value expressions* are evaluated to set values for the corresponding input names. The inputs are processed from left to right, so a default value expression can be based on earlier inputs. Example:

```
to proc :inlist [:startvalue first :inlist]
```

If the procedure is invoked by saying

```
proc [a b c]
```

then the variable *inlist* will have the value [A B C] and the variable *startvalue* will have the value A. If the procedure is invoked by saying

```
(proc [a b c] "x)
```

then `inlist` will have the value `[A B C]` and `startvalue` will have the value `X`.

After all the required and optional input can come a single *rest* input, represented by the following notation:

```
[:inputname]
```

This is a rest input rather than an optional input because there is no default value expression. There can be at most one rest input. When the procedure is invoked, the value of this *inputname* will be a list containing all of the actual inputs provided that were not used for required or optional inputs. Example:

```
to proc :in1 [:in2 "foo] [:in3 "baz] [:in4]
```

If this procedure is invoked by saying

```
proc "x
```

then `in1` has the value `X`, `in2` has the value `FOO`, `in3` has the value `BAZ`, and `in4` has the value `[]` (the empty list). If it's invoked by saying

```
(proc "a "b "c "d "e)
```

then `in1` has the value `A`, `in2` has the value `B`, `in3` has the value `C`, and `in4` has the value `[D E]`.

The *maximum* number of inputs for a procedure is infinite if a rest input is given; otherwise, it is the number of required inputs plus the number of optional inputs.

The *default* number of inputs for a procedure, which is the number of inputs that it will accept if its invocation is not enclosed in parentheses, is ordinarily equal to the minimum number. If you want a different default number you can indicate that by putting the desired default number as the last thing on the `T0` line. example:

```
to proc :in1 [:in2 "foo] [:in3] 3
```

This procedure has a minimum of one input, a default of three inputs, and an infinite maximum.

Logo responds to the `T0` command by entering procedure definition mode. The prompt character changes from `?` to `>` and whatever instructions you type become part of the definition until you type a line containing only the word `END`.

define

```
DEFINE procname text
```

command. Defines a procedure with name *procname* and text *text*. If there is already a procedure with the same name, the new definition replaces the old one. The *text* input must be a list whose members are lists. The first member is a list of inputs; it looks like a `T0` line but without the word `T0`, without the procedure name, and without the colons before input names. In other words, the members of this first sublist are words for the names of required inputs and lists for the names of optional or rest inputs. The remaining sublists of the *text* input make up the body of the procedure, with one sublist for each instruction line

of the body. (There is no **END** line in the text input.) It is an error to redefine a primitive procedure unless the variable **REDEFP** has the value **TRUE**.

See [REDEFP], page 91 .

text

TEXT *procname*

outputs the text of the procedure named *procname* in the form expected by **DEFINE**: a list of lists, the first of which describes the inputs to the procedure and the rest of which are the lines of its body. The text does not reflect formatting information used when the procedure was defined, such as continuation lines and extra spaces.

fulltext

FULLTEXT *procname*

outputs a representation of the procedure *procname* in which formatting information is preserved. If the procedure was defined with **T0**, **EDIT**, or **LOAD**, then the output is a list of words. Each word represents one entire line of the definition in the form output by **READWORD**, including extra spaces and continuation lines. The last member of the output represents the **END** line. If the procedure was defined with **DEFINE**, then the output is a list of lists. If these lists are printed, one per line, the result will look like a definition using **T0**. Note: the output from **FULLTEXT** is not suitable for use as input to **DEFINE**!

See [T0], page 49 , [EDIT], page 61 , [LOAD], page 63 , [DEFINE], page 50 .

copydef

COPYDEF *newname oldname*

command. Makes *newname* a procedure identical to *oldname*. The latter may be a primitive. If *newname* was already defined, its previous definition is lost. If *newname* was already a primitive, the redefinition is not permitted unless the variable **REDEFP** has the value **TRUE**.

Note: dialects of Logo differ as to the order of inputs to **COPYDEF**. This dialect uses "MAKE order," not "NAME order."

See [REDEFP], page 91 , [SAVE], page 62 , [PO], page 56 , [POT], page 57 .

7.2 Variable Definition

make

MAKE *varname value*

command. Assigns the value *value* to the variable named *varname*, which must be a word. Variable names are case-insensitive. If a variable with the same name already exists, the value of that variable is changed. If not, a new global variable is created.

name

NAME *value varname (library procedure)*

command. Same as **MAKE** but with the inputs in reverse order.

local

```

LOCAL varname
LOCAL varnamelist
(LOCAL varname1 varname2 ...)

```

command. Accepts as inputs one or more words, or a list of words. A variable is created for each of these words, with that word as its name. The variables are local to the currently running procedure. Logo variables follow dynamic scope rules; a variable that is local to a procedure is available to any subprocedure invoked by that procedure. The variables created by **LOCAL** have no initial value; they must be assigned a value (e.g., with **MAKE**) before the procedure attempts to read their value.

See [MAKE], page 51 .

localmake

```

LOCALMAKE varname value (library procedure)

```

command. Makes the named variable local, like **LOCAL**, and assigns it the given value, like **MAKE**.

See [LOCAL], page 52 , See [MAKE], page 51 .

thing

```

THING varname
:quoted.varname

```

outputs the value of the variable whose name is the input. If there is more than one such variable, the innermost local variable of that name is chosen. The colon notation is an abbreviation not for **THING** but for the combination

```

thing "

```

so that **:FOO** means **THING "FOO**.

global

```

GLOBAL varname
GLOBAL varnamelist
(GLOBAL varname1 varname2 ...)

```

command. Accepts as inputs one or more words, or a list of words. A global variable is created for each of these words, with that word as its name. The only reason this is necessary is that you might want to use the "setter" notation **SETXYZ** for a variable **XYZ** that does not already have a value; **GLOBAL "XYZ** makes that legal. Note: If there is currently a local variable of the same name, this command does **not** make Logo use the global value instead of the local one.

7.3 Property Lists

Note: Names of property lists are always case-insensitive. Names of individual properties are case-sensitive or case-insensitive depending on the value of `CASEIGNOREDP`, which is `TRUE` by default.

See [CASEIGNOREDP], page 89 .

In principle, every possible name is the name of a property list, which is initially empty. So Logo never gives a "no such property list" error, as it would for undefined procedure or variable names. But the primitive procedures that deal with "all" property lists (`CONTENTS`, `PLISTS`, etc.) list only nonempty ones. To "erase" a property list [ERASE], page 57 means to make it empty, removing all properties from it.

pprop

`PPROP plistname propname value`

command. Adds a property to the *plistname* property list with name *propname* and value *value*.

gprop

`GPROP plistname propname`

outputs the value of the *propname* property in the *plistname* property list, or the empty list if there is no such property.

remprop

`REMPROP plistname propname`

command. Removes the property named *propname* from the property list named *plistname*.

plist

`PLIST plistname`

outputs a list whose odd-numbered members are the names, and whose even-numbered members are the values, of the properties in the property list named *plistname*. The output is a copy of the actual property list; changing properties later will not magically change a list output earlier by `PLIST`.

7.4 Workspace Predicates

procedurep

`PROCEDUREP name`

`PROCEDURE? name`

outputs `TRUE` if the input is the name of a procedure.

primitivep

`PRIMITIVEP name`

`PRIMITIVE? name`

outputs **TRUE** if the input is the name of a primitive procedure (one built into Logo). Note that some of the procedures described in this document are library procedures, not primitives.

definedp

DEFINEDP *name*
DEFINED? *name*

outputs **TRUE** if the input is the name of a user-defined procedure, including a library procedure.

namep

NAMEP *name*
NAME? *name*

outputs **TRUE** if the input is the name of a variable.

plistp

PLISTP *name*
PLIST? *name*

outputs **TRUE** if the input is the name of a *nonempty* property list. (In principle every word is the name of a property list; if you haven't put any properties in it, **PLIST** of that name outputs an empty list, rather than giving an error message.)

7.5 Workspace Queries

Note: All procedures whose input is indicated as *contentslist* will accept a single word (taken as a procedure name), a list of words (taken as names of procedures), or a list of three lists as described under the **CONTENTS** command above.

contents

CONTENTS

outputs a "contents list," i.e., a list of three lists containing names of defined procedures, variables, and property lists respectively. This list includes all unburied named items in the workspace.

buried

BURIED

outputs a contents list including all buried named items in the workspace.

traced

TRACED

outputs a contents list including all traced named items in the workspace.

stepped

STEPPED

outputs a contents list including all stepped named items in the workspace.

procedures

`PROCEDURES`

outputs a list of the names of all unburied user-defined procedures in the workspace. Note that this is a list of names, not a contents list. (However, procedures that require a contents list as input will accept this list.)

primitives

`PRIMITIVES`

outputs a list of the names of all primitive procedures in the workspace. Note that this is a list of names, not a contents list. (However, procedures that require a contents list as input will accept this list.)

names

`NAMES`

outputs a contents list consisting of an empty list (indicating no procedure names) followed by a list of all unburied variable names in the workspace.

plists

`PLISTS`

outputs a contents list consisting of two empty lists (indicating no procedures or variables) followed by a list of all unburied nonempty property lists in the workspace.

namelist

`NAMELIST varname (library procedure)`
`NAMELIST varnamelist`

outputs a contents list consisting of an empty list followed by a list of the name or names given as input. This is useful in conjunction with workspace control procedures that require a contents list as input.

pplist

`PLLIST pname (library procedure)`
`PLLIST pnamelist`

outputs a contents list consisting of two empty lists followed by a list of the name or names given as input. This is useful in conjunction with workspace control procedures that require a contents list as input.

See [CONTENTS], page 54 .

arity

`ARITY procedurename`

outputs a list of three numbers: the minimum, default, and maximum number of inputs for the procedure whose name is the input. It is an error if there is no such procedure. A maximum of -1 means that the number of inputs is unlimited.

nodes

NODES

outputs a list of two numbers. The first represents the number of nodes of memory currently in use. The second shows the maximum number of nodes that have been in use at any time since the last invocation of **NODES**. (A node is a small block of computer memory as used by Logo. Each number uses one node. Each non-numeric word uses one node, plus some non-node memory for the characters in the word. Each array takes one node, plus some non-node memory, as well as the memory required by its elements. Each list requires one node per element, as well as the memory within the elements.) If you want to track the memory use of an algorithm, it is best if you invoke **GC** at the beginning of each iteration, since otherwise the maximum will include storage that is unused but not yet collected.

7.6 Workspace Inspection

po

```
PRINTOUT contentslist
PO contentslist
```

command. Prints to the write stream the definitions of all procedures, variables, and property lists named in the input contents list.

poall

```
POALL (library procedure)
```

command. Prints all unburied definitions in the workspace. Abbreviates **PO CONTENTS**.

See [CONTENTS], page 54 .

pops

```
POPS (library procedure)
```

command. Prints the definitions of all unburied procedures in the workspace. Abbreviates **PO PROCEDURES**.

See [PO], page 56 , [PROCEDURES], page 55 .

pons

```
PONS (library procedure)
```

command. Prints the definitions of all unburied variables in the workspace. Abbreviates **PO NAMES**.

See [PO], page 56 , [NAMES], page 55 .

popls

`POPLS (library procedure)`

command. Prints the contents of all unburied nonempty property lists in the workspace. Abbreviates `P0 PLISTS`.

See [PO], page 56 , [PLISTS], page 55 .

pon

`PON varname (library procedure)`

`PON varnamelist`

command. Prints the definitions of the named variable(s). Abbreviates `P0 NAMELIST varname(list)`.

See [PO], page 56 , [NAMELIST], page 55 .

popl

`POPL pname (library procedure)`

`POPL pnamelist`

command. Prints the definitions of the named property list(s). Abbreviates `P0 PLLIST pname(list)`.

See [PO], page 56 , [PLLIST], page 55 .

pot

`POT contentslist`

command. Prints the title lines of the named procedures and the definitions of the named variables and property lists. For property lists, the entire list is shown on one line instead of as a series of `PPROP` instructions as in `P0`.

See [PPROP], page 53 , [PO], page 56 .

pots

`POTS (library procedure)`

command. Prints the title lines of all unburied procedures in the workspace. Abbreviates `POT PROCEDURES`.

See [PROCEDURES], page 55 .

7.7 Workspace Control

erase

`ERASE contentslist`

`ER contentslist`

command. Erases from the workspace the procedures, variables, and property lists named in the input. Primitive procedures may not be erased unless the variable REDEFP has the value TRUE.

See [REDEFP], page 91 .

erall

ERALL

command. Erases all unburied procedures, variables, and property lists from the workspace. Abbreviates ERASE CONTENTS.

See [CONTENTS], page 54 .

erps

ERPS

command. Erases all unburied procedures from the workspace. Abbreviates ERASE PROCEDURES.

See [ERASE], page 57 , [PROCEDURES], page 55 .

erns

ERNS

command. Erases all unburied variables from the workspace. Abbreviates ERASE NAMES.

See [ERASE], page 57 , [NAMES], page 55 .

erpls

ERPLS

command. Erases all unburied property lists from the workspace. Abbreviates ERASE PLISTS.

See [ERASE], page 57 , [PLISTS], page 55 .

ern

ERN *varname* (library procedure)
ERN *varnamelist*

command. Erases from the workspace the variable(s) named in the input. Abbreviates ERASE NAMELIST *varname(list)*.

See [ERASE], page 57 , [NAMELIST], page 55 .

erpl

ERPL *pname* (library procedure)
ERPL *plnamelist*

command. Erases from the workspace the property list(s) named in the input. Abbreviates ERASE PLLIST *pname(list)*.

See [ERASE], page 57 , [PLLIST], page 55 .

bury

`BURY contentslist`

command. Buries the procedures, variables, and property lists named in the input. A buried item is not included in the lists output by `CONTENTS`, `PROCEDURES`, `VARIABLES`, and `PLISTS`, but is included in the list output by `BURIED`. By implication, buried things are not printed by `POALL` or saved by `SAVE`.

See [CONTENTS], page 54 , [PROCEDURES], page 55 , [PONS], page 56 , [PLISTS], page 55 , [POALL], page 56 , [SAVE], page 62 .

buryall

`BURYALL`

(library procedure)

command. Abbreviates `BURY CONTENTS`.

See [CONTENTS], page 54 .

buryname

`BURYNAMENAME varname (library procedure)`

`BURYNAMENAME varnamelist`

command. Abbreviates `BURY NAMELIST varname(list)`.

See [BURY], page 59 , [NAMELIST], page 55 .

unbury

`UNBURY contentslist`

command. Unburies the procedures, variables, and property lists named in the input. That is, the named items will be returned to view in `CONTENTS`, etc.

See [CONTENTS], page 54 .

unburyall

`UNBURYALL (library procedure)`

command. Abbreviates `UNBURY BURIED`.

See [BURIED], page 54 .

unburyname

`UNBURYNAME varname (library procedure)`

`UNBURYNAME varnamelist`

command. Abbreviates `UNBURY NAMELIST varname(list)`.

See [UNBURY], page 59 , [NAMELIST], page 55 .

buriedp

```
BURIEDP contentslist
BURIED? contentslist
```

outputs TRUE if the first procedure, variable, or property list named in the contents list is buried, FALSE if not. Only the first thing in the list is tested; the most common use will be with a word as input, naming a procedure, but a contents list is allowed so that you can BURIEDP [[] [variable]] or BURIEDP [[] [] [proplist]].

trace

```
TRACE contentslist
```

command. Marks the named items for tracing. A message is printed whenever a traced procedure is invoked, giving the actual input values, and whenever a traced procedure **STOPS** or **OUTPUTS**. A message is printed whenever a new value is assigned to a traced variable using **MAKE**. A message is printed whenever a new property is given to a traced property list using **PPROP**.

See [STOP], page 69 , [OUTPUT], page 69 , [MAKE], page 51 , [PPROP], page 53 .

untrace

```
UNTRACE contentslist
```

command. Turns off tracing for the named items.

tracedp

```
TRACEDP contentslist
TRACED? contentslist
```

outputs TRUE if the first procedure, variable, or property list named in the contents list is traced, FALSE if not. Only the first thing in the list is tested; the most common use will be with a word as input, naming a procedure, but a contents list is allowed so that you can TRACEDP [[] [variable]] or TRACEDP [[] [] [proplist]].

step

```
STEP contentslist
```

command. Marks the named items for stepping. Whenever a stepped procedure is invoked, each instruction line in the procedure body is printed before being executed, and Logo waits for the user to type a newline at the terminal. A message is printed whenever a stepped variable name is *shadowed* because a local variable of the same name is created either as a procedure input or by the **LOCAL** command.

See [LOCAL], page 52 .

unstep

```
UNSTEP contentslist
```

command. Turns off stepping for the named items.

steppedp

```

STEPPEDP contentslist
STEPPED? contentslist

```

outputs **TRUE** if the first procedure, variable, or property list named in the contents list is stepped, **FALSE** if not. Only the first thing in the list is tested; the most common use will be with a word as input, naming a procedure, but a contents list is allowed so that you can **STEPPEDP** `[] [variable]` or **STEPPEDP** `[] [] [proplist]`.

edit

```

EDIT contentslist
ED contentslist
(EDIT)
(ED)

```

command. If invoked with an input, **EDIT** writes the definitions of the named items into a temporary file and edits that file, using an editor that depends on the platform you're using. In wxWidgets, and in the MacOS Classic version, there is an editor built into Logo. In the non-wxWidgets versions for Unix, MacOS X, Windows, and DOS, Logo uses your favorite editor as determined by the **EDITOR** environment variable. If you don't have an **EDITOR** variable, edits the definitions using **jove**. If invoked without an input, **EDIT** edits the same file left over from a previous **EDIT** or **EDITFILE** instruction. When you leave the editor, Logo reads the revised definitions and modifies the workspace accordingly. It is not an error if the input includes names for which there is no previous definition.

If there is a variable **LOADNOISILY** whose value is **TRUE**, then, after leaving the editor, **TO** commands in the temporary file print '*procname* defined' (where *procname* is the name of the procedure being defined); if **LOADNOISILY** is **FALSE** or undefined, **TO** commands in the file are carried out silently.

If there is an environment variable called **TEMP**, then Logo uses its value as the directory in which to write the temporary file used for editing.

Exceptionally, the **EDIT** command can be used without its default input and without parentheses provided that nothing follows it on the instruction line.

See [LOADNOISILY], page 90 , See [EDITFILE], page 61 .

editfile

```

EDITFILE filename

```

command. Starts the Logo editor, like **EDIT**, but instead of editing a temporary file it edits the file specified by the input. When you leave the editor, Logo reads the revised file, as for **EDIT**. **EDITFILE** also remembers the filename, so that a subsequent **EDIT** command with no input will re-edit the same file.

EDITFILE is intended as an alternative to **LOAD** and **SAVE**. You can maintain a workspace file yourself, controlling the order in which definitions appear, maintaining comments in the file, and so on.

In the wxWidgets version, `EDITFILE` asks whether or not you want to load the file into Logo when you finish editing. This allows you to use `EDITFILE` to edit data files without leaving Logo.

edall

`EDALL (library procedure)`

command. Abbreviates `EDIT CONTENTS`.

See [CONTENTS], page 54 .

edps

`EDPS (library procedure)`

command. Abbreviates `EDIT PROCEDURES`.

See [EDIT], page 61 , [PROCEDURES], page 55 .

edns

`EDNS (library procedure)`

command. Abbreviates `EDIT NAMES`.

See [EDIT], page 61 , [NAMES], page 55 .

edpls

`EDPLS (library procedure)`

command. Abbreviates `EDIT PLISTS`.

See [EDIT], page 61 , [PLISTS], page 55 .

edn

`EDN varname (library procedure)`

`EDN varnamelist`

command. Abbreviates `EDIT NAMELIST varname(list)`.

See [EDIT], page 61 , [NAMELIST], page 55 .

edpl

`EDPL pname (library procedure)`

`EDPL pnamelist`

command. Abbreviates `EDIT PLLIST pname(list)`.

See [EDIT], page 61 , [PLLIST], page 55 .

save

`SAVE filename`

command. Saves the definitions of all unburied procedures, variables, and nonempty property lists in the named file. Equivalent to

```

to save :filename
  local "oldwriter
  make "oldwriter writer
  openwrite :filename
  setwrite :filename
  poall
  setwrite :oldwriter
  close :filename
end

```

Exceptionally, **SAVE** can be used with no input and without parentheses if it is the last thing on the command line. In this case, the filename from the most recent **LOAD** or **SAVE** command will be used. (It is an error if there has been no previous **LOAD** or **SAVE**.)

savel

SAVEL contentslist filename (library procedure)

command. Saves the definitions of the procedures, variables, and property lists specified by *contentslist* to the file named *filename*.

load

LOAD filename

command. Reads instructions from the named file and executes them. The file can include procedure definitions with **TO**, and these are accepted even if a procedure by the same name already exists. If the file assigns a list value to a variable named **STARTUP**, then that list is run as an instructionlist after the file is loaded. If there is a variable **LOADNOISILY** whose value is **TRUE**, then **TO** commands in the file print '*procname defined*' (where *procname* is the name of the procedure being defined); if **LOADNOISILY** is **FALSE** or undefined, **TO** commands in the file are carried out silently.

See [STARTUP], page 91 , See [LOADNOISILY], page 90 .

csload

CSLOAD name

command. Loads the named file, like **LOAD**, but from the directory containing the Computer Science Logo Style programs instead of the current user's directory.

See [LOAD], page 63 .

help

HELP name
(HELP)

command. Prints information from the reference manual about the primitive procedure named by the input. With no input, lists all the primitives about which help is available. If there is an environment variable **LOGOHELP**, then its value is taken as the directory in which to look for help files, instead of the default help directory.

If **HELP** is called with the name of a defined procedure for which there is no help file, it will print the title line of the procedure followed by lines from the procedure body that start with semicolon, stopping when a non-semicolon line is seen.

Exceptionally, the **HELP** command can be used without its default input and without parentheses provided that nothing follows it on the instruction line.

seteditor

SETEDITOR path

command. Tells Logo to use the specified program as its editor instead of the default editor. The format of a path depends on your operating system.

setlibloc

SETLIBLOC path

command. Tells Logo to use the specified directory as its library instead of the default. (Note that many Logo "primitive" procedures are actually found in the library, so they may become unavailable if your new library does not include them!) The format of a path depends on your operating system.

setcsloc

SETCSLOC path

command. Tells Logo to use the specified directory for the **CSLSLOAD** command, instead of the default directory. The format of a path depends on your operating system.

See [CSLSLOAD], page 63 .

sethelploc

SETHelpLOC path

command. Tells Logo to look in the specified directory for the information provided by the **HELP** command, instead of the default directory. The format of a path depends on your operating system.

settemploc

SETTEMPLOC path

command. Tells Logo to write editor temporary files in the specified directory rather than in the default directory. You must have write permission for this directory. The format of a path depends on your operating system.

gc

GC
(GC anything)

command. Runs the garbage collector, reclaiming unused nodes. Logo does this when necessary anyway, but you may want to use this command to control exactly when Logo does it. In particular, the numbers output by the **NODES** operation will not be very meaningful

unless garbage has been collected. Another reason to use **GC** is that a garbage collection takes a noticeable fraction of a second, and you may want to schedule collections for times before or after some time-critical animation. If invoked with an argument (of any value), **GC** runs a full garbage collection, including GCTWA (Garbage Collect Truly Worthless Atoms, which means that it removes from Logo's memory words that used to be procedure or variable names but aren't any more); without an argument, **GC** does a generational garbage collection, which means that only recently created nodes are examined. (The latter is usually good enough.)

.setsegmentsize

.SETSEGMENTSIZE *num*

command. Sets the number of nodes that Logo allocates from the operating system at once to *num*, which must be a positive integer. The name is dotted because bad things will happen if you use a number that's too small or too large for your computer. The initial value is 16,000 for most systems, but is smaller for 68000-based Macs. Making it larger will speed up computations (by reducing the number of garbage collections) at the cost of allocating more memory than necessary.

8 Control Structures

8.1 Control

Note: in the following descriptions, an *instructionlist* can be a list or a word. In the latter case, the word is parsed into list form before it is run. Thus, `RUN READWORD` or `RUN READLIST` will work. The former is slightly preferable because it allows for a continued line (with `~`) that includes a comment (with `;`) on the first line.

A *tf* input must be the word `TRUE`, the word `FALSE`, or a list. If it's a list, then it must be a Logo expression, which will be evaluated to produce a value that must be `TRUE` or `FALSE`. The comparisons with `TRUE` and `FALSE` are always case-insensitive.

A runlist can consist of either a single expression (that produces a value) or zero or more instructions (that do something, rather than output a value), depending on the context:

```
PRINT IFELSE :X<0 ["NEGATIVE] ["POSITIVE] ; one value in each case
REPEAT 4 [PRINT "A PRINT "B] ; two instructions
```

run

```
RUN instructionlist
```

command or operation. Runs the Logo instructions in the input list; outputs if the list contains an expression that outputs.

See `[READWORD]`, page 20 , `[READLIST]`, page 20 .

runresult

```
RUNRESULT instructionlist
```

runs the instructions in the input; outputs an empty list if those instructions produce no output, or a list whose only member is the output from running the input instructionlist. Useful for inventing command-or-operation control structures:

```
local "result
make "result runresult [something]
if empty? :result [stop]
output first :result
```

repeat

```
REPEAT num instructionlist
```

command. Runs the *instructionlist* repeatedly, *num* times.

forever

```
FOREVER instructionlist
```

command. Runs the "instructionlist" repeatedly, until something inside the instructionlist (such as `STOP` or `THROW`) makes it stop.

See `[STOP]`, page 69 , See `[THROW]`, page 69 .

repcount

REPCOUNT

outputs the repetition count of the innermost current REPEAT or FOREVER, starting from 1. If no REPEAT or FOREVER is active, outputs -1.

The abbreviation # can be used for REPCOUNT unless the REPEAT is inside the template input to a higher order procedure such as FOREACH, in which case # has a different meaning.

if

IF tf instructionlist
(IF tf instructionlist1 instructionlist2)

command. If the first input has the value TRUE, then IF runs the second input. If the first input has the value FALSE, then IF does nothing. (If given a third input, IF acts like IFELSE, as described below.) It is an error if the first input is not either TRUE or FALSE.

For compatibility with earlier versions of Logo, if an IF instruction is not enclosed in parentheses, but the first thing on the instruction line after the second input expression is a literal list (i.e., a list in square brackets), the IF is treated as if it were IFELSE, but a warning message is given. If this aberrant IF appears in a procedure body, the warning is given only the first time the procedure is invoked in each Logo session.

ifelse

IFELSE tf instructionlist1 instructionlist2

command or operation. If the first input has the value TRUE, then IFELSE runs the second input. If the first input has the value FALSE, then IFELSE runs the third input. IFELSE outputs a value if the *instructionlist* contains an expression that outputs a value.

test

TEST tf

command. Remembers its input, which must be TRUE or FALSE, for use by later IFTRUE or IFFALSE instructions. The effect of TEST is local to the procedure in which it is used; any corresponding IFTRUE or IFFALSE must be in the same procedure or a subprocedure.

See [IFFALSE], page 68 .

iftrue

IFTRUE instructionlist
IFT instructionlist

command. Runs its input if the most recent TEST instruction had a TRUE input. The TEST must have been in the same procedure or a superprocedure.

iffalse

IFFALSE instructionlist
IFF instructionlist

command. Runs its input if the most recent **TEST** instruction had a **FALSE** input. The **TEST** must have been in the same procedure or a superprocedure.

See [TEST], page 68 .

stop

STOP

command. Ends the running of the procedure in which it appears. Control is returned to the context in which that procedure was invoked. The stopped procedure does not output a value.

output

OUTPUT value

OP value

command. Ends the running of the procedure in which it appears. That procedure outputs the value *value* to the context in which it was invoked. Don't be confused: **OUTPUT** itself is a command, but the procedure that invokes **OUTPUT** is an operation.

catch

CATCH tag *instructionlist*

command or operation. Runs its second input. Outputs if that *instructionlist* outputs. If, while running the *instructionlist*, a **THROW** instruction is executed with a tag equal to the first input (case-insensitive comparison), then the running of the *instructionlist* is terminated immediately. In this case the **CATCH** outputs if a value input is given to **THROW**. The *tag* must be a word.

If the tag is the word **ERROR**, then any error condition that arises during the running of the *instructionlist* has the effect of **THROW "ERROR** instead of printing an error message and returning to toplevel. The **CATCH** does not output if an error is caught. Also, during the running of the *instructionlist*, the variable **ERRACT** is temporarily unbound. (If there is an error while **ERRACT** has a value, that value is taken as an *instructionlist* to be run after printing the error message. Typically the value of **ERRACT**, if any, is the list [PAUSE].)

See [ERROR], page 70 , [ERRACT], page 89 , [PAUSE], page 70 .

throw

THROW tag

(**THROW** tag value)

command. Must be used within the scope of a **CATCH** with an equal tag. Ends the running of the *instructionlist* of the **CATCH**. If **THROW** is used with only one input, the corresponding **CATCH** does not output a value. If **THROW** is used with two inputs, the second provides an output for the **CATCH**.

THROW "TOPLEVEL can be used to terminate all running procedures and interactive pauses, and return to the toplevel instruction prompt. Typing the system interrupt character

(**alt-S** for wxWidgets; otherwise normally **control-C** for Unix, **control-Q** for DOS, or **command-period** for Mac) has the same effect.

THROW "ERROR can be used to generate an error condition. If the error is not caught, it prints a message (**THROW "ERROR**) with the usual indication of where the error (in this case the **THROW**) occurred. If a second input is used along with a tag of **ERROR**, that second input is used as the text of the error message instead of the standard message. Also, in this case, the location indicated for the error will be, not the location of the **THROW**, but the location where the procedure containing the **THROW** was invoked. This allows user-defined procedures to generate error messages as if they were primitives. Note: in this case the corresponding **CATCH "ERROR**, if any, does not output, since the second input to **THROW** is not considered a return value.

THROW "SYSTEM immediately leaves Logo, returning to the operating system, without printing the usual parting message and without deleting any editor temporary file written by **EDIT**.

See [EDIT], page 61 .

error

ERROR

outputs a list describing the error just caught, if any. If there was not an error caught since the last use of **ERROR**, the empty list will be output. The error list contains four members: an integer code corresponding to the type of error, the text of the error message (as a single word including spaces), the name of the procedure in which the error occurred, and the instruction line on which the error occurred.

pause

PAUSE

command or operation. Enters an interactive pause. The user is prompted for instructions, as at toplevel, but with a prompt that includes the name of the procedure in which **PAUSE** was invoked. Local variables of that procedure are available during the pause. **PAUSE** outputs if the pause is ended by a **CONTINUE** with an input.

If the variable **ERRACT** exists, and an error condition occurs, the contents of that variable are run as an instructionlist. Typically **ERRACT** is given the value **[PAUSE]** so that an interactive pause will be entered in the event of an error. This allows the user to check values of local variables at the time of the error.

Typing the system quit character (**alt-S** for wxWidgets; otherwise normally **control-** for Unix, **control-W** for DOS, or **command-comma** for Mac) will also enter a pause.

See [ERRACT], page 89 .

continue

```
CONTINUE value
CO value
(CONTINUE)
```

(CO)

command. Ends the current interactive pause, returning to the context of the **PAUSE** invocation that began it. If **CONTINUE** is given an input, that value is used as the output from the **PAUSE**. If not, the **PAUSE** does not output.

Exceptionally, the **CONTINUE** command can be used without its default input and without parentheses provided that nothing follows it on the instruction line.

wait

WAIT *time*

command. Delays further execution for *time* 60ths of a second. Also causes any buffered characters destined for the terminal to be printed immediately. **WAIT 0** can be used to achieve this buffer flushing without actually waiting.

bye

BYE

command. Exits from Logo; returns to the operating system.

.maybeoutput

.MAYBEOUTPUT *value* (special form)

works like **OUTPUT** except that the expression that provides the input value might not, in fact, output a value, in which case the effect is like **STOP**. This is intended for use in control structure definitions, for cases in which you don't know whether or not some expression produces a value. Example:

```
to invoke :function [:inputs] 2
  .maybeoutput apply :function :inputs
end

? (invoke "print "a "b "c)
a b c
? print (invoke "word "a "b "c)
abc
```

This is an alternative to **RUNRESULT**. It's fast and easy to use, at the cost of being an exception to Logo's evaluation rules. (Ordinarily, it should be an error if the expression that's supposed to provide an input to something doesn't have a value.)

See [OUTPUT], page 69 , [STOP], page 69 , [RUNRESULT], page 67 .

goto

GOTO *word*

command. Looks for a **TAG** command with the same input in the same procedure, and continues running the procedure from the location of that **TAG**. It is meaningless to use **GOTO** outside of a procedure.

tag

TAG quoted.word

command. Does nothing. The input must be a literal word following a quotation mark ("), not the result of a computation. Tags are used by the **GOTO** command.

ignore

IGNORE value (library procedure)

command. Does nothing. Used when an expression is evaluated for a side effect and its actual value is unimportant.

,

, list (library procedure)

outputs a list equal to its input but with certain substitutions. If a member of the input list is the word **,** (comma) then the following member should be an instructionlist that produces an output when run. That output value replaces the comma and the instructionlist. If a member of the input list is the word **,@** (comma atsign) then the following member should be an instructionlist that outputs a list when run. The members of that list replace the **,@** and the instructionlist. Example:

```
show '[foo baz ,[bf [a b c]] garply ,@[bf [a b c]]]
```

will print

```
[foo baz [b c] garply b c]
```

A word starting with **,** or **,@** is treated as if the rest of the word were a one-word list, e.g., **,:foo** is equivalent to **,[:Foo]**.

A word starting with **",** (quote comma) or **:',** (colon comma) becomes a word starting with **"** or **:** but with the result of running the substitution (or its first word, if the result is a list) replacing what comes after the comma.

Backquotes can be nested. Substitution is done only for commas at the same depth as the backquote in which they are found:

```
? show '[a '[b ,[1+2] ,[foo ,[1+3] d] e] f]
[a ' [b , [1+2] , [foo 4 d] e] f]
```

```
?make "name1 "x
?make "name2 "y
? show '[a '[b ,:,:name1 ,",:name2 d] e]
[a ' [b , [:x] , ["y] d] e]
```

for

FOR forcontrol instructionlist (library procedure)

command. The first input must be a list containing three or four members: (1) a word, which will be used as the name of a local variable; (2) a word or list that will be evaluated as

by `RUN` to determine a number, the starting value of the variable; (3) a word or list that will be evaluated to determine a number, the limit value of the variable; (4) an optional word or list that will be evaluated to determine the step size. If the fourth member is missing, the step size will be 1 or -1 depending on whether the limit value is greater than or less than the starting value, respectively.

The second input is an *instructionlist*. The effect of `FOR` is to run that *instructionlist* repeatedly, assigning a new value to the control variable (the one named by the first member of the *forcontrol* list) each time. First the starting value is assigned to the control variable. Then the value is compared to the limit value. `FOR` is complete when the sign of (`current` - `limit`) is the same as the sign of the step size. (If no explicit step size is provided, the *instructionlist* is always run at least once. An explicit step size can lead to a zero-trip `FOR`, e.g., `FOR [I 1 0 1] ...`). Otherwise, the *instructionlist* is run, then the step is added to the current value of the control variable and `FOR` returns to the comparison step.

```
? for [i 2 7 1.5] [print :i]
2
3.5
5
6.5
?
```

See [RUN], page 67 .

do.while

`DO.WHILE instructionlist tfexpression (library procedure)`

command. Repeatedly evaluates the *instructionlist* as long as the evaluated *tfexpression* remains `TRUE`. Evaluates the first input first, so the *instructionlist* is always run at least once. The *tfexpression* must be an expressionlist whose value when evaluated is `TRUE` or `FALSE`.

while

`WHILE tfexpression instructionlist (library procedure)`

command. Repeatedly evaluates the *instructionlist* as long as the evaluated *tfexpression* remains `TRUE`. Evaluates the first input first, so the *instructionlist* may never be run at all. The *tfexpression* must be an expressionlist whose value when evaluated is `TRUE` or `FALSE`.

do.until

`DO.UNTIL instructionlist tfexpression (library procedure)`

command. Repeatedly evaluates the *instructionlist* as long as the evaluated *tfexpression* remains `FALSE`. Evaluates the first input first, so the *instructionlist* is always run at least once. The *tfexpression* must be an expressionlist whose value when evaluated is `TRUE` or `FALSE`.

until

`UNTIL tfexpression instructionlist (library procedure)`

command. Repeatedly evaluates the *instructionlist* as long as the evaluated *tfexpression* remains FALSE. Evaluates the first input first, so the *instructionlist* may never be run at all. The *tfexpression* must be an expressionlist whose value when evaluated is TRUE or FALSE.

case

CASE value clauses (library procedure)

command or operation. The second input is a list of lists (clauses); each clause is a list whose first element is either a list of values or the word ELSE and whose butfirst is a Logo expression or instruction. CASE examines the clauses in order. If a clause begins with the word ELSE (upper or lower case), then the butfirst of that clause is evaluated and CASE outputs its value, if any. If the first input to CASE is a member of the first element of a clause, then the butfirst of that clause is evaluated and CASE outputs its value, if any. If neither of these conditions is met, then CASE goes on to the next clause. If no clause is satisfied, CASE does nothing. Example:

```
to vowelp :letter
  output case :letter [ [[a e i o u] "true] [else "false] ]
end
```

cond

COND clauses (library procedure)

command or operation. The input is a list of lists (clauses); each clause is a list whose first element is either an expression whose value is TRUE or FALSE, or the word ELSE, and whose butfirst is a Logo expression or instruction. COND examines the clauses in order. If a clause begins with the word ELSE (upper or lower case), then the butfirst of that clause is evaluated and CASE outputs its value, if any. Otherwise, the first element of the clause is evaluated; the resulting value must be TRUE or FALSE. If it's TRUE, then the butfirst of that clause is evaluated and COND outputs its value, if any. If the value is FALSE, then COND goes on to the next clause. If no clause is satisfied, COND does nothing. Example:

```
to evens :numbers ; select even numbers from a list
  op cond [ [[empty? :numbers] []]
           [[evenp first :numbers] ; assuming EVENP is defined
            fput first :numbers evens butfirst :numbers]
           [else evens butfirst :numbers] ]
end
```

8.2 Template-based Iteration

The procedures in this section are iteration tools based on the idea of a *template*. This is a generalization of an instruction list or an expression list in which *slots* are provided for the tool to insert varying data. Four different forms of template can be used.

The most commonly used form for a template is 'explicit-slot' form, or 'question mark' form. Example:

```
? show map [? * ?] [2 3 4 5]
[4 9 16 25]
```

?

In this example, the MAP tool evaluated the template `[? * ?]` repeatedly, with each of the members of the data list `[2 3 4 5]` substituted in turn for the question marks. The same value was used for every question mark in a given evaluation. Some tools allow for more than one datum to be substituted in parallel; in these cases the slots are indicated by `?1` for the first datum, `?2` for the second, and so on:

```
? show (map [(word ?1 ?2 ?1)] [a b c] [d e f])
[ada beb cfc]
?
```

If the template wishes to compute the datum number, the form `(? 1)` is equivalent to `?1`, so `(? ?1)` means the datum whose number is given in datum number 1. Some tools allow additional slot designations, as shown in the individual descriptions.

The second form of template is the ‘**named-procedure**’ form. If the template is a word rather than a list, it is taken as the name of a procedure. That procedure must accept a number of inputs equal to the number of parallel data slots provided by the tool; the procedure is applied to all of the available data in order. That is, if data `?1` through `?3` are available, the template `"PROC` is equivalent to `[PROC ?1 ?2 ?3]`.

```
? show (map "word [a b c] [d e f])
[ad be cf]
?
```

```
to dotprod :a :b ; vector dot product
op apply "sum (map "product :a :b)
end
```

The third form of template is ‘**named-slot**’ or ‘**lambda**’ form. This form is indicated by a template list containing more than one member, whose first member is itself a list. The first member is taken as a list of names; local variables are created with those names and given the available data in order as their values. The number of names must equal the number of available data. This form is needed primarily when one iteration tool must be used within the template list of another, and the `?` notation would be ambiguous in the inner template. Example:

```
to matmul :m1 :m2 [:tm2 transpose :m2] ; multiply two matrices
output map [[row] map [[col] dotprod :row :col] :tm2] :m1
end
```

The fourth form is ‘**procedure text**’ form, a variant of lambda form. In this form, the template list contains at least two members, all of which are lists. This is the form used by the **DEFINE** and **TEXT** primitives, and **APPLY** accepts it so that the text of a defined procedure can be used as a template.

Note: The fourth form of template is interpreted differently from the others, in that Logo considers it to be an independent defined procedure for the purposes of **OUTPUT** and **STOP**. For example, the following two instructions are identical:


```
? print apply [[x] :x+3] [5]
8
? print apply [[x] [output :x+3]] [5]
8
```

although the first instruction is in named-slot form and the second is in procedure-text form. The named-slot form can be understood as telling Logo to evaluate the expression `:x+3` in place of the entire invocation of `apply`, with the variable `x` temporarily given the value 5. The procedure-text form can be understood as invoking the procedure

```
to foo :x
  output :x+3
end
```

with input 5, but without actually giving the procedure a name. If the use of `OUTPUT` were interchanged in these two examples, we'd get errors:

```
? print apply [[x] output :x+3] [5]
Can only use output inside a procedure
? print apply [[x] [:x+3]] [5]
You don't say what to do with 8
```

The named-slot form can be used with `STOP` or `OUTPUT` inside a procedure, to stop the enclosing procedure.

The following iteration tools are extended versions of the ones in Appendix B of the book *Computer Science Logo Style, Volume 3: Advanced Topics* by Brian Harvey [MIT Press, 1987]. The extensions are primarily to allow for variable numbers of inputs.

apply

APPLY *template* *inputlist*

command or operation. Runs the *template*, filling its slots with the members of *inputlist*. The number of members in *inputlist* must be an acceptable number of slots for *template*. It is illegal to apply the primitive `T0` as a template, but anything else is okay. **APPLY** outputs what *template* outputs, if anything.

See [TO], page 49 .

invoke

INVOKE *template* *input* (*library procedure*)
 (**INVOKE** *template* *input1* *input2* ...)

command or operation. Exactly like **APPLY** except that the inputs are provided as separate expressions rather than in a list.

foreach

FOREACH *data* *template* (*library procedure*)
 (**FOREACH** *data1* *data2* ... *template*)

command. Evaluates the *template* list repeatedly, once for each member of the *data* list. If more than one *data* list are given, each of them must be the same length. (The *data* inputs can be words, in which case the template is evaluated once for each character.)

In a template, the symbol `?REST` represents the portion of the *data* input to the right of the member currently being used as the `?` slot-filler. That is, if the *data* input is `[A B C D E]` and the template is being evaluated with `?` replaced by `B`, then `?REST` would be replaced by `[C D E]`. If multiple parallel slots are used, then `(?REST 1)` goes with `?1`, etc.

In a template, the symbol `#` represents the position in the *data* input of the member currently being used as the `?` slot-filler. That is, if the *data* input is `[A B C D E]` and the template is being evaluated with `?` replaced by `B`, then `#` would be replaced by `2`.

map

```
MAP template data (library procedure)
(MAP template data1 data2 ...)
```

outputs a word or list, depending on the type of the *data* input, of the same length as that *data* input. (If more than one *data* input are given, the output is of the same type as *data1*.) Each member of the output is the result of evaluating the *template* list, filling the slots with the corresponding member(s) of the *data* input(s). (All *data* inputs must be the same length.) In the case of a word output, the results of the template evaluation must be words, and they are concatenated with `WORD`.

In a template, the symbol `?REST` represents the portion of the *data* input to the right of the member currently being used as the `?` slot-filler. That is, if the *data* input is `[A B C D E]` and the *template* is being evaluated with `?` replaced by `B`, then `?REST` would be replaced by `[C D E]`. If multiple parallel slots are used, then `(?REST 1)` goes with `?1`, etc.

In a template, the symbol `#` represents the position in the *data* input of the member currently being used as the `?` slot-filler. That is, if the *data* input is `[A B C D E]` and the template is being evaluated with `?` replaced by `B`, then `#` would be replaced by `2`.

See [WORD], page 9 .

map.se

```
MAP.SE template data (library procedure)
(MAP.SE template data1 data2 ...)
```

outputs a list formed by evaluating the *template* list repeatedly and concatenating the results using `SENTENCE`. That is, the members of the output are the members of the results of the evaluations. The output list might, therefore, be of a different length from that of the *data* input(s). (If the result of an evaluation is the empty list, it contributes nothing to the final output.) The *data* inputs may be words or lists.

In a template, the symbol `?REST` represents the portion of the *data* input to the right of the member currently being used as the `?` slot-filler. That is, if the *data* input is `[A B C D E]` and the template is being evaluated with `?` replaced by `B`, then `?REST` would be replaced by `[C D E]`. If multiple parallel slots are used, then `(?REST 1)` goes with `?1`, etc.

In a template, the symbol # represents the position in the *data* input of the member currently being used as the ? slot-filler. That is, if the data input is [A B C D E] and the template is being evaluated with ? replaced by B, then # would be replaced by 2.

See [SENTENCE], page 9 .

filter

`FILTER tftemplate data (library procedure)`

outputs a word or list, depending on the type of the *data* input, containing a subset of the members (for a list) or characters (for a word) of the input. The template is evaluated once for each member or character of the data, and it must produce a TRUE or FALSE value. If the value is TRUE, then the corresponding input constituent is included in the output.

```
? print filter "vowelp "elephant
eea
?
```

In a template, the symbol ?REST represents the portion of the *data* input to the right of the member currently being used as the ? slot-filler. That is, if the data input is [A B C D E] and the template is being evaluated with ? replaced by B, then ?REST would be replaced by [C D E].

In a template, the symbol # represents the position in the *data* input of the member currently being used as the ? slot-filler. That is, if the data input is [A B C D E] and the template is being evaluated with ? replaced by B, then # would be replaced by 2.

find

`FIND tftemplate data (library procedure)`

outputs the first constituent of the *data* input (the first member of a list, or the first character of a word) for which the value produced by evaluating the *template* with that constituent in its slot is TRUE. If there is no such constituent, the empty list is output.

In a template, the symbol ?REST represents the portion of the *data* input to the right of the member currently being used as the ? slot-filler. That is, if the data input is [A B C D E] and the template is being evaluated with ? replaced by B, then ?REST would be replaced by [C D E].

In a template, the symbol # represents the position in the *data* input of the member currently being used as the ? slot-filler. That is, if the data input is [A B C D E] and the template is being evaluated with ? replaced by B, then # would be replaced by 2.

reduce

`REDUCE template data (library procedure)`

outputs the result of applying the *template* to accumulate the members of the *data* input. The template must be a two-slot function. Typically it is an associative function name like SUM. If the *data* input has only one constituent (member in a list or character in a word), the output is that constituent. Otherwise, the template is first applied with ?1 filled with the next-to-last constituent and ?2 with the last constituent. Then, if there are more

constituents, the template is applied with ?1 filled with the next constituent to the left and ?2 with the result from the previous evaluation. This process continues until all constituents have been used. The data input may not be empty.

Note: If the template is, like SUM, the name of a procedure that is capable of accepting arbitrarily many inputs, it is more efficient to use APPLY instead of REDUCE. The latter is good for associative procedures that have been written to accept exactly two inputs:

```
to max :a :b
  output ifelse :a > :b [:a] [:b]
end

print reduce "max [...]
```

Alternatively, REDUCE can be used to write MAX as a procedure that accepts any number of inputs, as SUM does:

```
to max [:inputs] 2
  if empty? :inputs ~
    [(throw "error [not enough inputs to max])]
  output reduce [ifelse ?1 > ?2 [?1] [?2]] :inputs
end
```

See [SUM], page 29 , [APPLY], page 76 .

crossmap

```
CROSSMAP template listlist (library procedure)
(CROSSMAP template data1 data2 ...)
```

outputs a list containing the results of template evaluations. Each *data* list contributes to a slot in the template; the number of slots is equal to the number of *data* list inputs. As a special case, if only one *data* list input is given, that list is taken as a list of data lists, and each of its members contributes values to a slot. CROSSMAP differs from MAP in that instead of taking members from the data inputs in parallel, it takes all possible combinations of members of data inputs, which need not be the same length.

```
? show (crossmap [word ?1 ?2] [a b c] [1 2 3 4])
[a1 a2 a3 a4 b1 b2 b3 b4 c1 c2 c3 c4]
?
```

For compatibility with the version in the first edition of CSLS¹, CROSSMAP templates may use the notation :1 instead of ?1 to indicate slots.

See [MAP], page 77 .

cascade

```
CASCADE endtest template startvalue (library procedure)
(CASCADE endtest tmp1 sv1 tmp2 sv2 ...)
(CASCADE endtest tmp1 sv1 tmp2 sv2 ... finaltemplate)
```

¹ Computer Science Logo Style

outputs the result of applying a template (or several templates, as explained below) repeatedly, with a given value filling the slot the first time, and the result of each application filling the slot for the following application.

In the simplest case, **CASCADE** has three inputs. The second input is a one-slot expression template. That template is evaluated some number of times (perhaps zero). On the first evaluation, the slot is filled with the third input; on subsequent evaluations, the slot is filled with the result of the previous evaluation. The number of evaluations is determined by the first input. This can be either a nonnegative integer, in which case the template is evaluated that many times, or a predicate expression template, in which case it is evaluated (with the same slot filler that will be used for the evaluation of the second input) repeatedly, and the **CASCADE** evaluation continues as long as the predicate value is **FALSE**. (In other words, the predicate template indicates the condition for stopping.)

If the template is evaluated zero times, the output from **CASCADE** is the third (*startvalue*) input. Otherwise, the output is the value produced by the last template evaluation.

CASCADE templates may include the symbol **#** to represent the number of times the template has been evaluated. This slot is filled with 1 for the first evaluation, 2 for the second, and so on.

```
? show cascade 5 [lput # ?] []
[1 2 3 4 5]
? show cascade [vowelp first ?] [bf ?] "spring
ing
? show cascade 5 [# * ?] 1
120
?
```

Several cascaded results can be computed in parallel by providing additional template-startvalue pairs as inputs to **CASCADE**. In this case, all templates (including the endtest template, if used) are multi-slot, with the number of slots equal to the number of pairs of inputs. In each round of evaluations, ?2, for example, represents the result of evaluating the second template in the previous round. If the total number of inputs (including the first endtest input) is odd, then the output from **CASCADE** is the final value of the first template. If the total number of inputs is even, then the last input is a template that is evaluated once, after the end test is satisfied, to determine the output from **CASCADE**.

```
to fibonacci :n
output (cascade :n [?1 + ?2] 1 [?1] 0)
end

to piglatin :word
output (cascade [vowelp first ?] ~
               [word bf ? first ?] ~
               :word ~
               [word ? "ay])
end
```

cascade.2

`CASCADE.2 endtest temp1 startval1 temp2 startval2 (library procedure)`

outputs the result of invoking `CASCADE` with the same inputs. The only difference is that the default number of inputs is five instead of three.

transfer

`TRANSFER endtest template inbasket (library procedure)`

outputs the result of repeated evaluation of the *template*. The template is evaluated once for each member of the list *inbasket*. `TRANSFER` maintains an *outbasket* that is initially the empty list. After each evaluation of the template, the resulting value becomes the new outbasket.

In the template, the symbol `?IN` represents the current member from the inbasket; the symbol `?OUT` represents the entire current outbasket. Other slot symbols should not be used.

If the first (*endtest*) input is an empty list, evaluation continues until all inbasket members have been used. If not, the first input must be a predicate expression template, and evaluation continues until either that template's value is `TRUE` or the inbasket is used up.

9 Macros

`.macro`

```
.MACRO procname :input1 :input2 ... (special form)
.DEFMACRO procname text
```

A macro is a special kind of procedure whose output is evaluated as Logo instructions in the context of the macro's caller. `.MACRO` is exactly like `TO` except that the new procedure becomes a macro; `.DEFMACRO` is exactly like `DEFINE` with the same exception.

Macros are useful for inventing new control structures comparable to `REPEAT`, `IF`, and so on. Such control structures can almost, but not quite, be duplicated by ordinary Logo procedures. For example, here is an ordinary procedure version of `REPEAT`:

```
to my.repeat :num :instructions
  if :num=0 [stop]
  run :instructions
  my.repeat :num-1 :instructions
end
```

This version works fine for most purposes, e.g.,

```
my.repeat 5 [print "hello]
```

But it doesn't work if the instructions to be carried out include `OUTPUT`, `STOP`, or `LOCAL`. For example, consider this procedure:

```
to example
  print [Guess my secret word. You get three guesses.]
  repeat 3 [type "|?? | ~
            if readword = "secret [pr "Right! stop]]
  print [Sorry, the word was "secret"!]
```

```
end
```

This procedure works as written, but if `MY.REPEAT` is used instead of `REPEAT`, it won't work because the `STOP` will stop `MY.REPEAT` instead of stopping `EXAMPLE` as desired.

The solution is to make `MY.REPEAT` a macro. Instead of actually carrying out the computation, a macro must return a list containing Logo instructions. The contents of that list are evaluated as if they appeared in place of the call to the macro. Here's a macro version of `REPEAT`:

```
.macro my.repeat :num :instructions
  if :num=0 [output []]
  output sentence :instructions ~
                (list "my.repeat :num-1 :instructions)
end
```

Every macro is an operation — it must always output something. Even in the base case, `MY.REPEAT` outputs an empty instruction list. To show how `MY.REPEAT` works, let's take the example


```
my.repeat 5 [print "hello]
```

For this example, MY.REPEAT will output the instruction list

```
[print "hello my.repeat 4 [print "hello]]
```

Logo then executes these instructions in place of the original invocation of MY.REPEAT; this prints `hello` once and invokes another repetition.

The technique just shown, although fairly easy to understand, has the defect of slowness because each repetition has to construct an instruction list for evaluation. Another approach is to make MY.REPEAT a macro that works just like the non-macro version unless the instructions to be repeated include OUTPUT or STOP:

```
.macro my.repeat :num :instructions
catch "repeat.catchtag ~
  [op repeat.done runresult [repeat1 :num :instructions]]
op []
end

to repeat1 :num :instructions
if :num=0 [throw "repeat.catchtag]
run :instructions
.maybeoutput repeat1 :num-1 :instructions
end

to repeat.done :repeat.result
if empty? :repeat.result [op [stop]]
op list "output quoted first :repeat.result
end
```

If the instructions do not include STOP or OUTPUT, then REPEAT1 will reach its base case and invoke THROW. As a result, MY.REPEAT's last instruction line will output an empty list, so the evaluation of the macro result by the caller will do nothing. But if a STOP or OUTPUT happens, then REPEAT.DONE will output a STOP or OUTPUT instruction that will be executed in the caller's context.

The macro-defining commands have names starting with a dot because macros are an advanced feature of Logo; it's easy to get in trouble by defining a macro that doesn't terminate, or by failing to construct the instruction list properly.

Lisp users should note that Logo macros are *not* special forms. That is, the inputs to the macro are evaluated normally, as they would be for any other Logo procedure. It's only the output from the macro that's handled unusually.

Here's another example:

```
.macro localmake :name :value
output (list "local      ~
           word "" :name  ~
           "apply       ~)
```

```

        "make      ~
      (list :name :value))
    end

```

It's used this way:

```

to try
  localmake "garply "hello
  print :garply
end

```

LOCALMAKE outputs the list

```
[local "garply apply "make [garply hello]]
```

The reason for the use of **APPLY** is to avoid having to decide whether or not the second input to **MAKE** requires a quotation mark before it. (In this case it would — **MAKE "GARPLY "HELLO** — but the quotation mark would be wrong if the value were a list.)

It's often convenient to use the `'` function to construct the instruction list:

```

.macro localmake :name :value
  op '[local ,[word "" :name] apply "make [,[:name] ,[:value]]]
end

```

On the other hand, `'` is pretty slow, since it's tree recursive and written in Logo.

See [TO], page 49 , [DEFINE], page 50 , [APPLY], page 76 , [STOP], page 69 , [OUTPUT], page 69 .

.defmacro

See [dMACRO], page 83 .

macrop

```

MACROP name
MACRO? name

```

outputs **TRUE** if its input is the name of a macro.

macroexpand

```
MACROEXPAND expr (library procedure)
```

takes as its input a Logo expression that invokes a macro (that is, one that begins with the name of a macro) and outputs the the Logo expression into which the macro would translate the input expression.

```

.macro localmake :name :value
  op '[local ,[word "" :name] apply "make [,[:name] ,[:value]]]
end

? show macroexpand [localmake "pi 3.14159]
[local "pi apply "make [pi 3.14159]]

```


10 Error Processing

If an error occurs, Logo takes the following steps. First, if there is an available variable named **ERRACT**, Logo takes its value as an instructionlist and runs the instructions. The operation **ERROR** may be used within the instructions (once) to examine the error condition. If the instructionlist invokes **PAUSE**, the error message is printed before the pause happens. Certain errors are *recoverable*; for one of those errors, if the instructionlist outputs a value, that value is used in place of the expression that caused the error. (If **ERRACT** invokes **PAUSE** and the user then invokes **CONTINUE** with an input, that input becomes the output from **PAUSE** and therefore the output from the **ERRACT** instructionlist.)

It is possible for an **ERRACT** instructionlist to produce an inappropriate value or no value where one is needed. As a result, the same error condition could recur forever because of this mechanism. To avoid that danger, if the same error condition occurs twice in a row from an **ERRACT** instructionlist without user interaction, the message ‘**Erract loop**’ is printed and control returns to toplevel. “Without user interaction” means that if **ERRACT** invokes **PAUSE** and the user provides an incorrect value, this loop prevention mechanism does not take effect and the user gets to try again.

During the running of the **ERRACT** instructionlist, **ERRACT** is locally unbound, so an error in the **ERRACT** instructions themselves will not cause a loop. In particular, an error during a pause will not cause a pause-within-a-pause unless the user reassigns the value [**PAUSE**] to **ERRACT** during the pause. But such an error will not return to toplevel; it will remain within the original pause loop.

If there is no available **ERRACT** value, Logo handles the error by generating an internal **THROW "ERROR**. (A user program can also generate an error condition deliberately by invoking **THROW**.) If this throw is not caught by a **CATCH "ERROR** in the user program, it is eventually caught either by the toplevel instruction loop or by a pause loop, which prints the error message. An invocation of **CATCH "ERROR** in a user program locally unbinds **ERRACT**, so the effect is that whichever of **ERRACT** and **CATCH "ERROR** is more local will take precedence.

If a floating point overflow occurs during an arithmetic operation, or a two-input mathematical function (like **POWER**) is invoked with an illegal combination of inputs, the ‘**doesn’t like**’ message refers to the second operand, but should be taken as meaning the combination.

See [**ERRACT**], page 89 , [**THROW**], page 69 , [**ERROR**], page 70 , [**CATCH**], page 69 , [**PAUSE**], page 70 , [**CONTINUE**], page 70 .

10.1 Error Codes

Here are the numeric codes that appear as the first member of the list output by **ERROR** when an error is caught, with the corresponding messages. Some messages may have two different codes depending on whether or not the error is recoverable (that is, a substitute value can be provided through the **ERRACT** mechanism) in the specific context. Some messages are warnings rather than errors; these will not be caught. Errors 0 and 32 are so bad that Logo exits immediately.

0 Fatal internal error (can’t be caught)

```
1 Out of memory
2 Stack overflow
3 Turtle out of bounds
4 proc doesn't like datum as input (not recoverable)
5 proc didn't output to proc
6 Not enough inputs to proc
7 proc doesn't like datum as input (recoverable)
8 Too much inside ()'s
9 You don't say what to do with datum
10 ')' not found
11 var has no value
12 Unexpected ')'
13 I don't know how to proc (recoverable)
14 Can't find catch tag for throwtag
15 proc is already defined
16 Stopped
17 Already dribbling
18 File system error
19 Assuming you mean IFELSE, not IF (warning only)
20 var shadowed by local in procedure call (warning only)
21 Throw "Error
22 proc is a primitive
23 Can't use T0 inside a procedure
24 I don't know how to proc (not recoverable)
25 IFTRUE/IFFALSE without TEST
26 Unexpected ']'
27 Unexpected '}'
28 Couldn't initialize graphics
29 Macro returned value instead of a list
30 You don't say what to do with value
31 Can only use STOP or OUTPUT inside a procedure
32 APPLY doesn't like badthing as input
33 END inside multi-line instruction
34 Really out of memory (can't be caught)
35 user-generated error message (THROW "ERROR message)
36 END inside multi-line instruction
37 Bad default expression for optional input: expr
38 Can't use OUTPUT or STOP inside RUNRESULT
39 Assuming you meant 'FD 100', not FD100 (or similar)
40 I can't open file filename
41 File filename already open
42 File filename not open
43 Runlist [expr expr] has more than one expression.
```

11 Special Variables

Logo takes special action if any of the following variable names exists. They follow the normal scoping rules, so a procedure can locally set one of them to limit the scope of its effect. Initially, no variables exist except for `ALLOWGETSET`, `CASEIGNOREDP`, and `UNBURYONEDIT`, which are `TRUE` and buried.

allowgetset

`ALLOWGETSET` (variable)

if `TRUE`, indicates that an attempt to use a procedure that doesn't exist should be taken as an implicit getter or setter procedure (setter if the first three letters of the name are `SET`) for a variable of the same name (without the `SET` if appropriate).

buttonact

`BUTTONACT` (variable)

if nonempty, should be an instruction list that will be evaluated whenever a mouse button is pressed. Note that the user may have released the button before the instructions are evaluated. `BUTTON` will still output which button was most recently pressed. `CLICKPOS` will output the position of the mouse cursor at the moment the button was pressed; this may be different from `MOUSEPOS` if the user moves the mouse after clicking.

Note that it's possible for the user to press a button during the evaluation of the instruction list. If this would confuse your program, prevent it by temporarily setting `BUTTONACT` to the empty list. One easy way to do that is the following:

```
make "buttonact [button.action]

to button.action [:buttonact []]
... ; whatever you want the button to do
end
```

caseignoredp

`CASEIGNOREDP` (variable)

if `TRUE`, indicates that lower case and upper case letters should be considered equal by `EQUALP`, `BEFOREP`, `MEMBERP`, etc. Logo initially makes this variable `TRUE`, and buries it.

See `[EQUALP]`, page 14 , `[BEFOREP]`, page 15 , `[MEMBERP]`, page 15 .

commandline

`COMMANDLINE` (variable)

contains any text appearing after a hyphen on the command line used to start Logo.

erract

`ERRACT` (variable)

an instructionlist that will be run in the event of an error. Typically has the value [PAUSE] to allow interactive debugging.

See [PAUSE], page 70 .

fullprintp

FULLPRINTP (variable)

if TRUE, then words that were created using backslash or vertical bar (to include characters that would otherwise not be treated as part of a word) are printed with the backslashes or vertical bars shown, so that the printed result could be re-read by Logo to produce the same value. If FULLPRINTP is TRUE then the empty word (however it was created) prints as | |. (Otherwise it prints as nothing at all.)

keyact

KEYACT (variable)

if nonempty, should be an instruction list that will be evaluated whenever a key is pressed on the keyboard. The instruction list can use READCHAR to find out what key was pressed. Note that only keys that produce characters qualify; pressing SHIFT or CONTROL alone will not cause KEYACT to be evaluated.

Note that it's possible for the user to press a key during the evaluation of the instruction list. If this would confuse your program, prevent it by temporarily setting KEYACT to the empty list. One easy way to do that is the following:

```
make "keyact [key.action]

to key.action [:keyact []]
... ; whatever you want the key to do
end
```

loadnoisily

LOADNOISILY (variable)

if TRUE, prints the names of procedures defined when loading from a file (including the temporary file made by EDIT).

See [EDIT], page 61 .

printdepthlimit

PRINTDEPTHLIMIT (variable)

if a nonnegative integer, indicates the maximum depth of sublist structure that will be printed by PRINT, etc.

See [PRINT], page 19 .

printwidthlimit

PRINTWIDTHLIMIT (variable)

if a nonnegative integer, indicates the maximum number of members in any one list that will be printed by `PRINT`, etc.

See `[PRINT]`, page 19 .

redefp

`REDEFP` (variable)

if `TRUE`, allows primitives to be erased (`ERASE`) or redefined (`COPYDEF`).

See `[ERASE]`, page 57 , `[COPYDEF]`, page 51 .

startup

`STARTUP` (variable)

if assigned a list value in a file loaded by `LOAD`, that value is run as an instructionlist after the loading.

See `[LOAD]`, page 63 .

unburyonedit

`UNBURYONEDIT` (variable)

if `TRUE`, causes any procedure defined during `EDIT` or `LOAD` to be unburied, so that it will be saved by a later `SAVE`. Files that want to define and bury procedures must do it in that order.

See `[EDIT]`, page 61 , See `[LOAD]`, page 63 , See `[SAVE]`, page 62 .

usealternatenames

`USEALTERNATENAMES` (variable)

if `TRUE`, causes Logo to generate non-English words (from the `Messages` file) instead of `TRUE`, `FALSE`, `END`, etc.

Logo provides the following buried variables that can be used by programs:

logoversion

`LOGOVERSION` (variable)

a real number indicating the Logo version number, e.g., 5.5

logoplatform

`LOGOPLATFORM` (variable)

one of the following words: `wxWidgets`, `X11`, `Windows`, or `Unix-nographics`.

12 Internationalization

Berkeley Logo has limited support for non-English-speaking users. Alas, there is no Unicode support, and high-bit-on ASCII codes work in some contexts but not others.

If you want to translate Berkeley Logo for use with another language, there are three main things you have to do:

1. Primitive names
2. Error (and other) messages
3. Documentation

For primitive names, the easiest thing is to provide a startup file that defines aliases for the English primitive names, using `COPYDEF`:

```
COPYDEF "AVANT "FORWARD
```

This should take care of it, unless your language's name for one primitive is spelled like the English name of a different primitive. In that case you have to turn `REDEF` on and be sure to copy the non-conflicting name before overwriting the conflicting one!

"Primitives" that are actually in the Logo library, of course, can just be replaced or augmented with native-language-named Logo procedures and filenames.

Of course Logo programs will still not look like your native language if the word order is dramatically different, especially if you don't put verbs before their objects.

For error messages, there is a file named `Messages` in the `logolib` directory with texts of messages, one per line. You can replace this with a file for your own language. Do not add, delete, or reorder lines; Logo finds messages by line number. The sequences `%p`, `%s`, and `%t` in these messages represent variable parts of the message and should not be translated. (`%p` PRINTs the variable part, while `%s` SHOWs it – that is, the difference is about whether or not brackets are shown surrounding a list. `%t` means that the variable part is a C text string rather than a Logo object.) If you want to change the order of two variable parts (no reorderable message has more than two), you would for example replace the line

```
%p doesn't like %s as input
```

with

```
%+s is a lousy input to %p
```

The plus sign tells the message printer to reverse the order; you must reverse the order of `%p` and `%s`, if both are used, to match. The plus sign goes just after the first percent sign in the message, which might not be at the beginning of the line. The sequence `\n` in a message represents a newline; don't be fooled into thinking that the `n` is part of the following word.

Some messages appear twice in the file; this isn't a mistake. The two spaces before `to` in `I don't know \ to` aren't a mistake either. The message containing just `%p` is for user-provided error messages in `THROW "ERROR`. The message `"\ \ in %s\n%s"` is the part of all error messages that indicates where the error occurred if it was inside a procedure; you might want to change the word `in` to your language. `%s defined\n` is what `LOAD` prints

for each procedure defined if the variable `LOADNOISILY` is `TRUE`. `"to %p\nend\n\n"` is what `EDIT` puts in the temporary file if you ask to edit a procedure that isn't already defined.

Also in the `Messages` file are lines containing only one word each; the first of these is the word `true`. Some of these words are recognized by Logo in user input; some are generated by Logo; some are both. For example, the words `TRUE` and `FALSE` are recognized as Boolean values by `IF` and `IFELSE`, and are also generated by Logo as outputs from the primitive predicates such as `EQUALP`. The word `END` is recognized as the end of a procedure definition, and may be generated when Logo reconstructs a procedure body for `PO` or `EDIT`. I've used capital letters in this paragraph for easier reading, but the words in the `Messages` file should be in lower case.

If you replace these with non-English words, Logo will *recognize* both the English names and your alternate names. For example, if you replace the word `true` with `vrai` then Logo will understand both of these:

```
IF "TRUE [PRINT "YES]
IF "VRAI [PRINT "YES]
```

The variable `UseAlternateNames` determines whether Logo will *generate* other-language names – for example, whether predicate functions return the other-language alternates for `TRUE` and `FALSE`. This variable is `FALSE` by default, meaning that the English words will be generated.

You might wish to have English-named predicate functions generate English `TRUE` and `FALSE`, while other-language-named predicates generate the alternate words. This can be done by leaving `UseAlternateNames` false, and instead of defining the other-language predicates with `COPYDEF`, do it this way:

```
to french.boolean :bool
  if equalp :bool "true [output "vrai]
  if equalp :bool "false [output "faux]
  output :bool ; shouldn't happen
end

to make.french.predicate :french :english :arity
  define :french '[[[inputs] ,[:arity]]
    [output french.boolean
      apply ,[word "" :english] :inputs]]
end

? make.french.predicate "egal? "equal? 2
? pr egal? 3 4
faux
? pr egal? 4 4
vrai
? pr equal? 3 4
false
? pr equal? 4 4
```

`true`

The third input to `make.french.predicate` is the number of inputs that the predicate expects. This solution isn't quite perfect because the infix predicates (`=`, `<`, `>`) will still output in English. If you want them to generate alternate-language words, set `UseAlternateNames` to `TRUE` instead.

Some of the words in this section of the `Messages` file are names of Logo primitives (`OUTPUT`, `STOP`, `GOTO`, `TAG`, `IF`, `IFELSE`, `TO`, `.MACRO`). To translate these names, you must use `COPYDEF` as described earlier, in addition to changing the names in `Messages`. You should be consistent in these two steps. Don't forget the period in `.macro`!

For documentation, there are two kinds: this manual and the help files. The latter are generated automatically from this manual if you have a Unix system, so in that case you need only translate this manual, maintaining the format. (The automatic helpfile generator notices things like capital letters, tabs, hyphens, and equal signs at the beginnings of lines.) The program `makefile.c` may require modification because a few of the primitive names are special cases (e.g., `LOG10` is the only name with digits included).

If you don't have Unix tools, you can just translate each helpfile individually. A period in a primitive name is represented as a `D` in the filename; there are no files for question marks because the `HELP` command looks for the file named after the corresponding primitive that ends in `P`.

INDEX

*

* 29

+

+ 29

-

- 29

.

.defmacro 83
 .eq 15
 .macro 83
 .maybeoutput 71
 .setbf 13
 .setfirst 13
 .setitem 13
 .setsegmentsize 65

/

/ 29

<

< 32
 <= 32
 <> 15

=

= 14

>

> 32
 >= 32

‘

‘ 72

A

allopen 23
 allowgetset 89
 AllowGetSet 4
 and 35
 apply 76
 arc 39
 arctan 31

arity 55
 array 9
 array? 14
 arrayp 14
 arraytolist 10
 ascii 16
 ashift 34

B

back 37
 background 46
 before? 15
 beforep 15
 bf 11
 bfs 11
 bg 46
 bitand 33
 bitnot 34
 bitor 33
 bitxor 33
 bk 37
 bl 12
 buried 54
 buried? 60
 buriedp 60
 bury 59
 buryall 59
 buryname 59
 butfirst 11
 butfirsts 11
 butlast 12
 button 47
 button? 47
 buttonact 89
 buttonp 47
 bye 71

C

cascade 79
 cascade.2 81
 case 74
 case-insensitive 6
 caseignoredp 89
 catch 69
 char 17
 clean 40
 clearscreen 40
 cleartext 26
 clickpos 47
 close 23
 closeall 23
 co 70
 combine 10

commandline	89
comments	6
Computer_Science_Logo_Style	1
cond	74
contents	54
continue	70
copydef	51
Copyright	1
cos	31
count	16
crossmap	79
cs	40
csload	63
ct	26
cursor	26

D

decreasefont	27
define	50
defined?	54
definedp	54
delimiters	6
dequeue	14
difference	29
do.until	73
do.while	73
dribble	24

E

ed	61
edall	62
edit	61
editfile	61
editor	61
edn	62
edns	62
edpl	62
edpls	62
edps	62
empty?	14
empty?	14
eof?	25
eofp	25
epsdict	47
equal?	14
equalp	14
er	57
erall	58
erase	57
erasefile	23
erf	23
ern	58
erns	58
erpl	58
erpls	58
erps	58

erract	89
error	70
errors	87
exp	30

F

fd	37
fence	40
file?	26
filep	26
fill	41
filled	41
filter	78
find	78
first	10
firsts	11
font	28
for	72
foreach	76
forever	67
form	33
forward	37
fput	9
fs	41
fullprintp	90
fullscreen	41
fulltext	51

G

gc	64
gensym	10
getter	2
global	52
goto	71
gprop	53
greater?	32
greaterequal?	32
greaterequalp	32
greaterp	32

H

heading	39
help	63
hideturtle	40
home	38
ht	40

I

if	68
ifelse	68
iff	68
iffalse	68
ift	68
iftrue	68

ignore	72
increasefont	27
int	30
invoke	76
iseq	31
item	12

K

key?	26
keyact	90
keyp	26

L

label	41
labelsize	43
last	11
leaving ucblgo	5
left	38
less?	32
lessequal?	32
lessequalp	32
lessp	32
line-continuation	6
list	9
list?	14
listp	14
listtoarray	10
ln	30
load	63
loadnoisily	90
loadpict	46
local	52
localmake	52
log10	30
logohelp	63
logoplatform	91
logoversion	91
lowercase	17
lput	9
lshift	34
lt	38

M

macro?	85
macroexpand	85
macrop	85
make	51
map	77
map.se	77
mdarray	10
mditem	12
mdsetitem	13
member	17
member?	15
memberp	15

minus	29
modulo	30
mousepos	47

N

name	51
name?	54
namelist	55
namep	54
names	55
nodes	56
nodribble	24
norefresh	42
not	35
notequal?	15
notequalp	15
number?	16
numberp	16

O

op	69
openappend	23
openread	22
openupdate	23
openwrite	22
or	35
output	69

P

palette	46
parse	18
pause	70
pc	45
pd	43
pe	44
pen	46
pencolor	45
pendown	43
pendown?	45
pendownp	45
penerase	44
penmode	45
penpaint	44
penpattern	46
penreverse	44
pensize	46
penup	43
pick	12
plist	53
plist?	54
plistp	54
plists	55
pllist	55
po	56
poall	56

pon	57
pons	56
pop	13
popl	57
popls	57
pops	56
pos	39
pot	57
pots	57
power	30
pprop	53
ppt	44
pr	19
prefix	22
primitive?	53
primitivep	53
primitives	55
print	19
printdepthlimit	90
printout	56
printwidthlimit	90
procedure?	53
procedurep	53
procedures	55
product	29
pu	43
push	13
px	44

Q

queue	14
quoted	12
quotient	29

R

radarctan	31
radcos	31
radsin	31
random	32
rawascii	16
rc	21
rcl	21
readchar	21
readchars	21
reader	25
readlist	20
readpos	25
readrawline	20
readword	20
redefp	91
reduce	78
refresh	42
remainder	30
remdup	12
remove	12
remprop	53

repcount	68
repeat	67
rerandom	33
reverse	10
right	38
rl	20
round	30
rseq	31
rt	38
run	67
runparse	18
runparsing	6
runresult	67
rw	20

S

save	62
savel	63
savepict	46
screenmode	43
scrunch	39
scrunch.dat	42
se	9
sentence	9
setbackground	45
setbg	45
setcslsloc	64
setcursor	26
seteditor	64
setfont	28
seth	38
setheading	38
sethelploc	64
setitem	12
setlabelheight	41
setlibloc	64
setmargins	26
setpalette	44
setpc	44
setpen	45
setpencolor	44
setpenpattern	45
setpensize	44
setpos	38
setprefix	22
setread	24
setreadpos	25
setscrunch	42
settc	27
settemploc	64
setter	2
settextcolor	27
settextsize	27
setwrite	24
setwritepos	25
setx	38
setxy	38

sety	38
shell	21
show	20
shown?	43
shownp	43
showturtle	39
sin	31
splitscreen	42
sqrt	30
ss	42
st	39
standout	17
starting <code>ucblogo</code>	5
startup	91
step	60
stepped	54
stepped?	61
steppedp	61
stop	69
substring?	16
substringp	16
sum	29

T

tag	72
temp	61
template	74
test	68
text	51
textscreen	41
textsize	27
thing	52
throw	69
to	49
towards	39
trace	60
traced	54
traced?	60
tracedp	60

transfer	81
turtlemode	43
type	19

U

unbury	59
unburyall	59
unburyname	59
unburyonedit	91
unstep	60
until	73
untrace	60
uppercase	17
usealternatenames	91

V

vbarred?	16
vbarredp	16

W

wait	71
while	73
window	40
word	9
wordp	14
wrap	40
writepos	25
writer	25

X

xcor	39
------------	----

Y

ycor	39
------------	----

